

Enchufes Rápidos

Serie INOXIDABLE AISI 316 L



Escala 1:1



Ø Nominal  
7,8 mm.

Perfil EUROPEO  
INOXIDABLE



Presión ejercicio 0 - 16 bar



1907/2006  
REACH

2011/65/CE  
RoHS

PED  
2014/68/UE

SILICON  
FREE

Temperatura:  
Mínima: -15°C  
Máxima: +200°C

Enchufes



63190

Enchufe macho short (FKM)



Código	Ref.	Pack	■
63190 1/4	6319000002	2	
63190 3/8	6319000003	2	
63190 1/2	6319000004	2	

63192

Enchufe hembra (FKM)



Código	Ref.	Pack	■
63192 1/4	6319200002	2	
63192 3/8	6319200003	2	
63192 1/2	6319200004	2	

Adaptadores



63260

Adaptador perfil europeo macho short (FKM) DN 7,8




Código	Ref.	Pack	■
63260 1/4	6326000002	2	
63260 3/8	6326000003	2	
63260 1/2	6326000004	2	

63262

Adaptador perfil europeo hembra DN 7,8



Código	Ref.	Pack	■
63262 1/4	6326200440300	2	
63262 3/8	6326200440400	2	
63262 1/2	6326200440500	2	



Escala 1:1



Ø Nominal  
7,8 mm.

Multipresa

Compatible

Juntas FKM

AISI 316 L  
Certificado

**ISO 6150 B12 DN 5,5**

**CAUDAL**  
6 bar Δ 1  
900 NI/min.  
6 bar Δ 0.5  
700 NI/min.  
6 bar Δ 0\*  
1450 NI/min.  
\* Escape libre

**Perfil ITALIANO DN 5**

**CAUDAL**  
6 bar Δ 1  
800 NI/min.  
6 bar Δ 0.5  
700 NI/min.  
6 bar Δ 0\*  
1300 NI/min.  
\* Escape libre



**Perfil EUROPEO DN 7,8**

**CAUDAL**  
6 bar Δ 1  
1900 NI/min.  
6 bar Δ 0.5  
1300 NI/min.  
6 bar Δ 0\*  
2450 NI/min.  
\* Escape libre

**Perfil SUECO DN 5,5**

**CAUDAL**  
6 bar Δ 1  
1100 NI/min.  
6 bar Δ 0.5  
750 NI/min.  
6 bar Δ 0\*  
1600 NI/min.  
\* Escape libre