

Poliuretani speciali / Special polyurethanes



14H / AVOTOP 95 Shore A

Ruota con rivestimento in poliuretano AVOTOP 95 Shore A per tutti gli ambienti e per tutte le condizioni di utilizzo più gravose come velocità, carichi e frequenza di utilizzo. Nucleo in ghisa meccanica di qualità, verniciata color nero. Mozzo su cuscinetti a sfere schermati assemblati con distanziale centrale. Possono essere assemblate con tutti i tipi di supporti.

Wheel with polyurethane AVOTOP 95 Shore A for all environments and for all operating conditions more severe as speed, load and frequency of use. Quality cast iron center, painted black. Hub on shielded ball bearings assembled with the central spacer. They can be assembled with all types of AVO castors.



14W / AVOWATER 91 Shore A

Ruota con rivestimento in poliuretano AVOWATER 91 Shore A per ambienti ad alto tasso di umidità ed a contatto con l'acqua. Nucleo in ghisa meccanica di qualità, verniciata color nero. Mozzo su cuscinetti a sfere schermati assemblati con distanziale centrale. Possono essere assemblate con tutti i tipi di supporti.

Wheel coated with AVOWATER polyurethane thread 91 Shore A for environments with a high amount of humidity and in contact with water. Black painted, mechanical cast iron centre. Hub on shielded ball bearings assembled with central spacer. Special castors are available for any needs.




14V / AVOBIO 91 Shore A

Ruota con rivestimento in poliuretano AVOBIO 91 Shore A per impianti di depurazione. Nucleo in ghisa meccanica di qualità, verniciata color nero. Mozzo su cuscinetti a sfere schermati assemblati con distanziale centrale. Possono essere assemblate con tutti i tipi di supporti.

Wheel coated with AVOBIO polyurethane thread 91 Shore A for purification plants. Black painted, mechanical cast iron centre. Hub on shielded ball bearings assembled with central spacer. Special castors are available for any needs.

** Spessore poliuretano 37mm. Con ingrassatore. / ** Polyurethane thickness 37mm. With greaser.

				
150x40	40	20	47x14	500
150x40	40	25	47x12	500
150x50	60	20	47x14	650
150x50	50	20-25	52x15	650
150x50	60	25	52x15	650
150x60	60	25	52x15	650
175x35	35	20	47x14	600
175x40	40	20	47x14	650
200x40	40	20	47x14	800
200x45	45	25	52x15	1000
200x50	60	20-25	52x15	1100
200x80	80	30	62x16	1600
250x50	60	25	52x15	1150
250x60	60	25	52x15	1400
250x80**	80	30	62x16	1800
300x70	70	30	62x16	2200
300x100	100	40	80x18	2800
400x100	100	40	80x18	4000
400x125	125	40	80x18	4600
500x100	100	50	90x20	4500
700x100	100	50	90x20	4500

Poliuretani speciali / *Special polyurethanes*



18AH / AVOTOP 95 Shore A

Ruota con rivestimento in poliuretano AVOTOP 95 Shore A per tutti gli ambienti e per tutte le condizioni di utilizzo più gravose come velocità, carichi e frequenza di utilizzo. Nucleo in alluminio. Mozzo su cuscinetti a sfere schermati assemblati con distanziale centrale. Possono essere assemblate con tutti i tipi di supporti.

Wheel with polyurethane AVOTOP 95 Shore A for all environments and for all operating conditions more severe as speed, load and frequency of use. Aluminium center, hub on shielded ball bearings are assembled with the central spacer. They can be assembled with all types of AVO castors.



18AW / AVOWATER 91 Shore A

Ruota con rivestimento in poliuretano AVOWATER 91 Shore A per ambienti ad alto tasso di umidità ed a contatto con l'acqua. Nucleo in alluminio. Mozzo su cuscinetti a sfere schermati assemblati con distanziale centrale. Possono essere assemblate con tutti i tipi di supporti.

Wheel coated with AVOWATER polyurethane thread 91 Shore A for environments with a high amount of humidity and in contact with water. Wheel centre in aluminium. Hub on shielded ball bearings assembled with central spacer. Special castors are available for any needs.