














30 | Range of accessories

Product and system overview at a glance.














The Click & Clean System is not only perfectly thought through, it is also really easy to use: connect the dust extractor and start working! This overview offers you a helpful guide to the tools, part numbers and extras such as adapters and accessories. You will also find mobile solutions for individual systems.

Product	Machine models	Applies to part no.	Required accessories for dust extraction
Rotary hammers	GBH 2-20 D GBH 2-24 D GBH 2-24 DF GBH 2-26 DRE GBH 2-26 DFR GBH 2-28 DV GBH 2-28 DFV GBH 3-28 DRE GBH 3-28 DFR GBH 18 V-EC GBH 36 V-LI GBH 36 VF-LI	0 611 25A ... 0 611 2A0 ... 0 611 2A0 ... 0 611 253 ... 0 611 254 ... 0 611 267 ... 0 611 267 ... 0 611 23A ... 0 611 24A ... 0 611 904 ... 0 611.900 ... 0 611 901 ...	* Dust extraction device GDE 16 Plus Drilling diameter 4–16 mm 1 600 A00 15Z * GDE 16 Plus available from autumn 2013
	GBH 2-23 REA	0 611 250 5..	2 607 002 611
	GBH 11 DE	0 611 245 7 ...	Dust extraction attachment Drilling diameter 16–40 mm 1 618 190 009
Diamond drills	GDB 1600 WE GDB 2500 WE	0 601 188 ... 0 601 18P ...	Drill stand 0 601 190 025
Impact drills	GSB 16 RE GSB 18-2 RE GSB 19-2 RE GSB 20-2 RE / RET GSB 22-2 RE / RCE GSB 21-2 RE / RCT	0 601 14E ... 0 601 17A ... 0 601 17B ... 0 601 184 ... 0 601 146 ... 0 601 19C ...	Dust extraction attachment set Drilling diameter 4–20 mm 1 607 000 173
	GSB 19-2 REA	0 601 17C 5..	
Wall chasers and slot cutters	GNF 20 CA GNF 35 CA GNF 65 A	0 601 612 ... 0 601 621 ... 0 601 368 ...	
670 W - 1400 W angle grinders	GWS 5-100 ... GWS 5-115 ... GWS 6-100 ... GWS 6-115 ... GWS 6-125 ... GWS 850 ...	0601 375 0 ... – 0 601 377 9 ...	Quick adjustment Cutting guide with dust extraction outlet 1 619 P06 514
	GWS 7-115 GWS 9-125 GWS 10-125 C GWS 10-125 CE GWS 14-125 C GWS 14-125 CE	0 601 80 ...	Clamp fitting/Lever Cutting guide with dust extraction outlet 1 605 510 291
	GWS 8-115 GWS 8-125 GWS 10-125 GWS 11-125 CI / CIE GWS 14-125 CI / CIE / CIT	0 601 820 ... – 0 601 825 ...	Quick adjustment Cutting guide with dust extraction outlet 2 605 510 264
	GWS 8-115 / Z GWS 8-125 GWS 10-125 / Z GWS 11-125 CI / CIE / CIH GWS 14-125 CI / CIE / CIT GWS 15-125 CIH / CIEH / CITH	3 601 H ...	Quick adjustment Cutting guide with dust extraction outlet 2 605 510 264



Product	Machine models	Applies to part no.	Required accessories for dust extraction	
	GWS 7-115 GWS 7-125 GWS 9-125 GWS 10-125 C GWS 10-125 CE GWS 14-125 C GWS 14-125 CE GWS 1000	0 601 80 ... - 0 601 805 ...		Clamp fitting/Lever Cutting guide with dust extraction outlet 1 605 510 291
	GWS 14-150 CI GWS 15-150 CIH	3 601 H ...		Quick adjustment Cutting guide with dust extraction outlet 2 605 510 265
	GWS 14-150 C	0 601 806 ...		Clamp fitting/Lever Cutting guide with dust extraction outlet 1 605 510 292
Cordless angle grinders	GWS 18 V-LI GWS 18-125 V-LI	0 601 93A 30A 0 601 93A 30B		Dust extraction protective guard 1 619 P06 514 Dust extraction adapter 1 600 793 007
2000 W – 2600 W angle grinders 	GWS 20-180 / H / JH GWS 21-180 HV / JHV GWS 22-180 H / JH GWS 24-180 BX / JBX / JVX GWS 24-180 H / BV / JBV GWS 24-180 H / JH GWS 26-180 H / JH GWS 26-180 B	0 601 849 ... 0 601 853 ... 0 601 883 ... 0 601 855...		Cutting guide with dust extraction outlet 1 605 510 179
	GWS 20-230 H / J / JH GWS 21-230 HV / JHV GWS 22-230 H / JH GWS 24-230 H / JH GWS 26-230 JH	0 601 852 ... 0 601 854 ... 0 601 884 ... 0 601 856 ...		Cutting guide with dust extraction outlet 1 605 510 180
	GWS 22-180 LVI GWS 24-180 LVI GWS 26-180 JBV (3 601 H55 U..) GWS 26-180 LVI	0 601 890 ... 0 601 892 ... 0 601 894 ...		Cutting guide with dust extraction outlet 2 602 025 284
Special cut-off grinders 	GWS 22-230 LVI GWS 24-230 LVI GWS 24-230 JBX / JVX GWS 26-230 BV (3 601 H56 S..) GWS 26-230 JBV (3 601 H56 U..) GWS 26-230 (3 601 H56 5..) GWS 26-230 LVI	0 601 891 ... 0 601 893 ... 0 601 864 ... 0 601 895 ...		Cutting guide with dust extraction outlet 2 602 025 285
	Concrete grinder 	GWS 24-300 GWS 24-300 J	0 601 364 8..	
	GBR 14 CA	0 601 773 ...		

32 | Range of accessories

Product	Machine models	Applies to part no.	Required accessories for dust extraction	
Jigsaws 	GST 14,4 V-LI GST 18 V-LI GST 140 CE GST 140 BCE	0 601 58J 404 0 601 58J 305 0 601 514 000 0 601 515 000	 Dust extraction adapter 2 605 510 301	
	GST 90 E GST 90 BE	0 601 58G ... 0 601 58F 000		
	GST 150 CE GST 150 BCE	0 601 512 ... 0 601 513 ...		
Power hand saw 	GFZ 16-35 AC	0 601 637 7..		
Plunge saw 	GKT 55 GCE	0 601 675 5..		
Hand-held circular saws 	GKS 55 GKS 55 GCE GKS 65 GKS 65 G GKS 65 GCE GKS 85 GKS 85 G GKS 160 GKS 190 GKS 18 V-LI GKS 36 V-LI	0 601 664 0.. 0 601 664 9.. 0 601 667 0.. 0 601 668 9.. 0 601 668 9.. 0 601 668 9.. 0 601 57A 0.. 0 601 97A 9.. 0 601 670 0.. 0 601 623 0.. 0 601 66H 0.. 0 601 645 R..		
	Palm router 	GKF 600	0 601 60A 1..	
	Routers 	GOF 2000 CE	0 601 619 7..	
		GOF 1600 CE	0 601 624 0..	
		GMF 1600 CE	0 601 624 0..	
		GOF 900 CE	0 601 614 6..	
	Biscuit jointer 	GFF 22 A	0 601 620 0..	 Adapter 1 600 499 005
	Multitool 	GOP 10,8 V-LI GOP 250 CE	0 601 858 00J 0 601 230 000	 Dust extraction adapter 2 608 190 054
		GOP 14,4 V-EC GOP 18 V-EC	0 601 8B0 101 0 601 8B0 000	 Dust extraction adapter 2 608 190 060
GOP 300 SCE		0 601 230 502	 Dust extraction adapter 2 608 190 056	





Product	Machine models	Applies to part no.	Required accessories for dust extraction	Mobile dust solution
 Planers	GHO 14,4 V-LI GHO 18 V-LI GHO 15-82 GHO 26-82 GHO 40-82 C	0 601 5A0 402 0 601 5A0 303 0 601 594 0.. 0 601 594 3.. 0 601 594 7..		 Dust bag 2 605 411 035
 Belt sander	GBS 75 AE Set	0 601 274 7..	 Adapter 2 600 499 045	 Dust bag 1 605 411 025
 Orbital sanders	GSS 23 AE	0 601 070 7..		 Microfilter box 2 605 411 233
	GSS 230 AVE GSS 280 AVE	0 601 292 8.. 0 601 292 9..		
	GSS 140 A	0 601 297 0..	 Adapter 2 600 306 007	 Microfilter box 2 605 411 203
	GSS 230 AE GSS 280 AE	0 601 292 6.. 0 601 293 6..		 Microfilter box 2 605 411 147
 Delta sander	GDA 280 E	0 601 294 7..		
 Random orbit sanders	GEX 125 AC GEX 150 AC GEX 150 Turbo	0 601 372 5.. 0 601 372 7.. 0 601 250 7..		 Microfilter box 2 609 199 176
	GEX 125-1 AE	0 601 387 5..		
	GEX 125-150 AVE	0 601 37B 1..		 Microfilter box 2 605 411 233
 Benchtop tools	GCM 8 S GCM 8 SJ GCM 8 SJL GCM 800 S	0 601 B16 1.. 0 601 B16 2.. 0 601 B19 1.. 0 601 B16 1..		 Dust bag 2 605 411 222
	GCM 10 J GCM 12 JL GCM 12 GDL	0 601 B20 2.. 0 601 B21 1.. 0 601 B23 6..		
	GCM 10 GCM 10 SD GCM 10 S	0 601 B20 0.. 0 601 B22 5.. 0 601 B20 5..		
	GCM 12 GCM 12 SD	0 601 B21 0.. 0 601 B23 5..		
	GTM 12	0 601 B15 0..		
	GTS 10 J GTS 10 XC	0 601 B30 5.. 0 601 B30 4..	 Dust extraction adapter 2 610 015 513	 Dust bag 2 605 411 205






34 | Technical data and scope of delivery

Technical data and scope of delivery – everything at a glance.

Dust extractor	GAS 20 L SFC Professional	GAS 25 L SFC Professional	GAS 35 L SFC+ Professional
			
Technical data	0 601 97B ...	0 601 979 ...	0 601 9C3 ...
Max. power input (Turbine)	1300 W	1280 W	1380 W
Container volume, gross	19 l	25 l	35 l
Container volume, net, water	7.5 l	16 l	19.2 l
Container volume, net, dust	10 l	20 l	23 l
Filter surface area	2,800 cm ²	4,300 cm ²	6,150 cm ²
Dust class of wet/dry extractor	L	L	L
Dust class of main filter	L	M	M
Weight	6.0 kg	12.7 kg	11.6 kg
Comes complete with	... 000	... 103	... 000
2 x extraction pipes 0.5 m, diameter 35 mm (2 607 000 162)	-	●	-
2 x extraction pipes 0.5 m, diameter 35 mm (2 607 002 631)	●	-	-
3 x chrome-plated extraction pipes 0.35 m (2 608 000 575)	-	-	●
Floor nozzle set (1 609 390 478)	-	-	●
Disposal bag (2 605 411 231)	●	-	-
Disposal bag (2 607 432 043)	-	-	●
Pleated filter (2 607 432 024)	●	-	-
Cellulose flat-pleated filter (2 607 432 033)	-	-	●
250 mm crevice nozzle (2 607 000 165)	●	●	●
Coarse dirt nozzle (2 607 000 170)	●	●	-
Elbow (2 608 000 573)	-	-	●
Suction regulator control (2 607 000 164)	-	●	-
Suction regulator control (2 607 002 630)	●	-	-
Multi-purpose nozzle	-	●	-
Paper dust bag (2 605 411 167)	-	●	-
Polyester filter (2 607 432 015)	-	●	-
SFC+ module	-	-	●
3 m hose, diameter 35 mm, with power tool adapter (2 608 000 569)	-	-	●
3 m hose, diameter 35 mm, with power tool adapter (2 609 390 392)	-	●	-
Universal power tool adapter (2 607 002 632)	●	-	-
3 m universal hose, diameter 40 mm (1 600 A00 0JF)	●	-	-



Dust extractor	GAS 35 L AFC Professional	GAS 35 M AFC Professional	GAS 55 M AFC Professional
			
Technical data	0 601 9C3 ...	0 601 9C3 ...	0 601 9C3 ...
Max. power input (Turbine)	1380 W	1380 W	1380 W
Container volume, gross	35 l	35 l	55 l
Container volume, net, water	19.2 l	19.2 l	40 l
Container volume, net, dust	23 l	23 l	43 l
Filter surface area	6,150 cm ²	6,150 cm ²	6,150 cm ²
Dust class of wet/dry extractor	L	M	M
Dust class of main filter	M	M	M
Weight	12.2 kg	12.4 kg	16.2 kg
Comes complete with	... 200	... 100	... 300
3 x chrome-plated extraction pipes 0.35 m (2 608 000 575)	●	●	●
Floor nozzle set (1 609 390 478)	●	●	●
Disposal bag (2 607 432 043)	●	●	●
PES flat-pleated filter (2 607 432 034)	●	●	●
250 mm crevice nozzle (2 607 000 165)	●	●	●
Elbow (2 608 000 573)	●	●	●
5 m hose, diameter 35 mm, antistatic with power tool adapter (2 608 000 566)	-	●	●
5 m hose, diameter 35 mm, with power tool adapter (2 608 000 565)	●	-	-



New accessories for GAS 35 / 55 Professional at a glance.

Working with a system means working completely cleanly because everything fits together. Bosch power tools, dust extractors and accessories are perfectly harmonised with each other. Whether filters or elbows, pipes or tool adapters, normal or antistatic hoses: with Bosch you are perfectly equipped to work cleanly.



Flat-pleated filter

Page 36

Filter bag




Page 37

Hoses

Page 38

Other accessories

Page 39





Flat-pleated filter product range	Part no.	Description
<p>Cellulose flat-pleated filter</p> 	2 607 432 033	<p>The cellulose flat-pleated filter is made of nano-coated paper material and is ideal for extracting fine dust and dry dirt particles.</p> <p>Examples: sanding, routing, drilling in wood</p> <p>Dust class certification: M</p>
<p>PES (polyester) flat-pleated filter</p> 	2 607 432 034	<p>The nano-coated PES (polyester) flat-pleated filter is ideal for wet and dry applications. The filter can be easily cleaned under running water without any problems. It is recommended that you let the filter dry after cleaning. The PES filter is rot-proof.</p> <p>Dust class certification: M</p>
<p>PTFE (polytetrafluoroethylene) flat-pleated filter</p> 	2 607 432 041	<p>The PTFE (polytetrafluoroethylene) special flat-pleated filter is ideal for wet and dry applications. The filter can be easily cleaned under running water without any problems. It is recommended that you let the filter dry after cleaning. The PTFE filter is rot-proof, extremely robust and durable.</p> <p>This filter is ideal for extreme applications such as working on "green concrete" or for extracting damp fine dusts.</p> <p>Dust class certification: M</p>









Flat-pleated filter product range	Part no.	Description
GAS 35 paper filter bag 	2 607 432 035	<p>The paper filter bag is advisable for simple, coarser dusts and dirt that have non-abrasive effects. The paper filter bag enables the extracted material to be disposed of with low levels of dust.</p> <p>This filter bag is only suitable for dry applications.</p> <p>If a paper filter bag is used, the automatic filter cleaning (AFC) or semi-automatic filter cleaning Plus (SFC+) should be switched off.</p> <p>The two paper filter bags in the range are certified for dust class 'M'.</p>
GAS 55 paper filter bag 	2 607 432 036	
GAS 35 fleece filter bag 	2 607 432 037	<p>The fleece filter bag is very robust, can hold a very high volume of dust (2 to 3 times that of a paper filter bag) and enables the extracted material to be disposed of easily and with low levels of dust. The fleece filter bag is also less sensitive to abrasive materials and moisture than, for example, paper filter bags.</p> <p>The fleece filter bag is suitable for dry applications.</p> <p>The fleece filter bags in the range are certified for dust class 'M'.</p>
GAS 55 fleece filter bag 	2 607 432 038	
GAS 35 reusable fleece filter bag 	2 607 432 045	<p>This fleece filter bag can be repeatedly reused because the contents can be emptied by opening the sealing rail. Their very sturdy construction enables large amounts of dust to be extracted.</p> <p>The fleece filter bag is suitable for dry applications.</p> <p>This fleece filter bag is suitable for extracting materials that require an 'L'-certification.</p>
GAS 35/55 wet filter bag 	2 607 432 039	<p>The wet filter bag is ideal for working in wet environments. In contrast to the fleece filter bag, the wet filter bag lets the liquid through. This means that solid dirt particles stay in the wet filter bag, while liquids flow into the container. This makes it easier to empty and dispose of the extracted materials and liquids.</p> <p>The wet filter bag is certified for dust class 'L'.</p>
GAS 35/55 disposal bag 	2 607 432 043	<p>The disposal bag is the ideal filter bag for working with the automatic filter cleaning system (AFC).</p> <p>The disposal bag is suitable for dry and wet applications.</p> <p>It enables the extracted materials to be disposed of with low levels of dust and is therefore suitable for use with 'M'-certified dust extractors.</p>



38 | System overview

Hose with tool adapter, 35 mm diameter	Part no.	Description
5 m hose 	2 608 000 565	<p>The new suction hoses with a diameter of 35 mm are available in two different lengths: 5 m or 3 m.</p> <p>These suction hoses are supplied with a mounted tool adapter.</p> <p>Bosch's antistatic suction hoses are blue and prevent static charge during work. Antistatic hoses are also non-marking and included as standard with the GAS 35 M AFC and GAS 55 M AFC dust extractors.</p>
5 m hose, antistatic 	2 608 000 566	
3 m hose 	2 608 000 569	
3 m hose, antistatic 	2 608 000 570	

Hose with tool adapter, 22 mm diameter	Part no.	Description
5 m hose 	2 608 000 567	<p>The new suction hoses with a diameter of 22 mm are available in two different lengths: 5 m or 3 m.</p> <p>These suction hoses are supplied with a mounted tool adapter.</p> <p>Bosch's antistatic suction hoses are blue and prevent static charge during work. Antistatic hoses are also non-marking.</p> <p>The hose is considerably lighter and more flexible due to its reduced diameter. This is ideal when working overhead for applications with low to medium dust development.</p>
5 m hose, antistatic 	2 608 000 568	
3 m hose 	2 608 000 571	
3 m hose, antistatic 	2 608 000 572	

Other accessories	Part no.	Description
Extension pipe, chrome-plated 	2 608 000 575	<p>The chrome-plated extension pipes support the high suction power of the wet and dry dust extractors due to their sufficiently large diameter.</p> <p>The extension pipes enable individual adjustment to various work heights. What's more, they fit into all L-BOXes for safe transport and clean storage.</p>
Antistatic elbow 	2 608 000 573	



Other accessories	Part no.	Description
Crevice nozzle 	2 607 000 165	The concentrated airflow of the crevice nozzle enables deep-seated dirt to be extracted from corners and crevices.
Floor nozzle set 	1 609 390 478	For optimum wet and dry dirt collection. The floor nozzle set has a working width of 300 mm. The side rollers make it easier to use. The brush strips are suitable for extracting dry and damp materials. The rubber lips included in the set are ideal for extracting liquids.
Floor nozzle 	1 609 201 230	The floor nozzle is ideal for use in buildings.
Coarse dirt nozzle 	2 607 000 170	The coarse dirt nozzle is ideal for extracting coarse chips and dirt.
Small floor nozzle 	2 607 000 166	The small floor nozzle is ideal for extracting smaller amounts of chips and dirt.
Rubber nozzle 	1 609 201 229	The rubber nozzle is ideal for extracting finer dirt in hard-to-reach areas.
Small round brush 	1 609 390 481	The small round brush is ideal for extracting a wide variety of materials.
Tool adapter 	2 608 000 585	The tool adapter with additional air control is used as a connector between the hose and the power tool. Due to the false air opening, you can control the suction power of the dust extractor at the adapter, e.g. to prevent the tool from sticking to the surface. An advantage: the tool adapter is antistatic and compatible with all power tools.
L-BOXX inlay 	2 608 438 091	Storage and transport made easy: the L-BOXX inlay ensures organised and easy storage of your accessories. You can easily transport the L-BOXX on the new dust extractors. Optimised for size 1 L-BOXX (2 608 438 691)



The **Bosch Toolbox App** –

Now you can experience for yourself the advantages of the Click & Clean System in our game!



► **Directly download the free Bosch Toolbox App: scan the QR code with a reader on your smartphone or search for “Bosch Toolbox” in the stores**





Everything fits because we've made it to fit.

A system that makes work easier for you: Bosch develops tools, accessories and dust extraction systems that are designed to work together perfectly. The system components and accessories such as the L-BOXX interact seamlessly to provide maximum user friendliness. The Click & Clean System from Bosch therefore enables not only clean, but also quick and uncomplicated work.



Robert Bosch Ltd
Power Tools Division
PO Box 98
Uxbridge
Middlesex
UB9 5HN
Tel. 0844 736 0107*
www.bosch-professional.co.uk



BOSCH
Invented for life

* 4 pence per minute from a BT landline, call charges from other networks will vary and mobiles may be significantly more