


STEEL WIRE ROPES

Accessories


Swivel with Jaw and Hook



Load cap.* in t	Rope Ø in mm	Dimensions in mm										Weight in kg/pce	Item no.
		F	G	H	J	K	L	M	N	P	V		
3	13	125	70	19.1	22.4	41.2	35.1	34.0	33.3	36.6	28.5	4.31	20202000015001
5	16	165	76	22.4	25.4	57.0	45.2	42.9	41.2	46.0	35.1	7.48	20202000015002
8.5	19	192	102	25.4	39.6	71.5	54.0	52.5	54.0	57.0	41.2	15.20	20202000015003
10	22	221	114	38.1	44.5	86.0	65.0	57.0	89.0	66.0	49.3	21.21	20202000015004
15	26	279	127	38.1	44.5	86.0	73.0	76.0	89.0	76.0	60.5	33.45	20202000015005
25	-	346	152	51.0	51.0	117	87.5	92.0	94.0	93.0	76.0	63.50	20202000015006
35	-	357	165	51.0	51.0	117	98.5	95.5	94.0	116	81.0	99.79	20202000015007
45	-	392	178	57.0	63.5	127	121	108	102	129	82.5	113.40	20202000015008

*Individually proof tested to twice the working load limit.
Minimum breaking load is 5 times the working load limit.


Swivel with 2 Jaws



Load cap.* in t	Rope Ø in mm	Dimensions in mm						Weight in kg/pce	Item no.
		D	G	Q	R	S	T		
3	13	239	70	19.1	26.2	28.5	31.8	4.20	20202000015009
5	16	249	76	25.4	32.5	31.8	31.8	6.46	20202000015010
8.5	19	302	102	31.8	35.8	41.2	38.1	13.27	20202000015011
10	22	394	114	42.9	42.9	70.0	47.8	20.75	20202000015012
15	26	416	127	49.3	51.5	70.0	54.0	33.45	20202000015013
25	-	565	152	57.0	58.5	98.5	60.5	63.50	20202000015014
35	-	556	165	57.0	58.5	98.5	60.5	70.31	20202000015015
45	-	673	178	63.5	64.5	102	76.0	106.59	20202000015016

*Individually proof tested to twice the working load limit.
Minimum breaking load is 5 times the working load limit.

Swivel with Jaw and Eye



Load cap.* in t	Rope Ø in mm	Dimensions in mm										Weight in kg/pce	Item no.
		G	H	J	K	N	Q	R	S	T			
3	13	70	19.1	22.4	41.2	33.3	19.1	26.2	28.5	31.8	4.08	20202000015017	
5	16	76	22.4	25.4	57.0	41.2	25.4	32.5	31.8	31.8	6.12	20202000015018	
8.5	19	102	25.4	39.6	71.5	54.0	31.8	35.8	41.2	38.1	13.27	20202000015019	
10	22	114	38.1	44.5	86.0	89.0	42.9	42.9	70.0	47.8	19.73	20202000015020	
15	26	127	38.1	44.5	86.0	89.0	49.3	51.5	70.0	54.0	28.46	20202000015021	
25	-	152	51.0	51.0	117	94.0	57.0	58.5	98.5	60.5	61.23	20202000015022	
35	-	165	51.0	51.0	117	94.0	57.0	58.5	98.5	60.5	68.04	20202000015023	
45	-	178	57.0	63.5	127	102	63.5	64.5	102	76.0	102.06	20202000015024	


*Individually proof tested to twice the working load limit.
Minimum breaking load is 5 times the working load limit.

STEEL WIRE ROPES

Accessories




Swivel with Eye and Jaw



Load cap.* in t	Rope Ø in mm	Dimensions in mm										Weight in kg/pce	Item no.
		C	G	H	J	K	N	Q	R	S	T		
3	13	237	70	19.1	22.4	41.2	33.3	19.1	26.2	28.5	31.8	4.08	20202000015025
5	16	256	76	22.4	25.4	57.0	41.2	25.4	32.5	31.8	31.8	6.24	20202000015026
8.5	19	311	102	25.4	39.6	71.5	54.0	31.8	35.8	41.2	38.1	13.15	20202000015027
10	22	409	114	38.1	44.5	86.0	89.0	42.9	42.9	70.0	47.8	19.96	20202000015028
15	26	525	127	38.1	44.5	86.0	89.0	49.3	51.5	70.0	54.0	27.67	20202000015029
25	-	546	152	51.0	51.0	117	94.0	57.0	58.5	98.5	60.5	61.23	20202000015030
35	-	546	165	51.0	51.0	117	94.0	57.0	58.5	98.5	60.5	68.04	20202000015031
45	-	657	178	57.0	63.5	127	102	63.5	64.5	102	76.0	102.06	20202000015032

*Individually proof tested to twice the working load limit.
Minimum breaking load is 5 times the working load limit.


Swivel with 2 Eyes



Load cap.* in t	Rope Ø in mm	Dimensions in mm										Weight in kg/pce	Item no.
		C	G	H	J	K	N	Q	R	S	T		
3	13	237	70	19.1	22.4	41.2	33.3	19.1	26.2	28.5	31.8	3.86	20202000015033
5	16	256	76	22.4	25.4	57.0	41.2	25.4	32.5	31.8	31.8	5.56	20202000015034
8.5	19	311	102	25.4	39.6	71.5	54.0	31.8	35.8	41.2	38.1	13.27	20202000015035
10	22	409	114	38.1	44.5	86.0	89.0	42.9	42.9	70.0	47.8	19.05	20202000015036
15	26	525	127	38.1	44.5	86.0	89.0	49.3	51.5	70.0	54.0	27.67	20202000015037
25	-	546	152	51.0	51.0	117	94.0	57.0	58.5	98.5	60.5	58.97	20202000015038
35	-	546	165	51.0	51.0	117	94.0	57.0	58.5	98.5	60.5	65.77	20202000015039
45	-	657	178	57.0	63.5	127	102	63.5	64.5	102	76.0	97.52	20202000015040

*Individually proof tested to twice the working load limit.
Minimum breaking load is 5 times the working load limit.

Swivel with Eye and Hook



Load cap.* in t	Rope Ø in mm	Dimensions in mm										Weight in kg/pce	Item no.
		F	G	L	M	P	Q	R	S	T	V		
3	13	125	70	35.1	34.0	36.6	19.1	26.2	28.5	31.8	28.5	4.08	20202000015041
5	16	165	76	45.2	42.9	46.0	25.4	32.5	31.8	31.8	35.1	6.92	20202000015042
8.5	19	192	102	54.0	52.5	57.0	31.8	35.8	41.2	38.1	41.2	14.51	20202000015043
10	22	221	114	65.0	57.0	66.0	42.9	42.9	70.0	47.8	49.3	20.64	20202000015044
15	26	279	127	73.0	76.0	76.0	49.3	51.5	70.0	54.0	60.5	33.57	20202000015045
25	-	346	152	87.5	92.0	93.0	57.0	58.5	98.5	60.5	76.0	61.23	20202000015046
35	-	357	165	98.5	95.5	116	57.0	58.5	98.5	60.5	81.0	97.52	20202000015047
45	-	392	178	121	108	129	63.5	64.5	102	76.0	82.5	122.17	20202000015048

*Individually proof tested to twice the working load limit.
Minimum breaking load is 5 times the working load limit.

Swivels with tapered roller thrust bearing

- Suitable for frequent rotation under load
- All swivels individually proof tested with certification
- All hooks furnished with latches assembled
- All jaws complete with bolts, nuts and cotter pins
- Pressure lube fitting provided
- Not to be used on demolition (wrecking) balls