



WIRE ROPE END FITTINGS

RESIN FOR SPELTER SOCKETS

Note: For use on 416, 417, 427 and 517 spelter sockets only.



WIRELOCK®
Socketing Compound

- 100% termination efficiency.
- Temperature operating range is -54°C to +116°C (-65°F to +240°F).
- Ideal for on-site applications.
- No hazardous molten metal.
- Improved fatigue life.
- Pouring temperature without booster pack is 6.67°C to 43.3°C (48°F to 110°F).
- One booster pack if pouring temperature is 1.67°C to 8.89°C (35°F to 48°F).
- Two booster packs if pouring temperature is -2.78°C to +1.67°C (27°F to 35°F).
- Refer to Crosby® Wire Rope End Terminations Manual for more information.
- Storage temperature is 20°C (68°F) max. Store in well ventilated area away from sunlight and sources of ignition.



7

APPROVALS:

Lloyds Register of Shipping

Det Norske Veritas (DNV)

United States Coast Guard

Registro Italiano Navale

Germanischer Lloyd

United States Navy

American Bureau of Shipping

ISO 17.558

DNV-OS-E304



U.S. Department of Transportation
United States Coast Guard



WIRELOCK® W416-7 Socket Compound

Kit Size	Kit Per Case	W416-7 Kits		Weight Each (kg)	Booster Pak Stock No.
		Stock No.	Weight Each (kg)		
100	20	1039602	.28		1039603
250	12	1039604	.57		1039605
500	12	1039606	1.15		1039607
1000	12	1039608	2.08		1039609
2000	6	1039610	4.08		1039611

Guide to amount WIRELOCK® Required

Wire Rope Size		WIRELOCK Required (cc)	Wire Rope Size		WIRELOCK Required (cc)
(in)	(mm)		(in)	(mm)	
1/4	6-7	9	1-3/4	44	700
5/16	8	17	1-7/8	48	700
3/8	9-10	17	2	51	1265
7/16	11	35	2-1/8	54	1265
1/2	13	35	2-1/4	56	1410
9/16	14	52	2-3/8	60	1410
5/8	16	52	2-1/2	64	1830
3/4	20	86	2-5/8	67	1830
7/8	22	125	2-3/4	70	2250
1	26	160	3	76	3160
1-1/8	28	210	3-1/4	82	3795
1-1/4	32	350	3-1/2	88	4920
1-3/8	36	350	3-3/4	94	5980
1-1/2	40	420	4	102	7730
1-5/8	42	495	—	—	—

Wirelock is a hazardous material regulated by US DOT, ICAO/IATA and IMO for transportation.

APPLICATION AND WARNING INFORMATION
SECTION 17

Witnessed and tested by American Bureau of Shipping. (ABS)

Approximate U.S. Measurements:
250cc's Kit 1 Cup