














APPLICATION INFORMATION

Crosby's Sling Saver® line is the first broad line of fittings developed exclusively for use with synthetic slings. Combined with additional Crosby products, a complete system is now available.

RECOMMENDED APPLICATION CHART

APPLICATION	USE
Web slings, connect to pad eye, eye bolt, or lifting lug.	S-281 Sling Saver Web Sling Shackle 
Web slings or roundslings, connecting to pad eye, eye bolt, or lifting lug.	S-253 or S-252 Sling Saver Shackle 
Connect two S-252 or S-253 Sling Saver shackles together.	S-256 Link Plate 
To keep the load centered on the pin, thus keeping the sling positioned correctly in the shackle bow.	S-255 Spool 
Web slings or roundslings connecting to master links, rings, or Crosby 320N Eye Hooks.	S-280 Sling Saver Web Connector with spool 
High strength, high capacity web or roundslings.	WSL-320A Synthetic Sling Hook 
Choking with web slings or roundslings.	S-287 Sliding Choker Hook 
Master links or master link assembly to be sewn into eye of web sling or attached utilizing web connector.	Welded Master Link A-1343 and Master Link Assembly A-1346 
Master links or master link assembly to be sewn into eye of web sling or attached utilizing web connector.	Welded Master Link A-342 and Master Link Assembly A-345 
Connecting high performance slings to master links or eye hooks and to other high performance slings.	S-237 or S-238 High Performance Connectors 
Wide body shackles greatly improve wearability of wire rope slings.	S/G-2160 Wide Body Bolt Type Shackles S/G-2169 Wide Body Screw Pin Shackles 
Always ensure rated Working Load Limits are greater than the load placed on the fitting. Designed for use with Type III (eye & eye), Class 7, 2-ply webbing, and synthetic round slings. Also accommodates single ply and endless slings.	
Crosby Sling Saver hardware meets the requirements for minimum stock diameter or thickness and effective contact width shown in the recommended standard specification for synthetic polyester round slings by the Web Sling and Tie Down Association. WSTDA-RS1 (revised 2010).	