

V-BELTS AUTOMOTIVE



V-BELTS AUTOMOTIVE

Description

Energy saving, higher performance thanks to their flexibility. Dunlop Automotive V-belts with a higher performance level have a longer service life. Special designs with Raw edges that allow higher slipping resistance even when they are working with low installation tensions.

Maximum resistance to the action of heat and oils. High antistatic properties used in automotive applications and conforming to ISO1813.

Part numbers are identified by 3 letters (e.g.AVX) the belts cross section and a 2 digit number (e.g.10)the belts top width and a 3 or 4 digit number which represents the belts length in mm. AVX10x800 etc.



AVX10 - SECTION

Part No	Outside Length (mm)	Pitch Length (mm)	Inside Length (mm)	Inside Length (in)
AVX10X600	638	622	600	23.6
AVX10X613	651	635	613	24.1
AVX10X617	655	639	617	24.3
AVX10X625	663	647	625	24.6
AVX10X635	673	657	635	25.0
AVX10X643	681	665	643	25.3
AVX10X650	688	672	650	25.6
AVX10X670	708	692	670	26.4
AVX10X675	713	697	675	26.6
AVX10X683	721	705	683	26.9
AVX10X685	723	707	685	27.0
AVX10X695	733	717	695	27.4
AVX10X700	738	722	700	27.6
AVX10X710	748	732	710	28.0
AVX10X725	763	747	725	28.5
AVX10X735	773	757	735	28.9
AVX10X740	778	762	740	29.1
AVX10X745	783	767	745	29.3
AVX10X750	788	772	750	29.5
AVX10X763	801	785	763	30.0
AVX10X775	813	797	775	30.5
AVX10X785	823	807	785	30.9
AVX10X800	838	822	800	31.5
AVX10X813	851	835	813	32.0
AVX10X818	856	840	818	32.2
AVX10X825	863	847	825	32.5
AVX10X838	876	860	838	33.0
AVX10X844	882	866	844	33.2
AVX10X850	888	872	850	33.5

Part No	Outside Length (mm)	Pitch Length (mm)	Inside Length (mm)	Inside Length (in)
AVX10X864	902	886	864	34.0
AVX10X875	913	897	875	34.4
AVX10X888	926	910	888	35.0
AVX10X900	938	922	900	35.4
AVX10X913	951	935	913	35.9
AVX10X920	958	942	920	36.2
AVX10X925	963	947	925	36.4
AVX10X930	968	952	930	36.6
AVX10X935	973	957	935	36.8
AVX10X940	978	962	940	37.0
AVX10X950	988	972	950	37.4
AVX10X960	998	982	960	37.8
AVX10X965	1003	987	965	38.0
AVX10X970	1008	992	970	38.2
AVX10X975	1013	997	975	38.4
AVX10X980	1018	1002	980	38.6
AVX10X990	1028	1012	990	39.0
AVX10X995	1033	1017	995	39.2
AVX10X1000	1038	1022	1000	39.4
AVX10X1005	1043	1027	1005	39.6
AVX10X1013	1051	1035	1013	39.9
AVX10X1025	1063	1047	1025	40.4
AVX10X1050	1088	1072	1050	41.3
AVX10X1060	1098	1082	1060	41.7
AVX10X1070	1108	1092	1070	42.1
AVX10X1075	1113	1097	1075	42.3
AVX10X1080	1118	1102	1080	42.5
AVX10X1090	1128	1112	1090	42.9
AVX10X1100	1138	1122	1100	43.3

V-BELTS AUTOMOTIVE



AVX10 - SECTION continued

Part No	Outside Length (mm)	Pitch Length (mm)	Inside Length (mm)	Inside Length (in)
AVX10X1110	1148	1132	1110	43.7
AVX10X1125	1163	1147	1125	44.3
AVX10X1140	1178	1162	1140	44.9
AVX10X1150	1188	1172	1150	45.3
AVX10X1165	1203	1187	1165	45.9
AVX10X1175	1213	1197	1175	46.3
AVX10X1184	1222	1206	1184	46.6
AVX10X1200	1238	1222	1200	47.2
AVX10X1215	1253	1237	1215	47.8
AVX10X1220	1258	1242	1220	48.0
AVX10X1225	1263	1247	1225	48.2
AVX10X1230	1268	1252	1230	48.4
AVX10X1235	1273	1257	1235	48.6
AVX10X1250	1288	1272	1250	49.2
AVX10X1260	1298	1282	1260	49.6
AVX10X1275	1313	1297	1275	50.2

Part No	Outside Length (mm)	Pitch Length (mm)	Inside Length (mm)	Inside Length (in)
AVX10X1300	1338	1322	1300	51.2
AVX10X1325	1363	1347	1325	52.2
AVX10X1340	1378	1362	1340	52.8
AVX10X1350	1388	1372	1350	53.1
AVX10X1375	1413	1397	1375	54.1
AVX10X1400	1438	1422	1400	55.1
AVX10X1425	1463	1447	1425	56.1
AVX10X1450	1488	1472	1450	57.1
AVX10X1475	1513	1497	1475	58.1
AVX10X1500	1538	1522	1500	59.1
AVX10X1525	1563	1547	1525	60.0
AVX10X1550	1588	1572	1550	61.0
AVX10X1575	1613	1597	1575	62.0
AVX10X1600	1638	1622	1600	63.0
AVX10X1625	1663	1647	1625	64.0
AVX10X1675	1713	1697	1675	65.9

AVX13 - SECTION

Part No	Outside Length (mm)	Pitch Length (mm)	Inside Length (mm)	Inside Length (in)
AVX13X750	800	780	750	29.5
AVX13X775	825	805	775	30.5
AVX13X800	850	830	800	31.5
AVX13X810	860	840	810	31.9
AVX13X818	868	848	818	32.2
AVX13X825	875	855	825	32.5
AVX13X835	885	865	835	32.9
AVX13X850	900	880	850	33.5
AVX13X875	925	905	875	34.4
AVX13X900	950	930	900	35.4
AVX13X918	968	948	918	36.1
AVX13X925	975	955	925	36.4
AVX13X950	1000	980	950	37.4
AVX13X960	1010	990	960	37.8
AVX13X975	1025	1005	975	38.4
AVX13X985	1035	1015	985	38.8
AVX13X992	1042	1022	992	39.1
AVX13X1000	1050	1030	1000	39.4
AVX13X1015	1065	1045	1015	40.0
AVX13X1025	1075	1055	1025	40.4
AVX13X1030	1080	1060	1030	40.6
AVX13X1040	1090	1070	1040	40.9
AVX13X1050	1100	1080	1050	41.3
AVX13X1055	1105	1085	1055	41.5
AVX13X1060	1110	1090	1060	41.7

Part No	Outside Length (mm)	Pitch Length (mm)	Inside Length (mm)	Inside Length (in)
AVX13X1075	1125	1105	1075	42.3
AVX13X1100	1150	1130	1100	43.3
AVX13X1125	1175	1155	1125	44.3
AVX13X1145	1195	1175	1145	45.1
AVX13X1150	1200	1180	1150	45.3
AVX13X1175	1225	1205	1175	46.3
AVX13X1200	1250	1230	1200	47.2
AVX13X1225	1275	1255	1225	48.2
AVX13X1250	1300	1280	1250	49.2
AVX13X1275	1325	1305	1275	50.2
AVX13X1285	1335	1315	1285	50.6
AVX13X1300	1350	1330	1300	51.2
AVX13X1325	1375	1355	1325	52.2
AVX13X1350	1400	1380	1350	53.1
AVX13X1375	1425	1405	1375	54.1
AVX13X1400	1450	1430	1400	55.1
AVX13X1425	1475	1455	1425	56.1
AVX13X1450	1500	1480	1450	57.1
AVX13X1475	1525	1505	1475	58.1
AVX13X1500	1550	1530	1500	59.1
AVX13X1525	1575	1555	1525	60.0
AVX13X1550	1600	1580	1550	61.0
AVX13X1575	1625	1605	1575	62.0
AVX13X1600	1650	1630	1600	63.0
AVX13X1625	1675	1655	1625	64.0