



12. PRODUCT DATA – CONTENT

Content

12. PRODUCT DATA – CONTENT	154
12.1 SINGLE ROW BALL BEARINGS	156
Single row ball bearings d = 2 to 1060 mm	
Single Row Ball Bearings with Seals or Shields d = 3 to 160 mm	
Single row ball bearings with groove for snap ring on outer race d = 12 to 120 mm	
Separable single row ball bearings d = 10 to 20 mm	
12.2 ANGULAR CONTACT BALL BEARINGS	211
Single row angular contact ball bearings d = 10 to 240 mm	
Single row high-speed angular contact ball bearings d = 7 to 130 mm	
Double row angular contact ball bearings d = 10 to 110 mm	
Four-point contact bearings d = 15 to 200 mm	
12.3 DOUBLE ROW SELF ALIGNING BALL BEARINGS	250
Double row self aligning ball bearings d = 10 to 150 mm	
12.4 CYLINDRICAL ROLLER BEARINGS	262
Single row cylindrical roller bearings d = 20 to 1180 mm	
Double row cylindrical roller bearings d = 25 to 1000 mm	
Single row full complement cylindrical roller bearings d = 20 to 1000 mm	
Double row full complement cylindrical roller bearings d = 20 to 400 mm	
12.5 SPHERICAL ROLLER BEARINGS	361
Double row spherical roller bearings d = 25 to 1120 mm	
12.6 TAPERED ROLLER BEARINGS	395
Single row tapered roller bearings in metric dimensions d = 15 to 320 mm	
Single row tapered roller bearings in inch dimensions d = 15.875 to 146.05 mm	
Four-row tapered roller bearings d = 160 to 630 mm	
12.7 THRUST BALL BEARINGS	432
Single direction thrust ball bearings d = 160 to 630 mm	
Double direction thrust ball bearings d = 10 to 140 mm	
Thrust ball bearings with sphered housing washer d = 15 to 130 mm	
Double direction thrust ball bearings with sphered housing washers d = 25 to 70 mm	
12.8 CYLINDRICAL ROLLER THRUST BEARINGS	456
Cylindrical roller thrust bearings d = 15 to 630 mm	



12.9 SPHERICAL ROLLER THRUST BEARINGS	468
Spherical roller thrust bearings d = 50 to 1120 mm	
12.10 SPLIT ROLLER BEARINGS	482
Split cylindrical roller bearings d = 150 to 600 mm	
12.11 BEARINGS FOR RAILWAY APPLICATIONS	494
Single row ball bearings for traction motors d = 65 to 150 mm	
Single row cylindrical roller bearings for traction motors d = 35 to 150 mm	
Special single row rolling bearings for railway vehicle axles d = 118 to 130 mm	
Double row spherical roller bearings for railway vehicle axles d = 100 to 190 mm	
Tapered bearing units TBU	
12.12 SPECIAL ROLLER BEARINGS	510
Hybrid ball bearings d = 10 to 120 mm	
Electrically insulated ball bearings d = 70 to 150 mm	
Electrically insulated cylindrical roller bearings d = 70 to 150 mm	
Double row spherical roller bearing PLC 58-11; PLC 58-9-1	
Double row spherical roller bearing PLC 010-3	
Single row ball bearing PLC 010-3	
Double row spherical roller bearings PLC 59-10; PLC 511-14	
Double row spherical roller bearing PLC 58-2	
Single row ball bearing 761	
Double row spherical roller bearings PLC 58-6; PLC 59-5; PLC 512-5	
Double row spherical roller bearings PLC 59-7; PLC 510-9; PLC 510-20 Special	
double row ball bearings PLC 77-1; PLC 14-28; PLC 14-29	
Single row ball bearings PLC 03-29; PLC 03-33; PLC 03-79	
Special thrust ball bearings 511Z30; PLC 23-4; PLC 23-5; 511Z35; PLC 24-2;	
PLC 24-4; PLC 24-5; PLC 24-6; PLC 23-7	
Special double row angular contact ball bearings PLC 15-2; PLC 14-26;	
PLC 14-25; PLC 14-24; PLC 15-22; PLC 15-12	
12.13 BEARING HOUSINGS AND ACCESSORIES	545
Adapter sleeves d = 20 to 150 mm	
Withdrawal sleeve d = 35 to 180 mm	
Adapter and withdrawal round nuts	
Safety mats d = 10 to 200 mm	
Snap rings for roller bearings with a groove on the outer ring	
Clamp bearings d = 20 to 40 mm	
Upright location units with clamp ring d = 25 to 40 mm	
Four row flanged location units with clamp ring d = 25 to 40 mm	
Oval shaped flanged location units with clamp ring d = 25 to 40 mm	
Triangular pressed flanged location units with clamp bearing	
Round pressed flanged location units with clamp bearing d = 20 to 35 mm	
Upright sheet metal location units with clamp bearing d = 25 to 35 mm	