

Accesorios para cilindros



▼ TABLA DE SELECCIÓN

Para ser utilizado con cilindro de una capacidad de (t)	Silletas			Placas base	Bloques de montaje	Horquillas de anillo	
	Lisas	Acanaladas ¹⁾	Inclinables			Base ⁴⁾	Émbolo
5	A-53F ²⁾	A-53G ²⁾	-	-	RB-5 ²⁾ , AW-51 ²⁾ , AW-53 ²⁾	REB-5 ²⁾	REP-5 ²⁾
10	A-12 ³⁾ , A-102F ³⁾	A-102G ³⁾	CAT-10 ³⁾	JBI-10	RB-10, AW-102	REB-10	REP-10 ³⁾
15	-	A-152G	CAT-10	-	RB-15	REB-15	REP-10
25	A-29	A-252G	CAT-50	JBI-25	RB-25	REB-25	REP-25
30	A-29	A-252G	CAT-50	-	RB-25	-	REP-25
50	-	-	CAT-100	JBI-50	-	-	-
75	-	-	CAT-100	-	-	-	-
100	-	-	CAT-100	-	-	-	-

¹⁾ Estándar en cilindros RC de 5 a 30 toneladas ²⁾ Excepto RC-50 ³⁾ Excepto RC-101 ⁴⁾ Se incluyen los tornillos de montaje.

▼ TABLAS DE DIMENSIONES

Número de modelo	Dimensiones de la silleta (pulg)			
	A	B	C	
Lisa				
A-53F	1.00	.25	.68	
A-102F	1.38	.24	.88	
A-12	2.00	1.88	1" - 8UNC	
A-29	2.00	1.88	1 1/2" - 16UN	
Acanalada				
A-53G	1.00	.25	.68	
A-102G	1.38	.24	.88	
A-152G	1.50	.37	.88	
A-252G	1.97	.37	1.40	

Número de modelo	Dimensiones de las silletas inclinables (pulg)			
	A	B	C	
Inclinables				
CAT-10	1.38	.79	.88	
CAT-50	1.97	.83	1.40	
Inclinables				
CAT-100	2.80	.98	-	

Número de modelo	Dimensiones de las placas base (pulg)						
	A	B	C	D	E		
JBI-10	9.00	9.00	5.34	2.29	.81		
JBI-25	11.00	11.00	5.53	3.41	1.03		
JBI-50	12.00	.60	3.75	5.19	1.25		

Número de modelo	Dimensiones de los bloques de montaje (pulg)											
	A	B	C	D	E	F	G	H				
RB-5	1 1/2" - 16	3.50	3.00	-	1.00	-	-	-				
AW-51	1 1/2" - 16	2.76	2.36	.43	.98	2.13	1/4" - 20	1.62				
AW-53	1 1/2" - 16	2.87	.28	.31	.75	2.25	1/4" - 20	.41				
RB-10	2 1/4" - 14	4.50	3.50	-	1.00	-	-	-				
AW-102	2 1/4" - 14	3.94	3.25	.63	1.18	3.00	7/16" - 20	2.31				
RB-15	2 3/4" - 16	4.00	4.50	-	1.50	-	-	-				
RB-25	3 5/16" - 12	5.00	6.50	-	2.00	-	-	-				

Tipo	Número de modelo	Dimensiones de las horquillas de anillo (pulg)						Distancia entre espigas* (pulg)		
		A	B	C	D	E	F			
Base ⁴⁾	REB-5	1.75	1.88	.56	.63	.63	1.00	2.37		
	REB-10	2.50	2.63	1.00	.88	1.00	1.38	3.07		
	REB-15	3.00	2.63	1.00	.88	1.00	1.38	3.07		
	REB-25	3.75	3.13	1.50	1.25	1.25	1.63	3.45		
Émbolo	REP-5	1.13	1.75	.56	.63	.63	.75	-		
	REP-10	1.69	2.43	1.00	.88	1.00	1.13	-		
	REP-25	2.25	2.81	1.50	1.25	1.25	1.38	-		

* Distancia entre pernos: con horquillas REB y REP. Añadir altura colapsada del cilindro.

⁴⁾ Se incluyen los tornillos de montaje.