



RODAVIGO, S.A.
RODAMIENTOS VIGO, S.A.

www.rodavigo.net

+34 986 288118
Servicio de Att. al Cliente

Heavy-Duty In-Drum Back-Geared Agitator

Reliable, Leak-Free Operation



**LEAK-FREE
DESIGN**

Quick connect heavy-duty back-geared agitator for drums or tanks with pre-installed blades

- ATEX approval for hazardous locations
- Oil free gear box eliminates material contamination
- Interchangeable adapters and couplers to fit a variety of drum designs
- Simple screw in installation
- Corrosion resistant stainless steel construction
- Available in either 1.5 inch or 2 inch bung sizes, with shaft adapters

PROVEN QUALITY. LEADING TECHNOLOGY.

Polígono Industrial O Rebullón s/n. 36416 - Mos - España - rodavigo@rodavigo.com



RODAVIGO, S.A.
RODAMIENTOS VIGO, S.A.

www.rodavigo.net

+34 986 288118
Servicio de Att. al Cliente

Technical Specifications

Maximum air input pressure 100 psi (7 bar)

Motor power rating at 1200 rpm (shaft at 50 rpm),

Using 12 cfm (0.34 m³/min) 0.25 hp (186 W)

Maximum recommended shaft rpm 100

Gear reducer ratio 24:1

Weight 17.7 lb (8 kg)

Height

From top of air motor to base of quick connect 11.25 in (286 mm)

Air inlet Mates with 1/4-in npt(f) quick-disconnect,
Part No 208536

Wetted parts 303 SST

Air consumption 3 to 30 scfm (0.08 to 0.85 m³/min)

Sound data*

Typical operating conditions†

Sound power 77.3 dB(A)

Sound pressure 63.8 dB(A)

Maximum noise conditions‡

Sound power 86.4 dB(A)

Sound pressure 72.9 dB(A)

*Sound data was measured per ISO 3744-1981.

† 50 rpm (shaft) agitating 300 cps water-base material

‡ 100 rpm (shaft) agitating an empty container

Ordering Information

24C293: 1.5 inch bung model

Includes heavy duty agitator drive,
plus 2 adapters for 4 different shaft
sizes (3/8, 7/16, 1/2 and 5/8 inch)



24C522: 2 inch bung model

Includes heavy duty agitator drive,
plus 2 adapters for 4 different shaft
sizes (3/8, 7/16, 1/2 and 5/8)

Accessories



Bung Adapters

16A521 1.5 inch bung adapter

16A754 2 inch bung adapter



Shaft Adapters

16H554 3/8 inch and 7/16 inch shaft adapter

16H555 1/2 inch and 5/8 inch shaft adapter



Speed Controller

24G621 Agitator Speed Controller
Controls and maintains agitator
speed regardless of drum level
or viscosity changes



All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Call today for product information or to request a demonstration.

877.84GRACO (1-877-844-7226) or visit us at www.graco.com.

©2011 Graco Inc. 344809 Rev. C 09/11 Printed in the U.S.A.

All other brand names or marks are used for identification purposes and are trademarks of their respective owners.

