

Triton Spray Packages



The Best Spray Finishing Package in its Class!

- Low pulsation output and smooth pump changeover deliver a consistent spray pattern for a high quality finish
- Quick color changes and fast material refills save time and money
- Rugged stainless steel or aluminum pump handles a wide variety of fluids



Available with AirPro™ Spray Guns

2. High-Flow Air Regulators
Supplies up to 35% extra air flow to gun
for superior atomization

3. AirPro Spray Gun


Superior finish quality for conventional, HVLP and compliant applications

- 4. Durable Metal TRITON Pump
 Provides low maintenance and long life
- Easy-to-use Circulation Valve
 Saves material and time during flushing, priming and color changes
- Low Pulsation TRITON Pump
 Delivers a consistent spray pattern and uniform film thickness
- 7. Flexible, Lightweight Air Hose Reduces operator fatigue
- 8. Heavy-Duty Suction Performance
 Sprays a wide variety of material viscosities

Low Pulsation Output!

Superior Finish Quality

- · Consistent pattern and film on parts.
- Constant flow to the spray gun.



TRITON pump provides 50% less pressure pulsation than standard diaphragm pumps.

Note: Pump-to-pump comparison without fluid regulator

For more information visit www.graco.com/finishing or call 1-877-844-7226

PROVEN QUALITY. LEADING TECHNOLOGY.



TRITON Spray Finishing Package Ordering Information 1. Select configuration

- 2. Select aluminum or stainless steel package
- 3. Select applicator

Pumn

Pump Material	Part No.	Pale	Fluid	Suction	AirHo	Fluid,	Application Description
5 Gallon, Pail-Mount Units							
Aluminum	233466	•		•			None
Stainless Steel	233467	•		•			None
Aluminum	233468			•	•	•	AirPro Conventional Gun .055 in (1.5 mm) nozzle
Stainless Steel	233469			٠	•	•	AirPro Conventional Gun .055 in (1.5 mm) nozzle
Aluminum	233470		60	•	•	•	AirPro HVLP Gun .055 in (1.5 mm) nozzle
Stainless Steel	233471		100	•	•	•	AirPro HVLP Gun .055 in (1.5 mm) nozzle
Aluminum	234911		60	٠	•	•	AirPro Compliant Gun .055 in (1.5 mm) nozzle
Stainless Steel	234912		100	•	•	•	AirPro Compliant Gun .055 in (1.5 mm) nozzle
4-Legged,	Stand-I	Mour	nt Un	its			
Aluminum	233473	•		•			None
Stainless Steel	233474	•		•			None
Aluminum	233475			•	•	•	AirPro Conventional Gun .055 in (1.5 mm) nozzle
Stainless Steel	233476			•	•	•	AirPro Conventional Gun .055 in (1.5 mm) nozzle
Aluminum	233477		60	•	•	•	AirPro HVLP Gun .055 in (1.5 mm) nozzle
Stainless Steel	233478		100	•	•	•	AirPro HVLP Gun .055 in (1.5 mm) nozzle
Aluminum	234913		60	•	•	•	AirPro Compliant Gun .055 in (1.5 mm) nozzle
Stainless Steel	234914		100	•	•	•	AirPro Compliant Gun .055 in (1.5 mm) nozzle
Cart-Mount	t Units						
Aluminum	233480			•			None
Stainless Steel	233481	•		•			None
Aluminum	233482			•	•	•	AirPro Conventional Gun .055 in (1.5 mm) nozzle
Stainless Steel	233483			•	•	•	AirPro Conventional Gun .055 in (1.5 mm) nozzle
Aluminum	233484		60	•	•	•	AirPro HVLP Gun .055 in (1.5 mm) nozzle
Stainless Steel	233485		100	•	•	•	AirPro HVLP Gun .055 in (1.5 mm) nozzle
Aluminum	234915		60	•	•	•	AirPro Compliant Gun .055 in (1.5 mm) nozzle
Stainless Steel	234916		100	•	•	•	AirPro Compliant Gun .055 in (1.5 mm) nozzle
Wall-Moun	t Units						
Aluminum	233487	•					None
Stainless Steel	233488	•					None
Aluminum	233489				•	•	AirPro Conventional Gun .055 in (1.5 mm) nozzle
Stainless Steel	233490				•	•	AirPro Conventional Gun .055 in (1.5 mm) nozzle
Aluminum	233491		60		•	•	AirPro HVLP Gun .055 in (1.5 mm) nozzle
Stainless Steel	233492		100		•	•	AirPro HVLP Gun .055 in (1.5 mm) nozzle
Aluminum	234917		60		•	•	AirPro Compliant Gun .055 in (1.5 mm) nozzle
Stainless Steel	234918		100		•	•	AirPro Compliant Gun .055 in (1.5 mm) nozzle









Wall-mount units do not include suction hose, siphon tube or pail. Must order separately.

For more information visit www.graco.com/finishing or call 1-877-844-7226



^{*}Bare packages do not include hose and gun.

^{**}HVLP and compliant packages include fluid regulator:

⁻ Aluminum packages use 60 psi (0.4 MPa, 4.1 bar) acetal fluid regulator.

⁻ Stainless steel packages use 100 psi (0.7 MPa, 7 bar) stainless steel fluid regulator.