

SR

080

I & 2-stage

Planetary gearboxes

Drawings


Input



**A** for motor shaft  $L \leq 45$   $6 \leq \varnothing d \leq 19$  result in LA



**B** for motor shaft  $45 < L \leq 55$   $19 < \varnothing d \leq 24$  result in LB

		I-stage	2-stage	3-stage
LA	[mm]	106.5	128.5	150.5
LB	[mm]	116	138	160



Example SR 080 B0, 2-stage


\* depending on the motor. See pages 130 et seq.





Output



Optional



Option 3 on request. Adjustments can reduce capacity.



Option 5 on request. Adjustments can reduce capacity.

Material 16MnCr5 DIN 1.7131  
Teeth pressure angle  $\alpha = 20^\circ$ , helical teeth left,  $19^\circ 31' 42''$  hardened ( $58^{+4}$  HRC), ground, crowned  
Quality 6f24 DIN 3962 / 63 / 67

Your ideal drive train

Function Package with gearbox, rack and pinion from Güdel



Pinion



	$m_n$	$P_t$	$z$	A	b	$D_k$	$D_0$	$D_v$	L12	L13	x2	a	M	
Pinion 1	[-]	2	6.66	20	43.221	25	46.44	42.441	42.441	52.5	40.0	20.0	20	0.3
Pinion 2	[-]	2.5	8.33	16	43.471	26	48.94	42.441	43.941	58	45	15	30	0.3

$m_n$ : Normal module,  $P_t$ : Transverse pitch [mm],  $z$ : Number of teeth,  $D_0$ : Pitch circle diameter for calculation,  $D_v$ : Pitch circle diameter for design, M: Weight [kg]

Available ratios	i		1-stage		2-stage				
			4	12	16	20	28	40	
Nominal torque S5 a)	T <sub>2N</sub>	[Nm]	95	95	95	95	95	95	
Acceleration torque S5 b)	T <sub>2B</sub>	[Nm]	150	140	140	140	140	140	
Nominal input speed S5 c)	n <sub>1N</sub>	[rpm]	2 600	2 900	3 100	3 100	3 100	3 100	
Maximum input speed S5	n <sub>1max</sub>	[rpm]	5 400	5 400	5 400	5 400	5 400	5 400	
Emergency stop torque d)	T <sub>2not</sub>	[Nm]	250	250	250	250	250	250	
Efficiency	η	[%]	96	93					
Lifetime	L <sub>h</sub>	[h]	> 20 000						
Weight	M	[kg]	4	5					
Angular backlash	j <sub>c</sub>	[arcmin]	Precision P I ≤ I / P 3 ≤ 3 / P 5 ≤ 5 / P 12 ≤ 12						
Torsionnal rigidity e)	C <sub>t2</sub>	[Nm/arcmin]	11.7	11.1	11.1	11.3	11.1	11.1	
Noise i)	L <sub>pA</sub>	[dB(A)]	≤ 70						
Max. permitted housing temperature g)	T	[°C]	90						
Protection class			IP 65						
Direction of rotation			Same way input / output						
Max. radial force on output shaft f)	F <sub>rmax</sub>	[N]	Center of output shaft: 4 200 / End of output shaft: 3 285						
Max. axial force on output shaft f)	F <sub>amax</sub>	[N]	3 600						
Color			Red, RAL 3003						
Inertia in kg.cm <sup>2</sup> h)	Ø 11	J <sub>1</sub>	[kg.cm <sup>2</sup> ]	0.46	0.46	0.45	0.45	0.34	0.31
	Ø 14			1.02	1.01	1.00	1.00	0.89	0.86
	Ø 19			1.03	1.03	1.02	1.01	0.91	0.88
	Ø 24			1.85	1.84	1.83	1.83	1.72	1.69

a) Nominal output torque when operating at n<sub>1N</sub>.

b) 1000 cycles per hour max.

c) Valid for an ambient temperature of 20°C and T<sub>2N</sub>.  
At higher ambient temperatures, please reduce speed.

d) Valid 1000 times the gearbox life.

e) Valid for an input Ø of 19mm in 1-stage and 14mm in 2- and 3-stage.

f) Values for 300 rpm.

g) For other temperatures, please contact us. Nominal output torque when operating at n<sub>1N</sub>.

h) Depending on the motor output shaft Ø.

i) With i=10 and n<sub>1N</sub>=2500 rpm no load.

## Rack



	F <sub>2B</sub>	[N]	Pinion 1			Pinion 2		
			Q6	Q7	Q9	Q6	Q7	Q9
Max acceleration force			7 490	2 963	5 036	7 490	2 963	5 036
Max acceleration torque	T <sub>2B</sub>	[Nm]	159	63	107	159	63	107
Precision			PI		PI2	PI		PI2
Feed force			High	Medium	Elevated	High	Medium	Elevated

Above values for rack and pinion take into consideration a number of load cycles:  
1x10<sup>6</sup> for the rack; 1x10<sup>7</sup> for the pinion. Both in pulsating operation.For proper sizing follow flowchart  
**calculate your ideal drive train**  
on pages 136 et seq.More on the technical datasheets  
**your ideal drive train** on pages  
120 et seq.

SR

080

3-stage

Planetary gearboxes

Drawings


Input



**A** for motor shaft  $L \leq 45$   $6 \leq \varnothing d \leq 19$  result in LA

**B** for motor shaft  $45 < L \leq 55$   $19 < \varnothing d \leq 24$  result in LB

		1-stage	2-stage	3-stage
LA	[mm]	106.5	128.5	150.5
LB	[mm]	116	138	160



\* depending on the motor. See pages 130 et seq.




Example SR 080 A1, 3-stage




Output



Optional




Option 3 on request. Adjustments can reduce capacity.



Option 5 on request. Adjustments can reduce capacity.

Your ideal drive train

Function Package with gearbox, rack and pinion from Güdel



Pinion



	$m_n$	$P_t$	$z$	$A$	$b$	$D_k$	$D_0$	$D_v$	$L12$	$L13$	$x2$	$a$	$M$
Pinion 1	[-]	2	6.66	20	43.221	25	46.44	42.441	42.441	52.5	40.0	20.0	0.3
Pinion 2	[-]	2.5	8.33	16	43.471	26	48.94	42.441	43.941	58	45	15	0.3

$m_n$ : Normal module,  $P_t$ : Transverse pitch [mm],  $z$ : Number of teeth,  $D_0$ : Pitch circle diameter for calculation,  $D_v$ : Pitch circle diameter for design,  $M$ : Weight [kg]

Available ratios	i		3-stage											
			60	80	100	112	120	140	160	200	280	400		
Nominal torque S5 <sup>a)</sup>	T <sub>2N</sub>	[Nm]	95	95	95	95	95	95	95	95	95	95		
Acceleration torque S5 <sup>b)</sup>	T <sub>2B</sub>	[Nm]	140	140	140	140	140	140	140	140	140	140		
Nominal input speed S5 <sup>c)</sup>	n <sub>1N</sub>	[rpm]	4 000	4 000	4 000	4 000	4 000	4 000	4 000	4 000	4 000	4 000		
Maximum input speed S5	n <sub>1max</sub>	[rpm]	5 400	5 400	5 400	5 400	5 400	5 400	5 400	5 400	5 400	5 400		
Emergency stop torque <sup>d)</sup>	T <sub>2not</sub>	[Nm]	250	250	250	250	250	250	250	250	250	250		
Efficiency	η	[%]	90											
Lifetime	L <sub>h</sub>	[h]	> 20 000											
Weight	M	[kg]	6											
Angular backlash	j <sub>c</sub>	[arcmin]	Precision P 1 ≤ 1 / P 3 ≤ 3 / P 5 ≤ 5 / P 12 ≤ 12											
Torsionnal rigidity <sup>e)</sup>	C <sub>t2</sub>	[Nm/arcmin]	10.7	10.7	9.8	10.6	10.6	10.7	10.6	10.7	10.6	10.1		
Noise <sup>f)</sup>	L <sub>pA</sub>	[dB(A)]	≤ 70											
Max. permitted housing temperature <sup>g)</sup>	T	[°C]	90											
Protection class			IP 65											
Direction of rotation			Same way input / output											
Max. radial force on output shaft <sup>f)</sup>	F <sub>rmax</sub>	[N]	Center of output shaft: 4 200 / End of output shaft: 3 285											
Max. axial force on output shaft <sup>f)</sup>	F <sub>amax</sub>	[N]	3 600											
Color			Red, RAL 3003											
Inertia in kg.cm <sup>2</sup> <sup>h)</sup>	Ø	J <sub>1</sub>	[kgcm <sup>2</sup> ]	Ø 11	0.46	0.45	0.31	0.34	0.31	0.34	0.31	0.31	0.31	
				Ø 14	1.01	1.00	0.86	0.89	0.86	0.89	0.86	0.86	0.86	0.86
				Ø 19	1.03	1.02	0.88	0.91	0.88	0.91	0.88	0.88	0.88	0.88
				Ø 24	1.84	1.83	1.69	1.72	1.69	1.72	1.69	1.69	1.69	1.69

- \* Other ratios available. 36, 64, 84, 180, 196, 300, 360, 500, 600, 700, 1 000 on request.
- a) Nominal output torque when operating at n<sub>1N</sub>.
- b) 1 000 cycles per hour max.
- c) Valid for an ambient temperature of 20°C and T<sub>2N</sub>. At higher ambient temperatures, please reduce speed.

- d) Valid 1 000 times the gearbox life.
- e) Valid for an input Ø of 19 mm in 1-stage and 14 mm in 2- and 3-stage.
- f) Values for 300 rpm.
- g) For other temperatures, please contact us. Nominal output torque when operating at n<sub>1N</sub>.
- h) Depending on the motor output shaft Ø.
- i) With i=10 and n<sub>1N</sub>=2500 rpm no load.

3-stage  
080  
SR

Rack



	F <sub>2B</sub>	[N]	Pinion 1			Pinion 2		
			Q6	Q7	Q9	Q6	Q7	Q9
Max acceleration force			7 490	2 963	5 036	7 490	2 963	5 036
Max acceleration torque	T <sub>2B</sub>	[Nm]	159	63	107	159	63	107
Precision			PI		P12	PI		P12
Feed force			High	Medium	Elevated	High	Medium	Elevated

Above values for rack and pinion take into consideration a number of load cycles: 1x10<sup>6</sup> for the rack; 1x10<sup>7</sup> for the pinion. Both in pulsating operation.

For proper sizing follow flowchart **calculate your ideal drive train** on pages 136 et seq.

More on the technical datasheets **your ideal drive train** on pages 120 et seq.

SR

100

I & 2-stage

Planetary gearboxes

Drawings



Input

<b>A</b>	for motor shaft	$L \leq 50$	$9 \leq \varnothing d \leq 24$	result in LA
<b>B</b>	for motor shaft	$51 < L \leq 64$	$24 < \varnothing d \leq 35$	result in LB


Output

<b>0</b>	Standard	<b>3</b>	Optional
----------	----------	----------	----------



		<b>1-stage</b>	<b>2-stage</b>	<b>3-stage</b>
<b>LA</b>	[mm]	126	164	202
<b>LB</b>	[mm]	140	178	216



Example SR 100 A0, 1-stage





Option 3 on request. Adjustments can reduce capacity.



Option 5 on request. Adjustments can reduce capacity.

\* depending on the motor. See pages 130 et seq.



Your ideal drive train

Function Package with gearbox, rack and pinion from Güdel



Pinion

	$m_n$	$P_t$	$z$	$A$	$b$	$D_k$	$D_0$	$D_v$	$L12$	$L13$	$x2$	$a$	$M$	
Pinion 1	[-]	2	6.66	25	48.526	25	57.05	53.052	53.052	63.3	51.0	24.0	27	0.4
Pinion 2	[-]	3	10.00	20	57.831	30	69.66	63.662	63.662	69.0	54.0	27.0	27	0.7

$m_n$ : Normal module,  $P_t$ : Transverse pitch [mm],  $z$ : Number of teeth,  $D_0$ : Pitch circle diameter for calculation,  $D_v$ : Pitch circle diameter for design,  $M$ : Weight [kg]

Available ratios	i		1-stage		2-stage				
			4	12	16	20	28	40	
Nominal torque S5 <sup>a)</sup>	T <sub>2N</sub>	[Nm]	300	300	300	300	300	300	
Acceleration torque S5 <sup>b)</sup>	T <sub>2B</sub>	[Nm]	370	370	370	370	370	370	
Nominal input speed S5 <sup>c)</sup>	n <sub>1N</sub>	[rpm]	2 200	2 600	2 800	2 800	2 800	2 800	
Maximum input speed S5	n <sub>1max</sub>	[rpm]	4 000	4 000	4 000	4 000	4 000	4 000	
Emergency stop torque <sup>d)</sup>	T <sub>2not</sub>	[Nm]	800	800	800	800	800	800	
Efficiency	η	[%]	96	93					
Lifetime	L <sub>h</sub>	[h]	> 20 000						
Weight	M	[kg]	8	10					
Angular backlash	j <sub>c</sub>	[arcmin]	Precision P 1 ≤ 1 / P 3 ≤ 3 / P 5 ≤ 5 / P 12 ≤ 12						
Torsionnal rigidity <sup>e)</sup>	C <sub>t2</sub>	[Nm/arcmin]	41.0	32.0	38.7	38.4	36.8	38.7	
Noise <sup>i)</sup>	L <sub>pA</sub>	[dB(A)]	≤ 71						
Max. permitted housing temperature <sup>g)</sup>	T	[°C]	90						
Protection class			IP 65						
Direction of rotation			Same way input / output						
Max. radial force on output shaft <sup>f)</sup>	F <sub>rmax</sub>	[N]	Center of output shaft: 6 600 / End of output shaft: 4 300						
Max. axial force on output shaft <sup>f)</sup>	F <sub>amax</sub>	[N]	6 000						
Color			Red, RAL 3003						
Inertia in kg·cm <sup>2</sup> <sup>h)</sup>	Ø14	J <sub>1</sub>	[kg·cm <sup>2</sup> ]	2.83	2.76	2.69	2.23	1.83	1.60
	Ø19			2.83	2.76	2.69	2.23	1.83	1.60
	Ø24			2.84	2.77	2.70	2.24	1.84	1.61
	Ø32			6.04	5.97	5.90	5.44	5.04	4.81
	Ø35			8.67	8.60	8.53	8.07	7.67	7.44

- a) Nominal output torque when operating at n<sub>1N</sub>.  
b) 1000 cycles per hour max.  
c) Valid for an ambient temperature of 20°C and T<sub>2N</sub>.  
At higher ambient temperatures, please reduce speed.  
d) Valid 1000 times the gearbox life.

- e) Valid for an input Ø of 24 mm in 1-stage and 19 mm in 2- and 3-stage.  
f) Values for 300 rpm.  
g) For other temperatures, please contact us. Nominal output torque when operating at n<sub>1N</sub>.  
h) Depending on the motor output shaft Ø.  
i) With n<sub>1N</sub>=2500 rpm no load.

## Rack



	F <sub>2B</sub>	[N]	Pinion 1			Pinion 2		
			Q6	Q7	Q9	Q6	Q7	Q9
Max acceleration force			7 540	4 107	4 805	16 163	7 565	12 980
Max acceleration torque	T <sub>2B</sub>	[Nm]	200	109	127	515	241	413
Precision			PI		PI2	PI		PI2
Feed force			High	Medium	Elevated	High	Medium	Elevated

Above values for rack and pinion take into consideration a number of load cycles:  
1x10<sup>6</sup> for the rack; 1x10<sup>7</sup> for the pinion. Both in pulsating operation.

For proper sizing follow flowchart  
**calculate your ideal drive train**  
on pages 136 et seq.

More on the technical datasheets  
**your ideal drive train** on pages  
120 et seq.

SR

100

3-stage



Planetary gearboxes

Drawings


Input Standard Output

<b>A</b>	for motor shaft	$L \leq 50$	$9 \leq \varnothing d \leq 24$	result in LA
<b>B</b>	for motor shaft	$51 < L \leq 64$	$24 < \varnothing d \leq 35$	result in LB



		1-stage	2-stage	3-stage
LA	[mm]	126	164	202
LB	[mm]	140	178	216





Example SR 100 A0. 3-stage



Option 3 on request. Adjustments can reduce capacity.



Option 5 on request. Adjustments can reduce capacity.



\* depending on the motor. See pages 130 et seq.

Your ideal drive train

Function Package with gearbox, rack and pinion from Güdel



Material 16MnCr5 DIN 1.7131  
 Teeth pressure angle  $\alpha = 20^\circ$ , helical teeth left,  $19^\circ 31' 42''$  hardened ( $58^{+4}$  HRC), ground, crowned  
 Quality 6f24 DIN 3962 / 63 / 67

Pinion

	$m_n$	$P_t$	$z$	A	b	$D_k$	$D_0$	$D_v$	L12	L13	x2	a	M	
Pinion 1	[-]	2	6.66	25	48.526	25	57.05	53.052	53.052	63.3	51.0	24.0	27	0.4
Pinion 2	[-]	3	10.00	20	57.831	30	69.66	63.662	63.662	69.0	54.0	27.0	27	0.7

$m_n$ : Normal module,  $P_t$ : Transverse pitch [mm],  $z$ : Number of teeth,  $D_0$ : Pitch circle diameter for calculation,  $D_v$ : Pitch circle diameter for design, M: Weight [kg]

Available ratios *	i		3-stage										
			60	80	100	112	120	140	160	200	280	400	
Nominal torque S5 <sup>a)</sup>	T <sub>2N</sub>	[Nm]	300	300	300	300	300	300	300	300	300	300	
Acceleration torque S5 <sup>b)</sup>	T <sub>2B</sub>	[Nm]	404	404	404	404	404	404	404	404	404	404	
Nominal input speed S5 <sup>c)</sup>	n <sub>1N</sub>	[rpm]	3 800	3 800	3 800	3 800	3 800	3 800	3 800	3 800	3 800	3 800	
Maximum input speed S5	n <sub>1max</sub>	[rpm]	4 500	4 500	4 500	4 500	4 500	4 500	4 500	4 500	4 500	4 500	
Emergency stop torque <sup>d)</sup>	T <sub>2not</sub>	[Nm]	800	800	800	800	800	800	800	800	800	800	
Efficiency	η	[%]	90										
Lifetime	L <sub>h</sub>	[h]	> 20 000										
Weight	M	[kg]	12										
Angular backlash	j <sub>c</sub>	[arcmin]	Precision P I ≤ 1 / P 3 ≤ 3 / P 5 ≤ 5 / P 12 ≤ 12										
Torsionnal rigidity <sup>e)</sup>	C <sub>t2</sub>	[Nm/arcmin]	38.4	38.4	34.3	37.0	37.0	38.4	37.0	38.4	37.0	37.0	
Noise <sup>i)</sup>	L <sub>pA</sub>	[dB(A)]	≤ 71										
Max. permitted housing temperature <sup>g)</sup>	T	[°C]	90										
Protection class			IP 65										
Direction of rotation			Same way input / output										
Max. radial force on output shaft <sup>f)</sup>	F <sub>rmax</sub>	[N]	Center of output shaft: 6 600 / End of output shaft: 4 300										
Max. axial force on output shaft <sup>f)</sup>	F <sub>amax</sub>	[N]	6 000										
Color			Red, RAL 3003										
Inertia in kg.cm <sup>2</sup> <sup>h)</sup>	Ø14	J <sub>I</sub>	[kgcm <sup>2</sup> ]	2.23	2.22	1.59	1.83	1.59	1.82	1.60	1.59	1.59	1.59
	Ø19			2.23	2.22	1.59	1.83	1.59	1.82	1.60	1.59	1.59	1.59
	Ø24			2.24	2.23	1.60	1.84	1.61	1.83	1.61	1.60	1.60	1.60
	Ø32			5.44	5.43	4.80	5.04	4.80	5.03	4.81	4.80	4.80	4.80
	Ø35			8.07	8.06	7.43	7.67	7.44	7.66	7.44	7.43	7.43	7.43

\* Other ratios available. 36, 64, 84, 180, 196, 300, 360, 500, 600, 700, 1000 on request.

a) Nominal output torque when operating at n<sub>1N</sub>.

b) 1000 cycles per hour max.

c) Valid for an ambient temperature of 20°C and T<sub>2N</sub>. At higher ambient temperatures, please reduce speed.

d) Valid 1000 times the gearbox life.

e) Valid for an input Ø of 24 mm in 1-stage and 19 mm in 2- and 3-stage.

f) Values for 300 rpm.

g) For other temperatures, please contact us. Nominal output torque when operating at n<sub>1N</sub>.

h) Depending on the motor output shaft Ø.

i) With n<sub>1N</sub>=2500 rpm no load.

Rack



			Pinion 1			Pinion 2		
			Q6	Q7	Q9	Q6	Q7	Q9
Max acceleration force	F <sub>2B</sub>	[N]	7 540	4 107	4 805	16 163	7 565	12 980
Max acceleration torque	T <sub>2B</sub>	[Nm]	200	109	127	515	241	413
Precision			PI		P12	PI		P12
Feed force			High	Medium	Elevated	High	Medium	Elevated

Above values for rack and pinion take into consideration a number of load cycles: 1x10<sup>6</sup> for the rack; 1x10<sup>7</sup> for the pinion. Both in pulsating operation.

For proper sizing follow flowchart **calculate your ideal drive train** on pages 136 et seq.

More on the technical datasheets **your ideal drive train** on pages 120 et seq.

SR

140 | 1 & 2-stage

Planetary gearboxes


Drawings

Input



<b>A</b>	for motor shaft	$L \leq 51$	$14 \leq \varnothing d \leq 24$	result in LA
<b>B</b>	for motor shaft	$51 < L \leq 63$	$24 < \varnothing d \leq 35$	result in LB
<b>C</b>	for motor shaft	$63 < L \leq 83$	$24 < \varnothing d \leq 42$	result in LC

		1-stage	2-stage	3-stage
LA	[mm]	143	185	227
LB	[mm]	155	197	239
LC	[mm]	175	217	

Output





Option 3 on request. Adjustments can reduce capacity.





Option 5 on request. Adjustments can reduce capacity.

Material 16MnCr5 DIN 1.7131  
Teeth pressure angle  $\alpha = 20^\circ$ , helical teeth left, 19°31'42" hardened (58<sup>+4</sup>HRC), ground, crowned  
Quality 6f24 DIN 3962 / 63 / 67



\* depending on the motor. See pages 130 et seq.



Example SR 140 A2, 1-stage

Your ideal drive train

Function Package with gearbox, rack and pinion from Güdel



Pinion

	$m_n$	$P_t$	$z$	$A$	$b$	$D_k$	$D_0$	$D_v$	$L12$	$L13$	$\times 2$	$a$	$M$	
Pinion 1	[-]	3	10.00	22	61.014	30	76.03	70.028	70.028	69.5	54.5	27.5	27	0.8
Pinion 2	[-]	4	13.33	20	77.441	40	92.88	84.883	84.883	79.0	59.0	32.0	27	1.6

$m_n$ : Normal module,  $P_t$ : Transverse pitch [mm],  $z$ : Number of teeth,  $D_0$ : Pitch circle diameter for calculation,  $D_v$ : Pitch circle diameter for design,  $M$ : Weight [kg]

Available ratios	i		1-stage		2-stage				
			4	12	16	20	28	40	
Nominal torque S5 <sup>a)</sup>	T <sub>2N</sub>	[Nm]	500	500	500	500	500	500	
Acceleration torque S5 <sup>b)</sup>	T <sub>2B</sub>	[Nm]	750	750	750	750	750	750	
Nominal input speed S5 <sup>c)</sup>	n <sub>1N</sub>	[rpm]	1 900	2 400	2 600	2 600	2 600	2 600	
Maximum input speed S5	n <sub>1max</sub>	[rpm]	3 600	3 600	3 600	3 600	3 600	3 600	
Emergency stop torque <sup>d)</sup>	T <sub>2not</sub>	[Nm]	1 300	1 300	1 300	1 300	1 300	1 300	
Efficiency	η	[%]	96	93					
Lifetime	L <sub>h</sub>	[h]	> 20 000						
Weight	M	[kg]	14	18					
Angular backlash	j <sub>c</sub>	[arcmin]	Precision P I ≤ I / P 3 ≤ 3 / P 5 ≤ 5 / P 12 ≤ 12						
Torsionnal rigidity <sup>e)</sup>	C <sub>t2</sub>	[Nm/arcmin]	106.2	85.0	95.7	102.1	95.7	95.7	
Noise <sup>f)</sup>	L <sub>pA</sub>	[dB(A)]	≤ 71						
Max. permitted housing temperature <sup>g)</sup>	T	[°C]	90						
Protection class			IP 65						
Direction of rotation			Same way input / output						
Max. radial force on output shaft <sup>f)</sup>	F <sub>rmax</sub>	[N]	Center of output shaft: 9 950 / End of output shaft: 6 700						
Max. axial force on output shaft <sup>f)</sup>	F <sub>amax</sub>	[N]	10 300						
Color			Red, RAL 3003						
Inertia in kg·cm <sup>2</sup> <sup>h)</sup>	Ø14	J <sub>1</sub>	[kg·cm <sup>2</sup> ]	7.12	6.86	6.63	5.29	4.15	3.48
	Ø19			7.12	6.86	6.63	5.29	4.15	3.48
	Ø24			8.13	7.87	7.64	6.30	5.16	4.49
	Ø32			10.33	10.07	9.84	8.50	7.36	6.69
	Ø35			13.16	12.90	12.67	11.33	10.19	9.52
	Ø38			18.35	18.09	17.86	16.52	15.38	14.71
	Ø42			17.95	17.69	17.46	16.12	14.98	14.31

a) Nominal output torque when operating at n<sub>1N</sub>.

b) 1000 cycles per hour max.

c) Valid for an ambient temperature of 20°C and T<sub>2N</sub>.  
At higher ambient temperatures, please reduce speed.

d) Valid 1000 times the gearbox life.

e) Valid for an input Ø of 38 mm in 1-stage and 24 mm in 2- and 3-stage.

f) Values for 300 rpm.

g) For other temperatures, please contact us. Nominal output torque when operating at n<sub>1N</sub>.

h) Depending on the motor output shaft Ø.

i) With n<sub>1N</sub>=2500 rpm no load.

## Rack



	F <sub>2B</sub>	[N]	Pinion 1			Pinion 2		
			Q6	Q7	Q9	Q6	Q7	Q9
Max acceleration force			16 230	8 715	12 919	28 585	14 084	24 045
Max acceleration torque	T <sub>2B</sub>	[Nm]	568	305	452	1 213	598	1 021
Precision			PI		PI2	PI		PI2
Feed force			High	Medium	Elevated	High	Medium	Elevated

Above values for rack and pinion take into consideration a number of load cycles:  
1x10<sup>6</sup> for the rack; 1x10<sup>7</sup> for the pinion. Both in pulsating operation.For proper sizing follow flowchart  
**calculate your ideal drive train**  
on pages 136 et seq.More on the technical datasheets  
**your ideal drive train** on pages  
120 et seq.

SR

140

3-stage

Planetary gearboxes

Drawings



Input

- A** for motor shaft  $L \leq 51$
- B** for motor shaft  $51 < L \leq 63$
- C** for motor shaft  $63 < L \leq 83$

		1-stage	2-stage	3-stage
LA	[mm]	143	185	227
LB	[mm]	155	197	239
LC	[mm]	175	217	

Output

Standard Optional






\* depending on the motor. See pages 130 et seq.





Example SR 140 A4, 1-stage

Your ideal drive train

Function Package with gearbox, rack and pinion from Güdel



Option 3 on request. Adjustments can reduce capacity.



Option 5 on request. Adjustments can reduce capacity.

Material 16MnCr5 DIN 1.7131  
Teeth pressure angle  $\alpha = 20^\circ$ , helical teeth left, 19°31'42" hardened (58<sup>+4</sup>HRC), ground, crowned  
Quality 6f24 DIN 3962 / 63 / 67

Pinion



	$m_n$	$P_t$	$z$	A	b	$D_k$	$D_0$	$D_v$	L12	L13	x2	a	M	
Pinion 1	[-]	3	10.00	22	61.014	30	76.03	70.028	70.028	69.5	54.5	27.5	27	0.8
Pinion 2	[-]	4	13.33	20	77.441	40	92.88	84.883	84.883	79.0	59.0	32.0	27	1.6

$m_n$ : Normal module,  $P_t$ : Transverse pitch [mm],  $z$ : Number of teeth,  $D_0$ : Pitch circle diameter for calculation,  $D_v$ : Pitch circle diameter for design, M: Weight [kg]

Available ratios *	i		3-stage										
			60	80	100	112	120	140	160	200	280	400	
Nominal torque S5 <sup>a)</sup>	T <sub>2N</sub>	[Nm]	500	500	500	500	500	500	500	500	500	500	500
Acceleration torque S5 <sup>b)</sup>	T <sub>2B</sub>	[Nm]	750	750	750	750	750	750	750	750	750	750	750
Nominal input speed S5 <sup>c)</sup>	n <sub>1N</sub>	[rpm]	3 500	3 500	3 500	3 500	3 500	3 500	3 500	3 500	3 500	3 500	3 500
Maximum input speed S5	n <sub>1max</sub>	[rpm]	4 000	4 000	4 000	4 000	4 000	4 000	4 000	4 000	4 000	4 000	4 000
Emergency stop torque <sup>d)</sup>	T <sub>2not</sub>	[Nm]	1 300	1 300	1 300	1 300	1 300	1 300	1 300	1 300	1 300	1 300	1 300
Efficiency	η	[%]	90										
Lifetime	L <sub>h</sub>	[h]	> 20 000										
Weight	M	[kg]	22										
Angular backlash	j <sub>c</sub>	[arcmin]	Precision P 1 ≤ 1 / P 3 ≤ 3 / P 5 ≤ 5 / P 12 ≤ 12										
Torsionnal rigidity <sup>e)</sup>	C <sub>t2</sub>	[Nm/arcmin]	92	92	84	86	86	92	86	92	86	86	86
Noise <sup>i)</sup>	L <sub>pA</sub>	[dB(A)]	≤ 71										
Max. permitted housing temperature <sup>g)</sup>	T	[°C]	90										
Protection class			IP 65										
Direction of rotation			Same way input / output										
Max. radial force on output shaft <sup>f)</sup>	F <sub>rmax</sub>	[N]	Center of output shaft: 9 950 / End of output shaft: 6 700										
Max. axial force on output shaft <sup>f)</sup>	F <sub>amax</sub>	[N]	10 300										
Color			Red, RAL 3003										
Inertia in kg·cm <sup>2</sup> <sup>h)</sup>	Ø14	J <sub>1</sub>	[kg·cm <sup>2</sup> ]	5.28	5.27	3.44	4.14	3.47	4.11	3.47	3.46	3.45	3.44
	Ø19			5.28	5.27	3.44	4.14	3.47	4.11	3.47	3.46	3.45	3.44
	Ø24			6.29	6.28	4.45	5.15	4.48	5.12	4.48	4.47	4.46	4.45
	Ø32			8.49	8.48	6.65	7.35	6.68	7.32	6.68	6.67	6.66	6.65
	Ø35			11.32	11.31	9.48	10.18	9.51	10.15	9.51	9.50	9.49	9.48
	Ø38			16.51	16.50	14.67	15.37	14.70	15.34	14.70	14.69	14.68	14.67
	Ø42			16.11	16.10	14.27	14.97	14.30	14.94	14.30	14.29	14.28	14.27

\* Other ratios available. 36, 64, 84, 180, 196, 300, 360, 500, 600, 700, 1 000 on request.

a) Nominal output torque when operating at n<sub>1N</sub>.

b) Maximal 1 000 Zyklen pro Stunde

c) Valid for an ambient temperature of 20°C and T<sub>2N</sub>.

At higher ambient temperatures, please reduce speed.

d) Valid 1000 times the gearbox life.

e) Valid for an input Ø of 38 mm in 1-stage and 24 mm in 2- and 3-stage.

f) Values for 300 rpm.

g) For other temperatures, please contact us. Nominal output torque when operating at n<sub>1N</sub>.

h) Depending on the motor output shaft Ø.

i) With n<sub>1N</sub>=2500 rpm no load.

## Rack



	F <sub>2B</sub>	[N]	Pinion 1			Pinion 2		
			Q6	Q7	Q9	Q6	Q7	Q9
Max acceleration force			16 230	8 715	12 919	28 585	14 084	24 045
Max acceleration torque	T <sub>2B</sub>	[Nm]	568	305	452	1 213	598	1 021
Precision			PI		P12	PI		P12
Feed force			High	Medium	Elevated	High	Medium	Elevated

Above values for rack and pinion take into consideration a number of load cycles:  
1x10<sup>6</sup> for the rack; 1x10<sup>7</sup> for the pinion. Both in pulsating operation.

For proper sizing follow flowchart  
**calculate your ideal drive train**  
on pages 136 et seq.

More on the technical datasheets  
**your ideal drive train** on pages  
120 et seq.

SR

180

I & 2-stage

Planetary gearboxes

Drawings

Input



<b>A</b>	for motor shaft	$L \leq 60$	$19 \leq \varnothing d \leq 32$	result in LA
<b>B</b>	for motor shaft	$60 < L \leq 85$	$32 < \varnothing d \leq 48$	result in LB
<b>C</b>	for motor shaft	$85 < L \leq 111$	$32 < \varnothing d \leq 48$	result in LC

		1-stage	2-stage	3-stage
LA	[mm]	168	220	273
LB	[mm]	193	246	298
LC	[mm]	219	272	


Output



0



3




Detail output shaft



Option 3 on request. Adjustments can reduce capacity.




4




Detail output shaft


14 JS9



1




Detail output shaft




\* depending on the motor. See pages 130 et seq.



2




Detail output shaft




Option 5 on request. Adjustments can reduce capacity.





5



Detail output shaft



Material 16MnCr5 DIN 1.7131  
Teeth pressure angle  $\alpha = 20^\circ$ , helical teeth left, 19°31'42" hardened (58<sup>+4</sup>HRC), ground, crowned  
Quality 6f24 DIN 3962 / 63 / 67



Example SR 180 A2, 1-stage

Your ideal drive train

Function Package with gearbox, rack and pinion from Güdel



Pinion



	$m_n$	$P_t$	$z$	A	b	$D_k$	$D_0$	$D_v$	L12	L13	x2	a	M	
Pinion 1	[-]	4	13.33	20	77.441	40	92.88	84.883	84.883	89.5	69.5	31.5	38	1.5
Pinion 2	[-]	5	16.66	20	87.052	50	116.10	106.103	106.103	95.5	70.5	32.5	38	3.0

$m_n$ : Normal module,  $P_t$ : Transverse pitch [mm],  $z$ : Number of teeth,  $D_0$ : Pitch circle diameter for calculation,  $D_v$ : Pitch circle diameter for design, M: Weight [kg]

Available ratios	i		1-stage		2-stage				
			4	12	16	20	28	40	
Nominal torque S5 <sup>a)</sup>	T <sub>2N</sub>	[Nm]	1 100	1 100	1 100	1 100	1 100	1 100	
Acceleration torque S5 <sup>b)</sup>	T <sub>2B</sub>	[Nm]	1 500	1 500	1 500	1 500	1 500	1 500	
Nominal input speed S5 <sup>c)</sup>	n <sub>1N</sub>	[rpm]	1 300	2 200	2 400	2 400	2 400	2 400	
Maximum input speed S5	n <sub>1max</sub>	[rpm]	3 100	3 600	3 600	3 600	3 600	3 600	
Emergency stop torque <sup>d)</sup>	T <sub>2not</sub>	[Nm]	2 780	2 780	2 780	2 780	2 780	2 780	
Efficiency	η	[%]	96	93					
Lifetime	L <sub>h</sub>	[h]	> 20 000						
Weight	M	[kg]	32	39					
Angular backlash	j <sub>c</sub>	[arcmin]	Precision P I ≤ I / P 3 ≤ 3 / P 5 ≤ 5 / P 12 ≤ 12						
Torsionnal rigidity <sup>e)</sup>	C <sub>t2</sub>	[Nm/arcmin]	191.8	147.5	172.5	182.7	172.5	172.5	
Noise <sup>f)</sup>	L <sub>pA</sub>	[dB(A)]	≤ 72						
Max. permitted housing temperature <sup>g)</sup>	T	[°C]	90						
Protection class			IP 65						
Direction of rotation			Same way input / output						
Max. radial force on output shaft <sup>f)</sup>	F <sub>rmax</sub>	[N]	Center of output shaft: 18 000 / End of output shaft: 13 000						
Max. axial force on output shaft <sup>f)</sup>	F <sub>amax</sub>	[N]	15 000						
Color			Red, RAL 3003						
Inertia in kg·cm <sup>2</sup> h)	Ø19	J <sub>1</sub>	[kg·cm <sup>2</sup> ]	23.35	23.57	22.65	16.76	11.90	9.07
	Ø24			24.40	24.62	23.70	17.81	12.95	10.12
	Ø32			26.61	26.83	25.91	20.02	15.16	12.33
	Ø35			29.53	29.75	28.83	22.94	18.08	15.25
	Ø38			35.13	35.35	34.43	28.54	23.68	20.85
	Ø42			34.63	34.85	33.93	28.04	23.18	20.35
	Ø48			35.03	35.25	34.33	28.44	23.58	20.75

a) Nominal output torque when operating at n<sub>1N</sub>.

b) 1000 cycles per hour max.

c) Valid for an ambient temperature of 20°C and T<sub>2N</sub>.  
At higher ambient temperatures, please reduce speed.

d) Valid 1000 times the gearbox life.

e) Valid for an input Ø of 48 mm in 1-stage and 38 mm in 2- and 3-stage.

f) Values for 300 rpm.

g) For other temperatures, please contact us. Nominal output torque when operating at n<sub>1N</sub>.

h) Depending on the motor output shaft Ø.

i) With n<sub>1N</sub>=2500 rpm no load.

## Rack



	F <sub>2B</sub>	[N]	Pinion 1			Pinion 2		
			Q6	Q7	Q9	Q6	Q7	Q9
Max acceleration force			28 585	14 084	24 045	44 505	23 785	40 048
Max acceleration torque	T <sub>2B</sub>	[Nm]	1 213	598	1 021	2 361	1 262	2 125
Precision			PI		PI2	PI		PI2
Feed force			High	Medium	Elevated	High	Medium	Elevated

Above values for rack and pinion take into consideration a number of load cycles:  
1×10<sup>6</sup> for the rack; 1×10<sup>7</sup> for the pinion. Both in pulsating operation.For proper sizing follow flowchart  
**calculate your ideal drive train**  
on pages 136 et seq.More on the technical datasheets  
**your ideal drive train** on pages  
120 et seq.

SR

180

3-stage

Planetary gearboxes

Drawings



Input

<b>A</b>	for motor shaft	$L \leq 60$	$19 \leq \varnothing d \leq 32$	result in LA
<b>B</b>	for motor shaft	$60 < L \leq 85$	$32 < \varnothing d \leq 48$	result in LB
<b>C</b>	for motor shaft	$85 < L \leq 111$	$32 < \varnothing d \leq 48$	result in LC

		1-stage	2-stage	3-stage
LA	[mm]	168	220	273
LB	[mm]	193	246	298
LC	[mm]	219	272	

Output


Standard Optional





\* depending on the motor. See pages 130 et seq.



Example SR 180 A5, 1-stage



Option 3 on request. Adjustments can reduce capacity.




Option 5 on request. Adjustments can reduce capacity.

Material 16MnCr5 DIN 1.7131  
Teeth pressure angle  $\alpha = 20^\circ$ , helical teeth left, 19°31'42" hardened (58<sup>+4</sup>HRC), ground, crowned  
Quality 6f24 DIN 3962 / 63 / 67

Your ideal drive train

Function Package with gearbox, rack and pinion from Güdel



Pinion

	$m_n$	$P_t$	$z$	A	b	$D_k$	$D_0$	$D_v$	L12	L13	x2	a	M	
Pinion 1	[-]	4	13.33	20	77.441	40	92.88	84.883	84.883	89.5	69.5	31.5	38	1.5
Pinion 2	[-]	5	16.66	20	87.052	50	116.10	106.103	106.103	95.5	70.5	32.5	38	3.0

$m_n$ : Normal module,  $P_t$ : Transverse pitch [mm],  $z$ : Number of teeth,  $D_0$ : Pitch circle diameter for calculation,  $D_v$ : Pitch circle diameter for design, M: Weight [kg]

Available ratios *	i		3-stage										
			60	80	100	112	120	140	160	200	280	400	
Nominal torque S5 <sup>a)</sup>	T <sub>2N</sub>	[Nm]	1 100	1 100	1 100	1 100	1 100	1 100	1 100	1 100	1 100	1 100	
Acceleration torque S5 <sup>b)</sup>	T <sub>2B</sub>	[Nm]	1 500	1 500	1 500	1 500	1 500	1 500	1 500	1 500	1 500	1 500	
Nominal input speed S5 <sup>c)</sup>	n <sub>1N</sub>	[rpm]	3 000	3 000	3 000	3 000	3 000	3 000	3 000	3 000	3 000	3 000	
Maximum input speed S5	n <sub>1max</sub>	[rpm]	3 600	3 600	3 600	3 600	3 600	3 600	3 600	3 600	3 600	3 600	
Emergency stop torque <sup>d)</sup>	T <sub>2not</sub>	[Nm]	2 780	2 780	2 780	2 780	2 780	2 780	2 780	2 780	2 780	2 780	
Efficiency	η	[%]	90										
Lifetime	L <sub>h</sub>	[h]	> 20 000										
Weight	M	[kg]	46										
Angular backlash	j <sub>c</sub>	[arcmin]	Precision P 1 ≤ 1 / P 3 ≤ 3 / P 5 ≤ 5 / P 12 ≤ 12										
Torsionnal rigidity <sup>e)</sup>	C <sub>t2</sub>	[Nm/arcmin]	173.4	173.4	173.1	164.1	164.1	173.4	164.1	140.0	164.1	164.1	
Noise <sup>i)</sup>	L <sub>pA</sub>	[dB(A)]	≤ 72										
Max. permitted housing temperature <sup>g)</sup>	T	[°C]	90										
Protection class			IP 65										
Direction of rotation			Same way input / output										
Max. radial force on output shaft <sup>f)</sup>	F <sub>rmax</sub>	[N]	Center of output shaft: 18 000 / End of output shaft: 13 000										
Max. axial force on output shaft <sup>f)</sup>	F <sub>amax</sub>	[N]	15 000										
Color			Red, RAL 3003										
Inertia in kg.cm <sup>2</sup> <sup>h)</sup>	Ø19	J <sub>1</sub>	[kgcm <sup>2</sup> ]	16.77	16.73	8.93	11.88	9.07	11.76	9.06	9.00	8.96	8.93
	Ø24			17.82	17.78	9.98	12.93	10.12	12.81	10.11	10.05	10.01	9.98
	Ø32			20.03	19.99	12.19	15.14	12.33	15.02	12.32	12.26	12.22	12.19
	Ø35			22.95	22.91	15.11	18.06	15.25	17.94	15.24	15.18	15.14	15.11
	Ø38			28.55	28.51	20.71	23.66	20.85	23.54	20.84	20.78	20.74	20.71
	Ø42			28.05	28.01	20.21	23.16	20.35	23.04	20.34	20.28	20.24	20.21
	Ø48			28.45	28.41	20.61	23.56	20.75	23.44	20.74	20.68	20.64	20.61

\* Other ratios available. 36, 64, 84, 180, 196, 300, 360, 500, 600, 700, 1000 on request.

a) Nominal output torque when operating at n<sub>1N</sub>.

b) 1000 cycles per hour max.

c) Valid for an ambient temperature of 20°C and T<sub>2N</sub>.  
At higher ambient temperatures, please reduce speed.

d) Valid 1000 times the gearbox life.

e) Valid for an input Ø of 48 mm in 1-stage and 38 mm in 2- and 3-stage.

f) Values for 300 rpm.

g) For other temperatures, please contact us. Nominal output torque when operating at n<sub>1N</sub>.

h) Depending on the motor output shaft Ø.

i) With n<sub>1N</sub>=2500 rpm no load.

Rack



			Pinion 1			Pinion 2		
			Q6	Q7	Q9	Q6	Q7	Q9
Max acceleration force	F <sub>2B</sub>	[N]	28 585	14 084	24 045	44 505	23 785	40 048
Max acceleration torque	T <sub>2B</sub>	[Nm]	1 213	598	1 021	2 361	1 262	2 125
Precision			P1		P12	P1		P12
Feed force			High	Medium	Elevated	High	Medium	Elevated

Above values for rack and pinion take into consideration a number of load cycles:  
1x10<sup>6</sup> for the rack; 1x10<sup>7</sup> for the pinion. Both in pulsating operation.

For proper sizing follow flowchart  
**calculate your ideal drive train**  
on pages 136 et seq.

More on the technical datasheets  
**your ideal drive train** on pages  
120 et seq.



Available ratios	i		1-stage		2-stage				
			4	12	16	20	28	40	
Nominal torque S5 <sup>a)</sup>	T <sub>2N</sub>	[Nm]	3 600	3 600	3 600	3 600	3 600	3 600	
Acceleration torque S5 <sup>b)</sup>	T <sub>2B</sub>	[Nm]	4 800	4 800	4 800	4 800	4 800	4 800	
Nominal input speed S5 <sup>c)</sup>	n <sub>1N</sub>	[rpm]	900	1 500	1 700	1 700	1 700	1 700	
Maximum input speed S5	n <sub>1max</sub>	[rpm]	2 000	3 100	3 100	3 100	3 100	3 100	
Emergency stop torque <sup>d)</sup>	T <sub>2not</sub>	[Nm]	8 500	8 500	8 500	8 500	8 500	8 500	
Efficiency	η	[%]	96	93					
Lifetime	L <sub>h</sub>	[h]	> 20 000						
Weight	M	[kg]	70	90					
Angular backlash	j <sub>c</sub>	[arcmin]	Precision P I ≤ I / P 3 ≤ 3 / P 5 ≤ 5 / P 12 ≤ 12						
Torsionnal rigidity <sup>e)</sup>	C <sub>t2</sub>	[Nm/arcmin]	718.8	593.5	611.0	628.5	611.0	611.0	
Noise <sup>i)</sup>	L <sub>pA</sub>	[dB(A)]	≤ 73						
Max. permitted housing temperature <sup>g)</sup>	T	[°C]	90						
Protection class			IP 65						
Direction of rotation			Same way input / output						
Max. radial force on output shaft <sup>f)</sup>	F <sub>rmax</sub>	[N]	Center of output shaft: 37 500 / End of output shaft: 25 000						
Max. axial force on output shaft <sup>f)</sup>	F <sub>amax</sub>	[N]	34 000						
Color			Red, RAL 3003						
Inertia in kg·cm <sup>2</sup> h)	Ø24	J <sub>1</sub>	[kg·cm <sup>2</sup> ]	83.3	79.1	74.9	73.3	34.0	22.9
	Ø32			85.5	81.3	77.1	75.5	36.2	25.1
	Ø35			90.8	86.6	82.4	80.8	41.5	30.4
	Ø38			94.2	90.0	85.8	84.2	44.9	33.8
	Ø42			93.7	89.5	85.3	83.7	44.4	33.3
	Ø48			93.9	89.7	85.5	83.9	44.6	33.5
	Ø55			116.5	112.3	108.1	106.5	67.2	56.1

a) Nominal output torque when operating at n<sub>1N</sub>.

b) 1000 cycles per hour max.

c) Valid for an ambient temperature of 20°C and T<sub>2N</sub>.  
At higher ambient temperatures, please reduce speed.

d) Valid 1000 times the gearbox life.

e) Valid for an input Ø of 55 mm in 1-stage and 48 mm in 2- and 3-stage.

f) Values for 300 rpm.

g) For other temperatures, please contact us. Nominal output torque when operating at n<sub>1N</sub>.

h) Depending on the motor output shaft Ø.

i) With n<sub>1N</sub>=1800 rpm no load.

## Rack



	F <sub>2B</sub>	[N]	Pinion 1			Pinion 2		
			Q6	Q7	Q9	Q6	Q7	Q9
Max acceleration force			44 786	29 748	39 992	63 300	-	59 005
Max acceleration torque	T <sub>2B</sub>	[Nm]	2 851	1 894	2 546	4 030	-	3 756
Precision			PI		PI2	PI		PI2
Feed force			High	Medium	Elevated	High	Medium	Elevated

Above values for rack and pinion take into consideration a number of load cycles:  
1x10<sup>6</sup> for the rack; 1x10<sup>7</sup> for the pinion. Both in pulsating operation.For proper sizing follow flowchart  
**calculate your ideal drive train**  
on pages 136 et seq.More on the technical datasheets  
**your ideal drive train** on pages  
120 et seq.

SR

240

3-stage

Planetary gearboxes

Drawings

Input





**A** for motor shaft L ≤ 85 24 ≤ Ød ≤ 48 result in LA  
**B** for motor shaft 85 < L ≤ 115 48 < Ød ≤ 55 result in LB

		1-stage	2-stage	3-stage
LA	[mm]	229	300	371
LB	[mm]	259	330	





Output



Optional





Option 3 on request. Adjustments can reduce capacity.





Option 5 on request. Adjustments can reduce capacity.

Material 16MnCr5 DIN 1.7131  
 Teeth pressure angle α = 20°, helical teeth left, 19°31'42" hardened (58<sup>+4</sup>HRC), ground, crowned  
 Quality 6f24 DIN 3962 / 63 / 67



\* depending on the motor. See pages 130 et seq.



Example SR 240 B2, 1-stage

Your ideal drive train

Function Package with gearbox, rack and pinion from Güdel



Pinion



	m <sub>n</sub>	P <sub>t</sub>	z	A	b	D <sub>k</sub>	D <sub>0</sub>	D <sub>v</sub>	L12	L13	x2	a	M	
Pinion 1	[-]	5	16.66	24	97.662	50	137.32	127.324	127.324	120.5	95.5	47.5	48	5.4
Pinion 2	[-]	6	20.00	20	106.662	60	139.32	127.324	127.324	119.0	89.0	41.0	48	5.6

m<sub>n</sub>: Normal module, P<sub>t</sub>: Transverse pitch [mm], z: Number of teeth, D<sub>0</sub>: Pitch circle diameter for calculation, D<sub>v</sub>: Pitch circle diameter for design, M: Weight [kg]

SR

240

3-stage

Planetary gearboxes

Available ratios *	i		3-stage										
			60	80	100	112	120	140	160	200	280	400	
Nominal torque S5 <sup>a)</sup>	T <sub>2N</sub>	[Nm]	3 600	3 600	3 600	3 600	3 600	3 600	3 600	3 600	3 600	3 600	
Acceleration torque S5 <sup>b)</sup>	T <sub>2B</sub>	[Nm]	4 800	4 800	4 800	4 800	4 800	4 800	4 800	4 800	4 800	4 800	
Nominal input speed S5 <sup>c)</sup>	n <sub>1N</sub>	[rpm]	2 100	2 100	2 100	2 100	2 100	2 100	2 100	2 100	2 100	2 100	
Maximum input speed S5	n <sub>1max</sub>	[rpm]	3 100	3 100	3 100	3 100	3 100	3 100	3 100	3 100	3 100	3 100	
Emergency stop torque <sup>d)</sup>	T <sub>2not</sub>	[Nm]	8 500	8 500	8 500	8 500	8 500	8 500	8 500	8 500	8 500	8 500	
Efficiency	η	[%]	90										
Lifetime	L <sub>h</sub>	[h]	> 20 000										
Weight	M	[kg]	110										
Angular backlash	j <sub>c</sub>	[arcmin]	Precision P 1 ≤ 1 / P 3 ≤ 3 / P 5 ≤ 5 / P 12 ≤ 12										
Torsionnal rigidity <sup>e)</sup>	C <sub>t2</sub>	[Nm/arcmin]	532.4	532.4	593.5	550.0	550.0	564.5	550.0	564.5	550.0	561.5	
Noise <sup>i)</sup>	L <sub>pA</sub>	[dB(A)]	≤ 73										
Max. permitted housing temperature <sup>g)</sup>	T	[°C]	90										
Protection class			IP 65										
Direction of rotation			Same way input / output										
Max. radial force on output shaft <sup>f)</sup>	F <sub>rmax</sub>	[N]	Center of output shaft: 37 500 / End of output shaft: 25 000										
Max. axial force on output shaft <sup>f)</sup>	F <sub>amax</sub>	[N]	34 000										
Color			Red, RAL 3003										
Inertia in kg.cm <sup>2</sup> <sup>h)</sup>	Ø24	J <sub>1</sub>	[kgcm <sup>2</sup> ]	78.0	74.2	22.3	33.9	23.4	33.9	22.8	22.8	22.4	22.3
	Ø32			80.2	76.4	24.5	36.1	25.6	36.1	25.0	25.0	24.6	24.5
	Ø35			85.5	81.7	29.8	41.4	30.9	41.4	30.3	30.3	29.9	29.8
	Ø38			88.9	85.1	33.2	44.8	34.3	44.8	33.7	33.7	33.3	33.2
	Ø42			88.4	84.6	32.7	44.3	33.8	44.3	33.2	33.2	32.8	32.7
	Ø48			88.6	84.8	32.9	44.5	34.0	44.5	33.4	33.4	33.0	32.9
	Ø55			111.2	107.4	55.5	67.1	56.6	67.1	56.0	56.0	55.6	55.5

\* Other ratios available. 36, 64, 84, 180, 196, 300, 360, 500, 600, 700, 1 000 on request.

a) Nominal output torque when operating at n<sub>1N</sub>.

b) 1000 cycles per hour max.

c) Valid for an ambient temperature of 20°C and T<sub>2N</sub>.  
At higher ambient temperatures, please reduce speed.

d) Valid 1000 times the gearbox life.

e) Valid for an input Ø of 55 mm in 1-stage and 48 mm in 2- and 3-stage.

f) Values for 300 rpm.

g) For other temperatures, please contact us. Nominal output torque when operating at n<sub>1N</sub>.

h) Depending on the motor output shaft Ø.

i) With n<sub>1N</sub>=1800 rpm no load.

## Rack



	F <sub>2B</sub>	[N]	Pinion 1			Pinion 2		
			Q6	Q7	Q9	Q6	Q7	Q9
Max acceleration force			44 786	29 748	39 992	63 300	-	59 005
Max acceleration torque	T <sub>2B</sub>	[Nm]	2 851	1 894	2 546	4 030	-	3 756
Precision			PI		PI2	PI		PI2
Feed force			High	Medium	Elevated	High	Medium	Elevated

Above values for rack and pinion take into consideration a number of load cycles:  
1x10<sup>6</sup> for the rack; 1x10<sup>7</sup> for the pinion. Both in pulsating operation.

For proper sizing follow flowchart  
**calculate your ideal drive train**  
on pages 136 et seq.

More on the technical datasheets  
**your ideal drive train** on pages  
120 et seq.