


2. Llaves



Llaves de golpe y tracción


LLAVE DE ESTRELLA DE GOLPE



- Acero aleado de alto rendimiento
- DIN 7444
- 24-46 mm, 34-40 HRc
- 50-100 mm, 30-36 HRc
- -2: Envase industrial

R		S mm	D mm	E mm	L mm	g
030241	1	24	43	15	165	235
030271	1	27	46	16	180	290
030301	1	30	53	18	195	435
030321	1	32	53	18	195	415
030341	1	34	59	18	205	510
030361	1	36	59	18	205	510
030381	1	38	59	18	205	510
030411	1	41	65	20	230	710
030461	1	46	74	22,5	240	980
030501	1	50	79	24	255	1.050
030551	1	55	86	25	270	1.410
030601	1	60	93	26	280	1.640
30-65-2	1	65	103	29	300	2.180
30-70-2	1	70	109	33	315	2.400
30-75-2	1	75	114	34	330	2.775
30-80-2	1	80	125	36	348	3.150
30-85-2	1	85	129	37	360	4.860
30-90-2	1	90	148	40	379	5.680
30-95-2	1	95	151	41	395	6.500
30-100-2	1	100	154	45	405	7.830

LLAVE FIJA DE GOLPE



- Acero aleado de alto rendimiento
- DIN 133
- 30-46 mm, 34-40 HRc
- 50-85 mm, 30-36 HRc
- -2: Envase industrial

R		S mm	A mm	B mm	L mm	g
31-30-2	1	30	17	65	190	550
31-32-2	1	32	17	67	195	560
31-36-2	1	36	18	77	210	845
31-41-2	1	41	19	88	230	1.040
31-46-2	1	46	20	96	250	1.375
31-50-2	1	50	21	106	275	1.670
31-55-2	1	55	24	116	305	2.175
31-60-2	1	60	24	125	315	2.455
31-65-2	1	65	28	136	345	3.550
31-70-2	1	70	30	148	370	4.075
31-75-2	1	75	30	158	385	5.170
31-80-2	1	80	33	170	400	5.785
31-85-2	1	85	33	174	410	6.870

