

Performance under Pressure

PRESSURE GAUGES

PRESSURE GAUGES




Type **AV-AVD-AT-AY**

Capacity **5 - 250 Tn**

Max. pressure **0 - 1.000 bar**



- ✓ High accuracy gauges, $\pm 1.6\%$ full scale.
- ✓ Essential for monitoring working pressure or force.
- ✓ Glycerine filled gauges.
- ✓ Available as system pressure gauges or as dual scale gauges to measure load on specific cylinders.



WARNING

Do not exceed the **70%** of the nominal capacity of the gauge.



Digital pressure gauge: **AVD10008**
Thread: 1/4"-BSP
Gauge adaptor: **AZ1507**



Pressure gauge for Hollow Cylinders: **ATH**
Digital Pressure Transducer: **AVT**

Used with	Model	Type		Scale	D	E	R	Gauge Adaptor
	LARZEP	Tn	kg/cm ²		mm	mm		
All Cylinders	AV10006	-	1000	50	68	31	1/4"-NPT	AZ1502
	AV10008	-	1000	20	80	35	3/8"-BSP	AZ1501
	AV10010	-	1000	10	100	35	3/8"-BSP	AZ1501
Cylinders	AT00410	5 / 10	1000	-	100	35	3/8"-BSP	AZ1501
	AT01610	16 / 23	1000	-	100	35	3/8"-BSP	AZ1501
	AT03010	30 / 50	1000	-	100	35	3/8"-BSP	AZ1501
	AT07510	75 / 100	1000	-	100	35	3/8"-BSP	AZ1501
	AT15010	150 / 200	1000	-	100	35	3/8"-BSP	AZ1501
Press 10 Tn	AY01008	10	-	0,5	80	35	3/8"-BSP	AZ1501
Press 20 Tn	AY02008	20	-	0,5	80	35	3/8"-BSP	AZ1501
Press 30 Tn	AY03008	30	-	2	80	35	3/8"-BSP	AZ1501
Press 60 Tn	AY06010	60	-	2	100	35	3/8"-BSP	AZ1501
Press 120 Tn	AY12010	120	-	4	100	35	3/8"-BSP	AZ1501
Press 250 Tn	AY25010	250	-	5	100	35	3/8"-BSP	AZ1501