PIPE BENDERS



Туре	VA - VB				
Capacity	1/2 - 3 inch				

Max. pressure

700 bar


PIPE BENDERS



- Suitable for carrying out bending operations with plumbing pipes DIN 2440 and DIN2441.
- Pipe bending capacities of up to 2" and 3" NB.
- Maximum bending angle: 180°.
- Built-in pump models VA and VB.
- Equipped with a safety relief valve to prevent overpressure.
- Delivered in storage box.
- VB1527 model equipped with a tripod stand.

HYDRAULIC PIPE BENDERS

Pipe	Model	Capacity	Stroke	Tripod Stand	Weight	
II .	LARZEP	Tn	mm	*	kg	
1/2" - 2"	VB1527	15	270	*	45	
1/2" - 3"	VA2034	20	340	-	90	



BENDING SHOES VB1527 (up to 2") and VA2034 (up to 3")

Nominal Bore	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"
External diameter d (mm)	21,3	26,9	33,7	42,4	48,3	60,3	76,1	88,9
Maximum Wall Thickness (mm) Pipe DIN-2440	2,65	2,65	3,25	3,25	3,25	3,65	3,65	4,05
Maximum Wall Thickness (mm) Pipe DIN-2441	3,25	3,25	4,05	4,05	4,05	4,5	4,5	4,85
Bend Radius R (mm)	83	114	146	184	210	241	290	350

VA - VB AUTOMOTIVE