

Series C9000 - Self-Venting Turning Motion Technology

Self-Venting System

9421A Coupler with valve, with Hosetail

Technical polymer, Nickel-plated brass, NBR




DN	ØD		F	G	L	L1	Kg
5.5	6	9421A06 06	17	31.5	86.5	26	
5.5	8	9421A06 08	17	31.5	86.5	26	
5.5	10	9421A06 10	17	31.5	86.5	26	

Series C9000 series: single shut-off = 1250 NI/min

9416A Coupler with valve, Bulkhead Mountable, Female BSPP Thread

Technical polymer, Nickel-plated brass, NBR




DN	C		E	F	G	K	L1	L2	ØT	Kg
5.5	G1/4	9416A06 13	12	22	31.5	6	12.5	66.5	18.5	

Series C9000 series: single shut-off = 1250 NI/min

9440A Y Coupler, Female BSPP Thread

Technical polymer, Nickel-plated brass, NBR



DN	C		E	F	F1	G	H	H1	Kg
5.5	G3/8	9440A06 17	11.5	19	20	31.5	68	16	

Series C9000 series: single shut-off = 1250 NI/min

9087A Plug without valve, Male BSPP Thread

Nickel-plated steel, technical polymer




DN	C		E	F	L	L1	Kg
5.5	G1/4	9087A06 13	9	17	36	22	
5.5	G3/8	9087A06 17	9	19	36	22	
5.5	G1/2	9087A06 21	12	24	40	22	

Probe without shut-off

Self-Venting System

9080A Plug without valve, LF 3000® Push-In Connection, with Spiral Protection Spring

Nickel-plated steel, NBR



DN	ØD		G	L	L1	Kg
5.5	8	9080A06 08	24	118	22	
5.5	10	9080A06 10	24	118	22	

Probe without shut-off

9094A Plug without valve, with Hosetail

Nickel-plated steel




DN	ØD		F	L	L1	L2	Kg
5.5	6	9094A06 06	14	48.5	22	25	
5.5	8	9094A06 08	14	48.5	22	25	
5.5	10	9094A06 10	14	48.5	22	25	

Probe without shut-off

9401E Coupler with valve, Male BSPP Thread

Technical polymer, Nickel-plated brass, NBR




DN	C		E	F	G	L	Kg
7.2	G1/4	9401E07 13	6.5	22	36.5	80	
7.2	G3/8	9401E07 17	7.5	22	36.5	81	
7.2	G1/2	9401E07 21	9	25	36.5	83.5	

Series C9000: single shut-off = 2000 NI/min

9414E Coupler with valve, Female BSPP Thread

Technical polymer, Nickel-plated brass, NBR



DN	C		E	F	G	L	Kg
7.2	G1/4	9414E07 13	12	22	36.5	73	
7.2	G3/8	9414E07 17	12	22	36.5	73	
7.2	G1/2	9414E07 21	15	27	36.5	78	

Series C9000: single shut-off = 2000 NI/min

Series C9000 - Self-Venting Turning Motion Technology



Self-Venting System

9410E Coupler with valve, LF 3000® Push-In Connection, Spiral Protection Spring

Technical polymer, Nickel-plated brass, NBR




DN	ØD		G	L	L1	Kg
7.2	10	9410E07 10	36.5	151	63	
7.2	12	9410E07 12	36.5	151	63	

Series C9000: single shut-off = 2000 NI/min

9421E Coupler with valve, with Hosetail

Technical polymer, Nickel-plated brass, NBR




DN	ØD		F	G	L	L1	Kg
7.2	8	9421E07 08	22	36.5	93	26	
7.2	10	9421E07 10	22	36.5	93	26	
7.2	13	9421E07 13	22	36.5	97	30	

Series C9000: single shut-off = 2000 NI/min

9416E Coupler with valve, Bulkhead Mountable, Female BSPP Thread

Technical polymer, Nickel-plated brass, NBR




DN	C		E	F	G	K max	L1	L2	ØT min	Kg
7.2	G3/8	9416E07 17	12	24	36.5	7	14.5	74	22.5	

Series C9000: single shut-off = 2000 NI/min

9440E Y Coupler, Female BSPP Thread

Technical polymer, Nickel-plated brass, NBR



DN	C		E	F	F1	G	H	H1	Kg
7.2	G1/2	9440E07 21	14	25	25	36.5	78	19	

Series C9000: single shut-off = 2000 NI/min



Self-Venting System

9087E Plug without valve, Male BSPP Thread

Nickel-plated steel, technical polymer



DN	C		E	F	L	L1	Kg
7.2	G1/4	9087E07 13	9	14	34	20	
7.2	G3/8	9087E07 17	9	17	34	20	
7.2	G1/2	9087E07 21	12	22	38	20	

Probe without shut-off

9080E Plug without valve, LF 3000® Push-In Connection, with Spiral Protection Spring

Nickel-plated steel, NBR



DN	ØD		G	L	L1	Kg
7.2	10	9080E07 10		24	114	20
7.2	12	9080E07 12		29.5	125	20

Probe without shut-off

9094E Plug without valve, with Hosetail

Nickel-plated steel



DN	ØD		F	L	L1	L2	Kg
7.2	8	9094E07 08	17	48	20	25	
7.2	10	9094E07 10	17	48	20	25	
7.2	13	9094E07 13	17	48	20	25	

Probe without shut-off

9401U Coupler with valve, Male BSPP Thread

Technical polymer, Nickel-plated brass, NBR



DN	C		E	F	G	L	Kg
5.5	G1/4	9401U06 13	7.5	17	31.5	74	
5.5	G3/8	9401U06 17	8.5	21	31.5	76.5	
5.5	G1/2	9401U06 21	10.5	25	31.5	80	
8	G1/4	9401U08 13	6.5	22	36.5	81.5	
8	G3/8	9401U08 17	7.5	22	36.5	82.5	
8	G1/2	9401U08 21	9	25	36.5	85.5	

Series C9000 ISO B6: single shut-off = 1250 NI/min
Series C9000 ISO B8: single shut-off = 2400 NI/min

