

Nickel-Plated Brass Adaptors

0900 Equal and Unequal Adaptor, Male BSPT Thread

Nickel-plated brass



C1	C2		F	L	Kg
R1/8	R1/8	0900 00 10	12	20.5	0.009
	R1/4	0900 10 13	14	24	0.014
	R3/8	0900 10 17	17	24.5	0.020
R1/4	R1/4	0900 00 13	14	27	0.017
	R3/8	0900 13 17	17	27.5	0.026
R1/2	R1/2	0900 13 21	22	30.5	0.046
	R3/8	0900 00 17	17	28	0.025
R3/8	R1/2	0900 17 21	22	31	0.046
	R1/2	0900 00 21	22	33.5	0.042
R1/2	R3/4	0900 21 27	27	37	0.084
	R3/4	0900 00 27	27	39.5	0.079
R3/4	R1	0900 27 34	34	42.5	0.145
	R1	0900 00 34	34	45.5	0.153

0191 Tailpiece Adaptor for Rubber Hose, Male BSPP Thread


Nickel-plated brass



ØD	ØD1	C		E	F	K	L	Kg
4	6	G1/4	0191 04 13	9.5	17	5	22.5	0.019
	9	G1/4	0191 07 13	9.5	17	5	22.5	0.022
7	9	G1/2	0191 07 21	11	27	7	29.5	0.058
	12.2	G1/4	0191 10 13	9.5	17	5	22.5	0.020
10	12.2	G1/2	0191 10 21	11	27	7	29.5	0.060
	15.2	G1/4	0191 13 13	9.5	17	5	22.5	0.022
13	15.2	G1/2	0191 13 21	11	27	7	29.5	0.059
	16	18.5	G1/2	0191 16 21	11	27	7	36.5

0931 Tailpiece Adaptor for Rubber Hose, Male BSPP Thread

Nickel-plated brass



ØD	ØD1	C		E	F	K	L	Kg
6	7	G1/8	0931 06 10	6	12	4.5	19	0.009
	7	G1/4	0931 06 13	8	14	5	19	0.013
7	8	G1/8	0931 07 10	6	12	4	19	0.009
	8	G3/8	0931 07 17	9	19	5	19	0.021
	9	G1/8	0931 08 10	6	12	4	19	0.009
8	9	G1/4	0931 08 13	8	14	5	19	0.014
	9	G3/8	0931 08 17	9	19	5	19	0.022
10	12	G1/4	0931 10 13	8	14	5	19	0.016
	12	G3/8	0931 10 17	9	19	5	19	0.024
	12	G1/2	0931 10 21	10	22	6	20	0.031
15	17	G3/8	0931 15 17	9	19	6	24	0.030
	17	G1/2	0931 15 21	10	22	6	24	0.036
18	20	G1/2	0931 18 21	10	22	6	24	0.040

0901 Equal and Unequal Adaptor, Male BSPP and Metric Thread

Nickel-plated brass



C1	C2		E	E1	F	L	Kg
M5x0.8	M5x0.8	0901 00 19	4	4	8	11.5	0.002
	G1/8	0901 19 10	4	6	14	14.5	0.008
G1/8	G1/8	0901 00 10	6	6	14	16.5	0.009
	G1/4	0901 10 13	6	8	17	19	0.016
G1/4	G1/4	0901 00 13	8	8	17	21	0.019
	G3/8	0901 13 17	8	9	19	22	0.023
G3/8	G1/2	0901 13 21	8	10	24	23.5	0.036
	G3/8	0901 00 17	9	9	19	23	0.025
G3/8	G1/2	0901 17 21	9	10	24	24.5	0.038
	G1/2	0901 00 21	10	10	24	25.5	0.040

0192 Unequal Straight Adaptor, Male BSPT/BSPP Thread

Nickel-plated brass




C1	C2		E	F	L	Kg
R1/8	G1/4	0192 10 13	9.5	17	23.5	0.019
R1/4	G1/4	0192 13 13	9.5	17	27.5	0.024
R1/4	G1/2	0192 13 21	11	27	31.5	0.066
R3/8	G1/4	0192 17 13	9.5	17	28	0.025
R3/8	G1/2	0192 17 21	11	27	31.5	0.060
R1/2	G1/2	0192 21 21	11	27	34	0.061

Nickel-Plated Brass Adaptors

0934 Tailpiece Adaptor for Polymer Tubing, Male BSPT Thread

Nickel-plated brass



ØD	C		F	L	L1	Kg
6	R1/8	0934 06 10	12	31.5	19	0.009
	R1/4	0934 06 13	14	35	19	0.014
7	R1/8	0934 07 10	12	31.5	19	0.009
	R1/4	0934 07 13	14	35	19	0.014
8	R1/8	0934 08 10	12	31.5	19	0.010
	R1/4	0934 08 13	14	35	19	0.015
	R1/4	0934 09 13	14	35	19	0.015
9	R3/8	0934 09 17	17	35.5	19	0.021
	R1/2	0934 09 21	22	38.5	19	0.032
	R1/8	0934 10 10	12	32.5	20	0.011
10	R1/4	0934 10 13	14	36	20	0.016
	R3/8	0934 10 17	17	36.5	20	0.021
	R1/2	0934 10 21	22	39.5	20	0.033
	R1/4	0934 12 13	14	36	20	0.016
12	R3/8	0934 12 17	17	36.5	20	0.021
	R1/2	0934 12 21	22	39.5	20	0.033
14	R3/8	0934 14 17	17	38.5	22	0.025
	R1/2	0934 14 21	22	41.5	22	0.036
16	R3/8	0934 16 17	17	38.5	22	0.026
	R1/2	0934 16 21	22	41.5	22	0.037
17	R3/4	0934 16 27	27	45	22	0.055
	R1/2	0934 17 21	22	43.5	24	0.041
18	R3/8	0934 18 17	19	40.5	24	0.035
	R1/2	0934 18 21	22	43.5	24	0.044
20	R3/4	0934 18 27	27	47	24	0.064
	R1/2	0934 20 21	22	43.5	24	0.041

0902 Equal and Unequal Adaptor, Female BSPP and Metric Thread


Nickel-plated brass



C1	C2		F	L	Kg
M5x0.8	M5x0.8	0902 00 19	8	11	0.003
	G1/8	0902 19 10	14	13.5	0.009
G1/8	G1/8	0902 00 10	14	15	0.010
	G1/4	0902 10 13	17	19	0.017
	G3/8	0902 10 17	22	20	0.028
G1/4	G1/4	0902 00 13	17	22	0.019
	G3/8	0902 13 17	22	22.5	0.031
	G1/2	0902 13 21	26	24	0.033
G3/8	G3/8	0902 00 17	22	23	0.035
	G1/2	0902 17 21	24	26	0.036
G1/2	G1/2	0902 00 21	26	28	0.049
	G3/4	0902 21 27	32	30	0.078
G3/4	G3/4	0902 00 27	32	32	0.076

0935 Tailpiece Adaptor for Polymer Tubing, Male BSPP Thread

Nickel-plated brass



ØD	C		E	F	L	L1	Kg
6	G1/8	0935 06 10	8	12	28.5	19	0.007
8	G1/4	0935 08 13	11	15	31.5	19	0.012
12	G1/2	0935 12 21	14.5	24	36	20	0.033

0950MB Maintenance Kit, BSPP Thread

Nickel-plated brass



	H	L	L1	Kg
0950 00 00 02	81	413	330	3.500

A selection of 250 references covering the most-used products

0950M0 Maintenance Kit, BSPT Thread

Nickel-plated brass



	H	L	L1	Kg
0950 00 00 03	81	413	330	3.500

A selection of 216 references covering the most-used products