

SAFETY LOCKOUT HASPS



Safety Lockout hasps allow multiple padlocks to be used when isolating one energy source. The lockout hasp is placed through the isolating point and each person carrying out maintenance or service work attaches and locks in place their own unique individually keyed padlock through the lockout hasp. This ensures each worker's safety as the energy cannot be restored until the work is finished and all padlocks have been removed.

					
LM-H-25	LM-H-38	LM-H-38-7H	LM-DH-6	LM-DH-3	LM-H-24P
					
LM-ALU-H-25	LM-ALU-H-38	LM-DH-SH-4		LM-SH-DS6	

The OSHA standard for The Control of Hazardous Energy (Lockout/Tagout): Title 29 (CFR) Part 1910.147

PRODUCT DESCRIPTION	PRODUCT CODE
Lockout Hasp – 25mm Jaw Size	LM-H-25
Lockout Hasp – 38mm Jaw Size	LM-H-38
Lockout Hasp – 38mm Jaw Size, 7holes	LM-H-38-7H
De-electric Lockout Hasp – 6 Holes	LM-DH-6
De-electric Lockout Hasp – 3 Holes	LM-DH-3
Lockout Hasp, 25mm Jaw Size, 24 Holes	LM-H-24P
Aluminium Hasp - 25mm Jaw Size	LM-ALU-H-25
Aluminium Hasp - 38mm Jaw Size	LM-ALU-H-38
De-electric Hasp - Scorpio Type, 4 Holes	LM-DH-SH-4
Lockout Hasp – Scorpio type, Double Sided Jaw	LM-SH-DS6

SAFETY LOCKOUT HASPS



Your Lockout / Tagout Expert

www.lotomaster.eu