

Fixing accessories

Fixing accessories



S12 - S16 - S20
HILTI
Hole required Ø 10-14-16
Galvanized steel.



M12 - M16
HILTI
Hole required Ø 12-16
Galvanized steel.



TM5
Hole required Ø 8.5
Neutral polyethylene. 100/500 Pcs. / bag.



TS9
Hole required Ø 5
White or grey nylon. 1000 Pcs. / bag.



B12 - B16 - B20
HILTI
Hole required Ø 22-28-32
Galvanized steel.



S8FH - S12FH
HILTI
Hole required Ø 6-10
Galvanized steel.
Countersunk.



TH
ABS.
100 Pcs. / bag.
RAL 9010 / 9002 / 9006 / 7040 / 7024 / Transparent.



TX12
ABS.
100 Pcs. / bag.
RAL 7035 / 9010



SF12 - SF16 - SF20 INOX
Hole required Ø 14-18-24
Stainless steel.



M12 - M16 INOX
Hole required Ø 12-16
Stainless steel.



TB14 - TB20
Hole required Ø 4-5
Steel / aluminium (white for ø 4)
500 Pcs. / box.



COVER 150 RE
Galvanized steel and painted.



KIT ROD 70-120
HILTI
Hole required Ø 38-56
Galvanized steel.



KIT ROD 70-120 INOX
HILTI
Hole required Ø 38-56
Galvanized steel.



FIX P90
Galvanized steel and painted.



COVER 90 RE
Galvanized steel and painted.



AA12 - AA16
Hole required Ø 22-22
Galvanized steel.
For asphalt.



ASPHALT CHEMICAL
CHEMICAL ANCHOR
585 ML



FIX P90 INOX
Stainless steel.



FIX P150
Galvanized steel and painted.



FR
HILTI CHEMICAL ANCHOR
300 ML



WIT NORDIC
CHEMICAL ANCHOR
420 ML
(Installation in working cold rooms
with negative temperatures)



FIX P150 FH
Galvanized steel and painted.
Countersunk.



FIX P150 INOX
Stainless steel.



SHOCK ABSORBER PAD
Soft material, optional for FIXP150.
(To be installed with S12x150)



FULL FRAME BASE
Galvanized steel and painted.

In collaboration with



MPM srl reserves the right, at any time, to introduce the necessary changes and improvements to its products.
Any small imperfection in the products and in the materials used are due to the processing method.
Any reproduction of this brochure, even in part, is forbidden.

Colours



MPM srl reserves the right, at any time, to introduce the necessary changes and improvements to its products.
Any small imperfection in the products and in the materials used are due to the processing method.
Any reproduction of this brochure, even in part, is forbidden.

Products marked with the symbol are recommended for indoor use, as prolonged UV exposure may cause discoloration.