www.rodavigo.net +34 986 288118

Servicio de Att. al Cliente

ELASTOMER PLATES E3PEPL

SILICONE RUBBER / SPECIAL ELECTRONICS / LOW LOADS



DESCRIPTION

VHDS elastomer sheet.

APPLICATIONS

These sheets may be used for making grommets, washers or anti-vibration mountings for equipment.

There is a wide range of VIBRACHOC moulded parts, but in certain cases, such as prototypes, undefined specification, etc, it is often advantageous to determine the suspension using elastomer compo-nents cut from sheet and bonded.

CHARACTERISTICS

- Overall tolerances :
 - on the lengths : \pm 5%;
 - on the thickness : ± 3%.

Shape	Dimensions (mm)	Thickness (mm)
SQUARE	300 x 300	2, 3, 4, 5, 6, 8, 10

VIBRACHOC plates should be ordered using the following reference : E3PEP

1 : dimension in cm - 2 : hardness (see p 114) - 3 : thickness in 1/10 mm.

For example : E3PEPL30S55C060 =

- square plate 300 X 300 mm;
- 6 mm thick;
- VHDS rubber compound, grade 55.

For other shapes, sizes or materials, ask us for details.

PAULSTRA - 61 rue Marius Aufan - 92309 Levallois-Perret Cedex - France - T. +33 1 40 89 53 31 - F. +33 1 47 25 28 96 - www.paulstra-industry.com

118