

MINIFIX®




DESCRIPTION

The MINIFIX® mount comprises an elastomer pad with an anti-slip ridged surface and a threaded stud allowing accurate height adjustment of equipment.

Made in two hardnesses (50 and 80 Sh) the MINIFIX® mount is perfectly suited to a variety of applications and is delivered complete with fixing nuts and washers. MINIFIX® mounting nuts and screws are made of steel or stainless steel.

CHARACTERISTICS



Load range (daN)	Reference Stainl. steel	Reference Steel	Hardness	Colour	Ø A (mm)	B (mm)	C (mm)	D
5-30 15-70	-	530801	50 SBR 80 Nitrile	grey black	32	15	38	M8 stud
10-40 25-100	-	530802*	50 SBR 80 Nitrile	grey black	46	15	-	M10 nut
10-40 25-100	530806	530805	50 SBR 80 Nitrile	grey black	46	15	38	M10 stud
50-120 100-350	-	530807	50 SBR 80 Nitrile	grey black	70	25,5	55,5	M12 stud

See current price list availability of items.

* Threaded centre hole.

APPLICATIONS

Simple and economic, MINIFIX® mountings are particularly suitable for the installation of equipment such as :

- electrical or electronic enclosures.
- packaging equipment.
- test and measuring equipment.
- equipment for the food industry.
- laboratory equipment.
- household appliances.