

# Text index

## A

### A

angular contact ball bearings 197  
axial-radial cylindrical roller bearings 333  
double direction angular contact thrust ball bearings 303, 311  
thrust bearings for screw drives 342, 364–365  
**AC** 130, 196  
**ACB** 196  
accuracy  
of bearings 24–25  
of seats and abutments 75–77, 325–326  
of seats and abutments (for screw drives) 349  
tolerance symbol definitions 48–49  
**ACD** 196  
**ACE** 196  
acrylonitrile-butadiene rubber (NBR) 56  
adapter sleeves 376  
adjusting  
angular contact ball bearings 166–172, 192  
cylindrical roller bearings 278–279, 280–283, 392  
precision lock nuts 380–381  
ageing 55–56, 101, 114, 125  
air flow  
effect on relubrication interval 109  
in an external sealing arrangement 96  
in an oil-air lubrication system 121  
aluminium thickeners 110  
ambient temperature  
considerations when selecting a grease 99  
effect on bearing speed capability 39  
angular contact ball bearings 127–261  
adjustment during mounting 166–172, 192  
applications 58–64, 131–132  
assortment 128–129  
axial displacement 31, 69, 91, 166  
bearing arrangements 141–144  
cages 134–135  
contact angles 130–131  
designation system 196–197  
designs and variants 21, 128–141  
dimension series 27, 129, 130  
dimension standards 146  
direct oil-air lubrication variants 120, 136–140  
dismounting 124  
equivalent bearing loads 190–191  
fits 71–74  
fitting and clamping bearing rings 183–189  
high-capacity bearings 129, 131  
high-speed design bearings 129, 132  
hybrid bearings 133, 141, 167, 198–261  
initial grease fill 101–102, 105  
lifting forces 91–92  
load carrying capacity 30, 189  
location 183–189  
lubrication (grease) 99–112, 136, 192  
lubrication (oil) 113–122, 136–140, 192

markings 145, 194  
matched sets 141–144  
mounted with spacer rings 166–172, 192–193  
mounting 123, 136, 145, 194  
oil nozzle positions 118, 199–261  
ordering possibilities 141  
preload 50, 69, 90–93, 151–172  
product table 198–261  
reference grease quantities 102, 199–261  
relubrication intervals 106–109  
reuse 124  
sealed bearings 136, 192  
speeds 28–29, 38–40, 42, 192–193  
spring-loaded 64, 90, 93, 165, 190  
stiffness 67–69, 173–182  
temperature limits 136  
temperature rise as a function of speed 38  
tolerance classes and tolerances 24, 146–150  
universally matchable bearings 141–144, 194  
with NitroMax steel rings 52–53, 141  
angular contact thrust ball bearings  
cartridge units (for screw drives) 342–343, 372–373  
designs and variants 21–22  
double direction bearings 301–317  
double direction bearings (for screw drives) 341, 368–371  
single direction bearings (for screw drives) 340, 366–367  
angularity 76  
anhydrous hydrofluorides 56  
annular grooves  
in angular contact ball bearings 120, 136–140  
in cylindrical roller bearings 266  
in double direction angular contact thrust ball bearings 303–304  
in shafts 96–97  
in thrust bearings for screw drives 341  
applications  
for angular contact ball bearings 58–64, 131–132  
for axial-radial cylindrical roller bearings 320  
for cylindrical roller bearings 57–59, 62  
for double direction angular contact thrust ball bearings 57, 59  
for thrust bearings for screw drives 350–351  
machine tools 57–64  
associated components 20  
accuracy of seats and abutments 75–77, 325–326  
accuracy of seats and abutments (for screw drives) 349  
provisions for mounting and dismounting 88–89  
attachment bolts  
for axial-radial cylindrical roller bearings 330–332, 335  
for thrust bearings for screw drives 371, 373  
attainable speeds 28, 44  
with grease lubrication 42–43, 45  
with oil lubrication 40–41, 45  
axial clamping forces 184, 186–188  
axial displacement  
considerations when selecting a bearing 31  
considerations when selecting a fit 70, 72  
in angular contact ball bearings 31, 69, 91, 166

Note: Designation prefixes and suffixes are shown in **bold**.

## Indexes

in cylindrical roller bearings 31, 264, 269, 280  
 axial drive-up 278–279, 280, 284  
 axial fitting forces 184, 186–188  
 axial location 78–87  
   with precision lock nuts 78, 375–389  
   with stepped sleeves 79, 80–87  
 axial locking screws 377, 378, 381  
 axial preload  
   in angular contact ball bearings 151–172  
   in axial-radial cylindrical roller bearings 322–323  
   in double direction angular contact thrust ball bearings 308  
   in thrust bearings for screw drives 355–357, 358  
 axial stiffness  
   of angular contact ball bearings 173–182  
   of axial-radial cylindrical roller bearings 322–323  
   of cylindrical roller bearings 275–276  
   of double direction angular contact thrust ball bearings 309  
   of thrust bearings for screw drives 339, 356–359  
   of typical spindle bearing systems 67  
 axial-radial cylindrical roller bearings 319–335  
   applications 320  
   associated components 324–326, 330  
   attachment bolts 330–332, 335  
   bearing damage 322  
   cages 320  
   designation system 333  
   designs and variants 22, 320  
   dimension standards 321  
   equivalent bearing loads 327  
   fits 324–326  
   friction 322–323, 330  
   load carrying capacity 30, 322, 327, 328–329  
   lubrication 320, 324  
   mounting 330–332  
   preload 322–323, 324  
   product table 334–335  
   retaining bolts 330, 335  
   running-in 324  
   stiffness 322–323  
   storage 330  
   temperature limits 324  
   tightening torques 332  
   tolerance classes and tolerances 24, 321  
   transport 330  
   unloading forces 322–323

## B

**B**  
 angular contact ball bearings 196–197  
 axial-radial cylindrical roller bearings 333  
 cylindrical roller bearings 286  
 double direction angular contact thrust ball bearings 303, 311  
 thrust bearings for screw drives 365  
 back-to-back arrangements  
   with angular contact ball bearings 142–144  
   with double direction angular contact thrust ball bearings 303  
   with thrust bearings for screw drives 341, 342–343, 346–348  
 ball screw support bearings → thrust bearings for screw drives  
 barium thickeners 110  
 base oil viscosity → viscosity  
 basic dynamic load rating 33  
 basic rating life 34  
 basic static load rating 36  
 bearing damage  
   contamination 124  
   creep 70  
   false brinelling 100  
   fracture 52  
   skid smearing 133, 268, 304, 322  
 bearing systems 57  
 black-oxide 342  
 blue dye 393

boat gyro stabilizers 131  
 bolt mounting  
   with cartridge units (for screw drives) 342–343, 372–373  
   with double direction bearings (for screw drives) 341, 370–371  
 bolts  
   attachment bolts 330–332, 335, 371, 373  
   retaining bolts 330, 335  
 bore gauges 282, 401  
 boring machines 131  
 brass  
   cages in angular contact ball bearings 134–135  
   cages in cylindrical roller bearings 265, 267  
   cages in double direction angular contact thrust ball bearings 304–305  
   material properties 55

## C

**C**  
 angular contact ball bearings 130, 196–197  
 double direction angular contact thrust ball bearings 311  
 thrust bearings for screw drives 364  
**C2** 273, 286  
**C3** 273, 286  
 cages  
   function 23  
   in angular contact ball bearings 134–135  
   in axial-radial cylindrical roller bearings 320  
   in cylindrical roller bearings 264, 267, 268, 280  
   in double direction angular contact thrust ball bearings 304–305  
   in thrust bearings for screw drives 344  
   materials 51, 55  
 calcium thickeners  
   compatibility 110  
   considerations when selecting a grease 99–100  
 car wheels → racing car wheels  
 carbon fibre reinforced cages 55  
   in angular contact ball bearings 134–135  
   in cylindrical roller bearings 264, 267  
 cartridge units 342–343, 372–373  
   applications 350–351  
   compared to other bearings for screw drives 339  
   designation system 364–365  
   designs and variants 22, 342–343  
   dimension standards 353  
   frictional moment 359–360  
   location 342  
   preload 355  
   product table 372–373  
   sealing solutions 344–345  
   speeds 344, 363  
   stiffness 358–359  
   surface treatment 342  
   temperature limits 344–345  
   tolerance classes and tolerances 353–354  
**CB** 196  
**CD** 196  
**CE** 196  
 centrifugal forces  
   in angular contact ball bearings 132, 162, 166, 167  
   in hybrid bearings 34, 37  
 ceramics 54  
 chamfer dimensions 46–47  
   maximum chamfer dimension limits 47, 50  
   tolerance symbol definitions 48  
 churning 111, 113  
 circulating oil 113, 114, 121  
 clay 110  
 clearance  
   in housing seats 30, 74, 302  
   internal clearance 50–51  
**CN** 273, 286

Note: Designation prefixes and suffixes are shown in **bold**.

CNC lathe spindles 57–58  
 coefficient of thermal expansion  
   effect on preload 162  
   of NitroMax steel 53  
   of silicon nitride versus steel 54  
 collars → spacer sleeves  
 collectors 96–97  
 consistency grades → NLGI consistency grades  
 contact angles  
   effect on lifting force 91–92  
   effect on load carrying capacity 30  
   effect on speed capability 30  
   effect on stiffness 26, 68–69  
   in angular contact ball bearings 130–131  
   in double direction angular contact thrust ball bearings 303  
   in thrust bearings for screw drives 340–341  
 contact seals  
   in external sealing arrangements 98  
   in thrust bearings for screw drives 32, 344–345  
 contamination  
   bearing damage 124  
   effect on relubrication interval 109  
   ISO oil contamination levels 122  
   protection prior to / during mounting 123, 125  
   protection with grease 99  
   protection with oil 114, 116  
   protection with seals 32, 95–98  
 coolants 23, 51, 122  
 cooling 39, 99, 113, 116  
 corrosion resistance  
   of NitroMax steel 52–53  
   protection prior to mounting 125  
   protection with grease 100–101  
 cotton fabric reinforced cages 55  
   in angular contact ball bearings 134–135  
 creep 70  
 cross-sectional height  
   considerations when selecting a bearing 27  
   effect on speed capability 38  
 cutting fluids 96, 106, 122  
 cyclic operation 35, 106  
 cylindrical roller bearings 263–299  
   adjustment during mounting 278–279, 280–283, 392  
   applications 57–59, 62  
   axial displacement 31, 264, 269, 280  
   axial drive-up 278–279, 280, 284  
   cages 264, 267, 268, 280  
   design considerations 278–280  
   designation system 286  
   designs and variants 21, 264–268  
   dimension standards 269  
   dismounting 124  
   double row bearings 265–267, 294–299  
   equivalent bearing loads 277  
   finish-grinding allowances 267  
   fits 71–72, 74  
   flanges 264  
   gauges for checking tapered seats 391–407  
   hybrid bearings 268, 288–293  
   identification numbers 273, 280  
   in combination with double direction bearings 302–303  
   initial grease fill 101, 103, 105  
   internal clearance 273–274, 275, 278–279  
   load carrying capacity 30  
   lubrication features 266, 268  
   markings 273, 280  
   mounted with spacer rings 78, 282–285  
   mounting 278–279, 280–285, 401, 405  
   oil nozzle positions 119, 266, 289–299  
   preload 50–51, 94, 275, 278  
   product tables 288–299  
   reference grease quantities 103, 289–299  
   relubrication 106–109, 266  
   reuse 124  
   single row bearings 264, 288–293  
   speeds 28, 40, 42, 264, 268, 277

stiffness 275–276  
 temperature rise as a function of speed 38  
 tolerance classes and tolerances 24, 269–272  
 with a pre-ground raceway 267  
 with a tapered bore 264–265, 272

## D

**D** 196–197

### DB

angular contact ball bearings 144, 197  
 double direction angular contact thrust ball bearings 311  
 thrust bearings for screw drives 342–343, 348, 365

**DBA** 308, 310, 311

**DBB** 308, 310, 311

deflection 66, 68

density 37, 54

designation systems

  for angular contact ball bearings 196–197  
   for axial-radial cylindrical roller bearings 333  
   for cylindrical roller bearings 286  
   for double direction angular contact thrust ball bearings 311  
   for precision lock nuts 382  
   for thrust bearings for screw drives 364–365

### DF

angular contact ball bearings 144, 197  
 thrust bearings for screw drives 342–343, 348, 365

dial indicators

  on internal clearance gauges 282–284, 400–401  
   on taper gauges 396

diameter series → ISO diameter series

dielectric strength 54

dimension series → ISO dimension series

dimension standards 46

dimensional accuracy

  of bearings 24–25  
   of seats and abutments 71–74, 325–326  
   of seats and abutments (for screw drives) 349  
   tolerance symbol definitions 48–49

dimensional stability → heat stabilization

direct oil-air lubrication 120

  bearing variants and dimensions 136–140

dismounting 123–124

  angular contact ball bearings 124  
   cylindrical roller bearings 124  
   design considerations 88–89  
   thrust bearings for screw drives 341

dismounting fluids 87

distance rings 278

distance sleeves 86

double direction angular contact thrust ball bearings 301–317

  applications 57, 59

  basic design bearings 302–303, 312–317

  cages 304–305

  contact angles 303

  designation system 311

  designs and variants 21–22, 302–305

  dimension standards 306

  equivalent bearing loads 310

  fits 71–72, 74, 308

  high-speed design bearings 302–303, 312–317

  hybrid bearings 304, 312–317

  identification/serial numbers 305

  in combination with cylindrical roller bearings 302–303

  initial grease fill 101, 104–105

  lifting forces 94

  load carrying capacity 30

  lubrication (oil) 116–117, 119

  lubrication features 303–304

  markings 305

  mounting 123, 305, 310

  oil nozzle positions 119, 313–317

  preload 50, 94, 308

  product tables 312–317

Note: Designation prefixes and suffixes are shown in **bold**.

## Indexes

radial clearance in the housing 30, 74, 302  
 reference grease quantities 104, 313–317  
 relubrication intervals 106–109  
 speeds 38, 41, 43, 310  
 stiffness 67, 309  
 temperature rise as a function of speed 38  
 tolerance classes and tolerances 24, 306–307  
 double direction angular contact thrust ball bearings (for screw drives) 341, 368–371  
   compared to other bearings for screw drives 339  
   designation system 364–365  
   dimension standards 353  
   for bolt mounting 341, 370–371  
   frictional moment 357, 360  
   preload 355, 357  
   product tables 368–371  
   sealed bearings 344–345  
   speeds 344, 363  
   stiffness 357–358  
   temperature limits 344–345  
   tolerance classes and tolerances 353–354  
 double direction bearings 301–317  
   for screw drives 341, 368–371  
 double row cylindrical roller bearings 265, 294–299  
   applications 57  
   axial displacement 264, 269, 280  
   axial drive-up 278–279  
   cages 267  
   compared to single row cylindrical roller bearings 264  
   designs and variants 21, 265–267  
   dimension standards 269  
   equivalent bearing loads 277  
   finish-grinding allowances 267  
   gauges for checking tapered seats 391–407  
   hybrid bearings 268  
   initial grease fill 101, 103, 105  
   internal clearance 273–274, 275, 278  
   mounting 280–285, 401, 405  
   oil nozzle positions 119, 266, 295–299  
   preload 275, 278  
   product tables 294–299  
   reference grease quantities 103  
   speeds 264, 268, 277  
   stiffness 275–276  
   tolerance classes and tolerances 24, 269–272  
 drainage  
   for oil-air lubrication 117  
   in a multi-stage labyrinth sealing arrangement 96–97  
 drilling heads 60, 131, 132, 166  
 drive-up → axial drive-up  
**DT**  
   angular contact ball bearings 144, 197  
   thrust bearings for screw drives 348, 365  
 dust  
   effect on relubrication interval 109  
   protection prior to / during mounting 123  
 dynamometers 131

## E

**E** 196  
 eccentric loads 327  
 elastic deformation 66, 68  
 elasto-hydrodynamic lubrication (EHL) 100  
 electrical resistivity 54  
 electro-spindles  
   oil cleanliness requirements 122  
   with angular contact ball bearings 62–64, 132  
   with cylindrical roller bearings 62, 264  
 ellipse truncation 36  
 end plates 183–189  
 envelope diameters 280, 392, 400, 404  
 envelope requirement → ISO envelope requirement  
 environmental considerations

for fluoro rubber (FKM) 56  
 for oil mist lubrication 115  
 for oil-air lubrication 116  
 EP additives  
   compatibility 55, 100  
   considerations for grease lubrication 99–100  
   considerations for oil lubrication 121  
 equivalent bearing loads  
   dynamic 33  
   static 36  
 ester oils  
   compatibility 109  
   in sealed bearings 104  
 esters 56  
 ethers 56  
 external seals 95–98  
 extreme pressure additives → EP additives

## F

**F** 130, 196–197  
 face-to-face arrangements  
   with angular contact ball bearings 142–144  
   with thrust bearings for screw drives 342–343, 346–348  
 false brinelling 100  
 fatigue strength 52–53, 141  
**FB** 196  
**FE** 196  
 filtering 114, 117  
 finish-grinding allowances  
   for inner rings of cylindrical roller bearings 267  
   for spacer rings for angular contact ball bearings 166–172  
 fits  
   axial location 78–79  
   effect of surface roughness 75  
   effect on preload and internal clearance 50–51, 90, 94  
   effect on stiffness 68  
   for housings 72–74, 326  
   for shafts 71, 73–74, 325  
   radial location 70  
 FKM → fluoro rubber (FKM)  
 flanged housings 342–343, 372–373  
 fluoro rubber (FKM)  
   material properties 56  
   seals for angular contact ball bearings 136  
 fracture 52  
 friction 37  
   effect of preload and internal clearance 37  
   effect on speed capability 38–39  
   generated by seals 96, 98  
   with grease lubrication 37, 100, 111  
   with hybrid bearings 37  
   with oil lubrication 113–115  
 frictional losses 53, 99, 113  
 frictional moment  
   in axial-radial cylindrical roller bearings 322–323  
   in thrust bearings for screw drives 357, 360  
   with grease lubrication 111

## G

**G**  
   angular contact ball bearings 142, 196  
   axial-radial cylindrical roller bearings 320, 324, 333  
**G...**  
   angular contact ball bearings 151, 197  
   double direction angular contact thrust ball bearings 311  
   thrust bearings for screw drives 355, 364–365  
**GA**  
   angular contact ball bearings 196  
   thrust bearings for screw drives 364  
 gauge blocks 282–283

Note: Designation prefixes and suffixes are shown in **bold**.

gauges 391–407  
 bore gauges 282  
 for mounting cylindrical roller bearings 280–283  
 internal clearance gauges 280–283, 400–407  
 ring gauges 393–395  
 taper gauges 396–399

**GB**  
 angular contact ball bearings 196  
 thrust bearings for screw drives 364

**GC** 196

**GD** 196

geometrical accuracy  
 of seats and abutments 75–77, 325–326  
 of seats and abutments (for screw drives) 349

glass fibre reinforced cages  
 in angular contact ball bearings 134–135  
 in cylindrical roller bearings 264, 267, 268  
 material properties 55

**GMM** 342, 365

grease fills  
 effect on friction 37  
 in sealed angular contact ball bearings 136  
 in sealed thrust bearings for screw drives 344  
 initial grease fill 101–105

grease lubrication 99–112  
 attainable speeds 42–43  
 compared with oil lubrication (speed capability) 45  
 initial grease fill 101–105  
 relubrication 106–109  
 running-in 111–112  
 service life 106

greases  
 in sealed bearings 104  
 selection criteria 99–100  
 SKF greases 99  
 storage 122  
 thickener compatibility 110

grinding allowances → finish-grinding allowances

grinding machines 64, 93, 131, 132

grub (set) screws  
 in double direction angular contact thrust ball bearings 341  
 in precision lock nuts 378, 380, 384–388  
 in thrust bearings for screw drives 341

## H

**H** 120, 137–139, 197

**H1** 120, 137–139, 197

hammers 380

hardness  
 of bearing steel 51, 54  
 of NitroMax steel 53  
 of silicon nitride 54

**HC**  
 angular contact ball bearings 133, 197  
 double direction angular contact thrust ball bearings 304, 311

**HC5** 268, 286

heat stabilization 51, 53

heat treatment  
 of carbon chromium steel 51  
 of NitroMax steel 52–53

heating bearings → hot mounting

hollow shafts  
 fits 71  
 with cylindrical roller bearings 279  
 with stepped sleeves 81, 84

hot mounting 123–124  
 angular contact ball bearings 194  
 sealed bearings 136, 345

housing covers 79  
 in a multi-stage labyrinth sealing arrangement 96–97

humidity 125

hybrid bearings  
 angular contact ball bearings 133, 141, 167, 198–261

basic static load rating 36

cylindrical roller bearings 268, 288–293

double direction angular contact thrust ball bearings 304, 312–317

effect on relubrication interval 106–108

frictional behaviour 37

material properties 54

rating life 34

speeds 38, 40–43  
 with NitroMax steel rings 52–53, 141

hydraulic nuts 86

hydrocarbons 56

## I

identification numbers  
 on cylindrical roller bearings 273, 280  
 on double direction angular contact thrust ball bearings 305

immersion 106

impact toughness 52–53

indexing heads 320

induction heaters 123  
 for heating sealed bearings 136, 345  
 for mounting axial-radial cylindrical roller bearings 330

initial grease fills 101–105

injectors 116–117

installation 123–124  
 of precision lock nuts 379–381  
 of stepped sleeves 86–87, 123–124

integral seals  
 design considerations 98  
 in angular contact ball bearings 136  
 in thrust bearings for screw drives 344–345  
 types and designs 32

interference fits 71  
 axial location 78–79  
 effect on preload and internal clearance 50–51  
 for angular contact ball bearings 74  
 for cylindrical roller bearings 31, 74  
 for stepped sleeves 80–81, 84  
 radial location 70

internal clearance 50–51  
 effect on friction 37  
 in cylindrical roller bearings 273–274, 275, 278–279

internal clearance gauges 280–283, 400–407

internal grinding machines 64, 132, 165

ISO  
 diameter series 27, 46  
 dimension series 46  
 envelope requirement 71–72  
 general plans 46  
 oil contamination levels 122  
 tolerance classes 24, 73  
 tolerance grades 77  
 tolerance standards 46–47

IT tolerance grades 77

## K

**K** 264–265, 286

ketones 55, 56

key slots 376

keyways 376

kinematic lubricant starvation 52, 264

kinematic viscosity → viscosity

## L

**L** 120, 137–140, 197

**L1** 120, 139, 197

Note: Designation prefixes and suffixes are shown in **bold**.



## Indexes

- labyrinth seals
    - in a multi-stage sealing arrangement 96–97
    - integral to stepped sleeves 80, 84
  - laminar rings 339, 344–345
  - lathe 57–58, 131, 166
  - life 33–35
  - lifting forces
    - for angular contact ball bearings 91–92
    - for double direction angular contact thrust ball bearings 94
    - for thrust bearings for screw drives 94, 360
  - linear springs → springs
  - lithium thickeners
    - compatibility 110
    - considerations when selecting a grease 99–100
    - in sealed bearings 104
  - live centres 59, 131
  - loads
    - considerations when selecting a bearing 30
    - effect on relubrication interval 109
    - load ratings 33–36
    - requisite minimum loads 34
  - locating/non-locating bearing systems 31
  - location
    - axial 78–87
    - radial 70–77
    - with precision lock nuts 376–377
    - with stepped sleeves 79, 80–87
  - lock nuts → precision lock nuts
  - lock washers 376
  - locking pins 376
  - loose fits 71
    - effect on stiffness 31, 68
    - for non-locating bearings 31
    - radial location 70
  - loosening torques 378
  - lubricants
    - greases 99–101, 104, 110
    - oils 121
    - storage 122
  - lubricating oils → oils
  - lubrication
    - grease 99–112
    - oil 113–122
  - lubrication holes
    - in angular contact ball bearings 120, 136–140
    - in axial-radial cylindrical roller bearings 324
    - in cylindrical roller bearings 266
    - in double direction angular contact thrust ball bearings 304
    - in thrust bearings for screw drives 341
  - lubrication intervals 117
- M**
- angular contact ball bearings 197
  - double direction angular contact thrust ball bearings 304–305, 311
- MA** 134, 196
- machine tool spindles → spindles
  - machine tools
    - applications 57–64, 131–132
    - considerations when selecting a bearing 23–32
  - machining centres
    - with angular contact ball bearings 62–63, 131–132, 141, 166
    - with axial-radial cylindrical roller bearings 320
    - with cylindrical roller bearings 62
  - markings
    - on angular contact ball bearings 145, 194
    - on cylindrical roller bearings 273, 280
    - on double direction angular contact thrust ball bearings 305
    - on thrust bearings for screw drives 352
  - matched sets
    - of angular contact ball bearings 141–144
    - of thrust bearings for screw drives 340, 346–348
  - materials 51–56
    - for bearings 51–54
    - for cages 55
    - for precision lock nuts 378
    - for seals 56
  - measuring systems 131
  - medical equipment 131
  - metal cutting machines 57–63, 132
  - metal-to-metal contact 113
  - microturbines 131
  - milling machines 59, 62–63, 131–132, 141, 166
  - mineral acids 56
  - mineral oils 56, 99
    - compatibility 109
  - minimum load 34
  - minimum quantity lubrication (MQL)
    - with oil-air lubrication 116
    - with SKF Microdosage system 121
  - misalignment 75
    - in thrust bearings for screw drives 346
  - miscibility 109–110
  - modulus of elasticity 54
  - moisture
    - effect on lubricant properties 122
    - effect on relubrication interval 109
    - protection prior to / during mounting 123
    - protection with grease 99
    - protection with seals 95
  - moment loads
    - on angular contact ball bearings 142, 167
    - on axial-radial cylindrical roller bearings 327, 328–329
    - on thrust bearings for screw drives 346
  - moment stiffness 323
  - motorized spindles → electro-spindles
  - mounting 123–124
    - angular contact ball bearings 136, 145, 194
    - axial-radial cylindrical roller bearings 330–332
    - cylindrical roller bearings 280–285
    - design considerations 88–89
    - double direction angular contact thrust ball bearings 305, 310
    - precision lock nuts 379–381
    - stepped sleeves 86–87
    - thrust bearings for screw drives 339, 345, 352, 362
  - mounting fluids 87
  - multi-spindle heads 320
- N**
- NBR → acrylonitrile-butadiene rubber (NBR)
  - needle roller bearings 347
  - NitroMax steel 52–53
    - in hybrid angular contact ball bearings 141
  - NLGI consistency grades 99
  - non-contact seals
    - in angular contact ball bearings 32, 136
    - in external sealing arrangements 96–97
    - in thrust bearings for screw drives 32, 344–345
- O**
- oil bath 114
    - attainable speeds 44
  - oil change intervals 121
  - oil distribution grooves 89
  - oil drop 115
  - oil flow rates 113–114
  - oil injection method
    - dimensions for ducts, grooves and holes 88–89
    - equipment and pressure media 87
    - for cylindrical roller bearings 285
    - for stepped sleeves 80, 86–87

Note: Designation prefixes and suffixes are shown in **bold**.

- oil jet 115
    - attainable speeds 44
    - lubricating oils 121
  - oil lubrication 113–122
    - compared with grease lubrication (speed capability) 45
    - contamination levels 122
    - effect on temperature and frictional losses 113
    - lubricating oils 121
  - oil mist 115
    - attainable speeds 44
    - lubricating oils 121
  - oil nozzles 116–117
    - for angular contact ball bearings 118, 199–261
    - for cylindrical roller bearings 119, 266, 289–299
    - for double direction angular contact thrust ball bearings 119, 313–317
  - oil supply ducts 89
  - oil-air 116–121
    - attainable speeds 40–41, 44
    - direct oil-air lubrication 120, 136–140
    - effect on bearing temperature and frictional losses 113
    - lubricating oils 121
  - oils 121
  - oil-spot → oil-air
  - open bearings
    - initial grease fill 101–105
    - shelf life 125
  - open flames 56
  - operating temperatures 37
    - as a function of oil quantity 113
    - as a function of speed 38
    - during running-in 112, 124
    - effect on preload and internal clearance 37
    - effect on relubrication interval 109
    - of cage materials 55
    - of seal materials 56
  - O-rings
    - in stepped sleeves 81, 83
    - on angular contact ball bearings 120, 136–140
  - oscillations
    - considerations when selecting a grease 99
    - with axial-radial cylindrical roller bearings 328
  - osculation 26, 131, 132
  - overhung shafts 346–347, 350–351
  - ozone 56
- P**
- P** 378, 382
  - P2** 197
  - P4** 197
  - P4A** 197
  - P4C** 311
  - PA66 → polyamide 66 (PA66)
  - PA9A** 197
  - PAO 104
  - Parallel Kinematic Machines (PKM) 131
  - PBC** 197
  - PBT** 197
  - PCB drilling machines 132
  - PE** 341, 365
  - PEEK → polyetheretherketone (PEEK)
  - permissible speeds 39
  - PFC** 197
  - PFT** 197
  - PG** 197
  - PHA** 264, 267, 268, 286
  - phenolic resin
    - cages in angular contact ball bearings 134–135
    - material properties 55
  - pin wrenches 379
  - polishing machines 131
  - polyamide 66 (PA66)
    - cages in cylindrical roller bearings 264, 267
    - material properties 55
  - polyetheretherketone (PEEK)
    - cages in angular contact ball bearings 134–135
    - material properties 55
  - polyglycol 109
  - polymers
    - cages in angular contact ball bearings 134–135
    - cages in cylindrical roller bearings 264, 267, 268, 280
    - material properties 55–56
  - polyphenylether 109
  - polyurea 110
  - precision
    - of bearings 24–25
    - of seats and abutments 75–77, 325–326
    - of seats and abutments (for screw drives) 349
  - precision lock nuts 78, 375–389
    - adjustment during mounting 380–381
    - compared with stepped sleeves 79
    - designation system 382
    - designs 376–377
    - dimension standards 378
    - installation 379–381
    - loosening torques 378
    - lubrication 378
    - materials 378
    - preload 376–377
    - product tables 384–389
    - removal 379–380
    - spanners 379, 384–388
    - thread standards 378
    - tolerances 378
    - with axial locking screws 377, 388–389
    - with locking pins 376, 384–387
  - pre-ground raceways 267
  - preload 90–94
    - effect on friction 37
    - effect on relubrication interval 108
    - effect on speed capability 64
    - in angular contact ball bearings 50, 69, 90–93, 151–172
    - in axial-radial cylindrical roller bearings 322–323, 324
    - in cylindrical roller bearings 50–51, 94, 275, 278
    - in double direction angular contact thrust ball bearings 50, 94, 308
    - in precision lock nuts 376–377
    - in thrust bearings for screw drives 50, 94, 341, 355–357, 358
  - preservatives 125
  - printing machines 131
  - protectors 381
  - PT** 197
  - PTFE 109
  - pumping effects 96
- Q**
- QBC**
    - angular contact ball bearings 144, 197
    - thrust bearings for screw drives 342–343, 348, 365
  - QBT**
    - angular contact ball bearings 144, 197
    - thrust bearings for screw drives 348, 365
  - QFC**
    - angular contact ball bearings 144, 197
    - thrust bearings for screw drives 342–343, 348, 365
  - QFT**
    - angular contact ball bearings 144, 197
    - thrust bearings for screw drives 348, 365
  - QT**
    - angular contact ball bearings 144, 197
    - thrust bearings for screw drives 348, 365

Note: Designation prefixes and suffixes are shown in **bold**.

## Indexes

## R

racing car wheels 131  
 radial clearance 30, 74, 288  
 radial internal clearance 50–51  
   in cylindrical roller bearings 273–274, 275, 278–279  
 radial location 70–77  
 radial stiffness 68–69  
   of axial-radial cylindrical roller bearings 322–323  
   of cylindrical roller bearings 275–276  
   of typical spindle bearing systems 67  
 reconditioning 125  
 reference grease quantities 101  
   for angular contact ball bearings 102, 199–261  
   for cylindrical roller bearings 103, 289–299  
   for double direction angular contact thrust ball bearings 104, 313–317  
   for thrust bearings for screw drives 104, 367  
 reliability 34–35  
   effect on relubrication interval 109  
 relubrication  
   effect on frictional moment 37  
   intervals and adjustments 106–109  
   of sealed bearings 32, 101  
 relubrication-free 101  
 removal  
   of precision lock nuts 380  
   of stepped sleeves 80–81, 87  
 retaining bolts 330, 335  
 reusing bearings 124  
 rigidity 66–69  
   considerations when selecting a bearing 26, 27  
 ring gauges 393–395  
 robotics 131  
 roller and cage thrust assemblies 320  
 rotary tables 320, 324  
 rotating outer ring loads 71–72  
**RS** 344–345, 363, 364  
 running accuracy  
   of bearings 24–25  
   of seats and abutments 75–76, 325–326  
   of seats and abutments (for screw drives) 349  
   tolerance symbol definitions 49  
 running-in 111–112  
   effect of grease fill on friction 37, 101, 124  
   of axial-radial cylindrical roller bearings 324  
 run-out → running accuracy  
 rust protection 100–101, 125  
**RZ** 344–345, 363, 364

## S

**S** 136, 196  
 safety factors → static safety factors  
 screw drive bearings → thrust bearings for screw drives  
 screw drives 338, 350–351  
 sealed bearings  
   angular contact ball bearings 136, 192  
   grease specifications 104  
   shelf life 125  
   thrust bearings for screw drives 344–345  
   washing 136, 345  
 sealing solutions 32, 95–98  
   materials 56  
 seats  
   accuracy 75–77, 324–326  
   accuracy (for screw drives) 349  
   fits 70–74, 324–326  
   fits (for screw drives) 349  
 selection criteria 20–32  
 semiconductor industry 61, 131  
 serial numbers  
   on angular contact ball bearings 145

  on double direction angular contact thrust ball bearings 305  
 service life  
   of bearings with NitroMax steel rings 52  
   of grease 99, 106  
   of hybrid bearings 34, 37, 52  
 set screws → grub (set) screws  
 sets  
   of angular contact ball bearings 141–144  
   of thrust bearings for screw drives 340, 346–348  
 shaft orientation  
   considerations for oil-air lubrication 117  
   considerations when selecting a grease 99–100  
   effect on relubrication interval 109  
 shaft systems 20  
 shelf life 125  
 shock loads  
   considerations for life calculations 35  
   considerations when selecting a grease 98–99  
   permissible static loads 36  
   suitability of preloading with springs 93  
 silicon nitride ( $\text{Si}_3\text{N}_4$ )  
   in hybrid angular contact ball bearings 133  
   in hybrid cylindrical roller bearings 268  
   in hybrid double direction angular contact thrust ball bearings 304  
   material properties 54  
 silicon wafer chips 61  
 silicone-methyl 109  
 silicone-phenyl 109  
 single direction angular contact thrust ball bearings (for screw drives) 340, 366–367  
   applications 350–351  
   bearing arrangements 346–348  
   compared to other bearings for screw drives 339  
   designation system 364–365  
   designs and variants 22, 340  
   dimension standards 353  
   frictional moment 356, 360  
   in cartridge units 342–343, 372–373  
   load carrying capacity 356, 361  
   preload 355–356  
   product table 366–367  
   reference grease quantities 104, 367  
   sealed bearings 344–345  
   sets 340, 346–348  
   speeds 344, 363  
   stiffness 356, 358  
   temperature limits 344–345  
   tolerance classes and tolerances 24, 353–354  
 single direction bearings 340, 366–367  
   in cartridge units 342–343, 372–373  
 single row cylindrical roller bearings 264, 288–293  
   axial displacement 264, 269, 280  
   axial drive-up 278–279  
   basic design bearings 264  
   cages 264, 267  
   compared to double row cylindrical roller bearings 264  
   designs and variants 264  
   dimension standards 269  
   equivalent bearing loads 277  
   gauges for checking tapered seats 391–407  
   high-speed design bearings 264  
   hybrid bearings 268  
   initial grease fill 101, 103, 105  
   internal clearance 273–274, 275, 278–279  
   lubrication features 268  
   mounting 278–279, 401  
   preload 275, 278  
   product tables 288–293  
   speeds 264, 268, 277  
   stiffness 275–276  
   tolerance classes and tolerances 24, 269–272  
 sintered steel 378, 382  
 SKF LubeSelect 100  
 SKF Microdosage system 121  
 SKF Spindle Service Centres 125, 166

Note: Designation prefixes and suffixes are shown in **bold**.



SKF Spindle Simulator 33, 358  
 skidding 90–91, 322  
   benefits of hybrid bearings 133, 268, 304  
 sleeves  
   spacer sleeves 78  
   stepped sleeves 79, 80–87  
 smearing 133, 268, 304  
 soaps 110  
 sodium thickeners 110  
**SP**  
   cylindrical roller bearings 273, 286  
   double direction angular contact thrust ball bearings 311  
 spacer rings  
   effect on running-in of bearings 111  
   for angular contact ball bearings 166–172, 192–193  
   for cylindrical roller bearings 78, 282–285  
   for oil-air lubrication 116  
 spacer sleeves 78  
 spacers → spacer rings  
 spanners 379, 384–388  
**SPC2** 273, 286  
 speed factor 33  
 speeds 38–45  
   attainable speeds 44  
   considerations when selecting a bearing 28  
   for typical spindle bearing systems 45  
   permissible speeds 39  
   with grease lubrication 42–45  
   with oil lubrication 40–41, 44–45  
 Spindle Service Centres → SKF Spindle Service Centres  
 Spindle Simulator → SKF Spindle Simulator  
 spindles  
   applications 57–64  
   service 125, 166  
 splash guards 96–97  
 spring curves 91  
 springs 64, 90, 93, 165  
 stainless steels → NitroMax steel  
 standalone bearings 141  
 start-up  
   benefits of hybrid bearings 133, 268, 304  
   benefits of preload 90  
   considerations when selecting a grease 100  
   effect of grease fill 37  
   when running in 111–112, 124  
 static loads 36  
 static safety factors 36  
 steels 51–54  
 stepped sleeves 79, 80–87  
   designs 80, 84  
   dimensions 81–83  
   fits 80, 84  
   installation 86–87, 123–124  
   load carrying capacity 84–85  
   material 84  
   removal 87  
   with O-ring 80, 81, 83  
   without O-ring 80, 81–82  
 stiffness 66–69  
   of angular contact ball bearings 173–182  
   of axial-radial cylindrical roller bearings 322–323  
   of cylindrical roller bearings 275–276  
   of double direction angular contact thrust ball bearings 309  
   of thrust bearings for screw drives 339, 356–359  
 stirrup gauges 405  
 storage  
   of bearings 125, 330  
   of lubricants 122  
 super-precision bearings  
   selection criteria 20–32  
   types and designs 21–22  
 surface roughness 75, 77, 325–326  
 surface treatments 342  
 synthetic oils  
   compatibility 109  
   considerations when selecting a grease 99

effect on cage materials 55  
 system rigidity → rigidity

## T

tandem arrangements  
   with angular contact ball bearings 142–144  
   with thrust bearings for screw drives 346–348  
 taper gauges 396–399  
 tapered bores 264–265, 272  
 tapered seats  
   checking the accuracy with a ring gauge 393  
   checking the accuracy with a taper gauge 396–397  
**TBT**  
   angular contact ball bearings 144, 197  
   thrust bearings for screw drives 348, 365  
 telescopes 131  
 temperatures  
   ambient 39  
   operating 37  
 test running 124  
**TFT**  
   angular contact ball bearings 144, 197  
   thrust bearings for screw drives 348, 365  
 thermal contraction 31  
 thermal expansion 31  
   effect on preload and internal clearance 50–51, 93  
   of silicon nitride versus steel 54  
 thickeners 110  
 thin-walled rings 75, 81, 123  
 threaded holes  
   in double direction angular contact thrust ball bearings 355  
   in housings 88  
   in shafts 89  
 thrust bearings  
   axial-radial cylindrical roller bearings 319–335  
   cartridge units (for screw drives) 342–343, 372–373  
   double direction bearings 301–317  
   double direction bearings (for screw drives) 341, 368–371  
   single direction bearings (for screw drives) 340, 366–367  
 thrust bearings for screw drives 337–373  
   applications 350–351  
   associated components 349  
   bearing arrangements 346–348  
   cages 344  
   cartridge units 342–343, 372–373  
   contact angles 340, 341  
   designation system 364–365  
   designs and variants 22, 338–345  
   dimension standards 353  
   dismounting 341  
   double direction bearings 341, 368–372  
   equivalent bearing loads 361–362  
   frictional moment 339, 346–360  
   initial grease fill 101, 104–105  
   lifting forces 94, 360  
   load carrying capacity 30, 339, 346, 361  
   lubrication 99, 106, 342, 344  
   markings 352  
   matched sets 340, 346–348  
   misalignment 346  
   moment stiffness 357  
   mounting 123, 339, 345, 352, 362  
   non-locating bearings 347  
   preload 50, 94, 355–357, 358  
   reference grease quantities 104, 367  
   relubrication 106–109, 341, 344  
   sealed bearings 339, 344–345  
   selection criteria 339  
   single direction bearings 340, 366–367  
   speeds 41, 43, 339, 344, 363  
   stiffness 339, 356–359  
   temperature limits 344–345  
   tolerance classes and tolerances 24, 353–354

Note: Designation prefixes and suffixes are shown in **bold**.

Indexes

universally matchable bearings 340, 346–348, 352  
washing 345  
tightening torques  
for locating angular contact ball bearings 183–189  
for precision lock nuts 384–388  
**TN** 264, 267, 286  
**TN9**  
cylindrical roller bearings 264, 267, 286  
double direction angular contact thrust ball bearings 304–305, 311  
**TNHA**  
angular contact ball bearings 134, 196  
cylindrical roller bearings 264, 267, 268, 286  
tolerance classes  
for bearings 24–25  
for seats 71–74, 325–326  
for seats (for screw drives) 349  
tolerance grades → IT tolerance grades  
tolerances 47  
symbols and definitions 48–50  
tommy bars 379  
torque wrenches 380  
toughness → impact toughness  
transition fits 71  
trial mounting 282–285  
troubleshooting 124  
**TT**  
angular contact ball bearings 144, 197  
thrust bearings for screw drives 348, 365  
turbochargers 131

U

unit conversion table 10  
universally matchable bearings  
angular contact ball bearings 141–144, 194  
thrust bearings for screw drives 340, 346–348, 352  
unloading forces 322–323  
**UP**  
cylindrical roller bearings 286  
double direction angular contact thrust ball bearings 311

V

**V** 141, 196  
vertical shaft arrangements  
applications 61, 131–132  
effect on relubrication interval 109  
with grease lubrication 99  
with oil-air lubrication 117  
with thrust bearings for screw drives 346–347  
vibrations  
considerations when selecting a grease 99–100  
troubleshooting 124  
viscosity  
considerations when selecting a grease 99–100  
of grease in sealed bearings 104  
of lubricating oils 121  
of mounting and dismounting fluids 87  
**VR521** 286  
V-shaped markings  
on angular contact ball bearings 145  
on double direction angular contact thrust ball bearings 305  
on thrust bearings for screw drives 352  
**VU001** 267, 286

W

**W33**

cylindrical roller bearings 266, 286  
double direction angular contact thrust ball bearings 311  
**W33X** 286  
washing  
bearings before regreasing 109  
sealed bearings 32, 136, 345  
water  
considerations when selecting a grease 99–100  
effect on lubricant shelf life 122  
resistance of NBR 56  
wash-out 100  
wear  
resistance of hybrid bearings 34  
resistance of NitroMax steel 52  
width series 46  
woodworking machines 132

Note: Designation prefixes and suffixes are shown in **bold**.

