

➤ Lifting stations

Lifting station type ABS Nirolift

Features and benefits

- Globular shape for extra strength
- Easily transported and fitted. Compact dimensions allow passage through a standard door opening
- Kit available as an accessory for sealing the top of the tank to a damp-proof course
- Universally adjustable in height and can be swiveled: easy to align with floor levels and tiling patterns

Key characteristics

Capacities	up to 16 m ³ /h
Heads	up to 11 m
Temperatures	40°C up to 60°C (max. 5 minutes)
Motor power	0.16–0.56 kW

Applications

- Pumping wastewater without toilet waste
- Washing machines, sinks, dishwashers, showers, and bathtubs



Lifting station type ABS Piranhamat

Features and benefits

- Ready for installation; robust, compact tank for buildings
- Easily transported and installed
- Fitted with Piranha submersible grinder pumps for problem-free pumping of sewage containing toilet waste

Key characteristics

Capacities	up to 9.8 m ³ /h / 43 USgpm
Heads	up to 30 m / 110 ft.
Temperatures	40°C up to 60°C (max. 5 minutes) / 104°F up to 140°F (max. 5 minutes)
Motor power	0.40–1.7 kW / 0.9–2.4 hp

Applications

- Sewage and wastewater containing toilet waste
- Locations where the diameter of the discharge line is restricted



Lifting station type ABS Sanimat

Features and benefits

- Ready for installation
- Robust, compact tank
- Easily transported and fitted, compact dimensions allow passage through a standard door opening
- Problem-free pumping of sewage and wastewater
- Dynamic pressure level sensor on the tank, with separate sensors for inflow level and high water alarm

Key characteristics

Capacities	up to 165 m ³ /h
Heads	up to 18 m
Temperatures	40°C up to 60°C (max. 5 minutes)
Motor power	1.3–6.0 kW

Applications

- Sewage and wastewater containing toilet waste
- Apartment blocks, hospitals, hotels, and large commercial developments



Lifting station type ABS Sanimax

Features and benefits

- Supplied as standard with pump, automatic level control and non-return valve
- Compact lifting station suitable for installation at floor level near the wastewater source below the sewer backwash level
- Flood-proof, with and odor preventing vent system
- Alarm float switch available as accessory

Key characteristics

Capacities	up to 16 m ³ /h
Heads	up to 11 m
Temperatures	40°C up to 60°C (max. 5 minutes)
Motor power	0.16–0.56 kW

Applications

- Pumping of wastewater without toilet waste
- Sinks
- Showers and bathtubs
- Domestic washing machines
- Domestic dishwashers, showers, and bathtubs



Lifting station type ABS Sanisett

Features and benefits

- Synthetic, single or twin pumping station for wastewater without toilet waste
- Easily transported and fitted. Compact dimensions allow passage through a standard door opening
- Kit available as an accessory for sealing top of tank to damp proof course
- Universally adjustable in height and can be swiveled: easy to align with floor levels and tiling patterns

Key characteristics

Capacities	up to 22 m ³ /h
Heads	up to 21 m
Temperatures	40°C up to 60°C (max. 5 minutes)
Motor power	0.16–2.0 kW

Applications

- Pumping of wastewater without toilet waste
- Washing machines, sinks, dish- washers, showers, and bathtubs
- For pumping of sewage with toilet waste outside of areas covered by EN when using Piranha pump



Lifting station type ABS Synconta

Features and benefits

- Simple pump installation and maintenance – no need to enter the sump
- Pump seals automatically onto the discharge line when lowered into the high level coupling, irrespective of the inflow or direction of the discharge lines
- For fitting with pumps from the Piranha and AS ranges

Key characteristics

Capacities	up to 38 m ³ /h
Heads	up to 37 m
Temperatures	40°C up to 60°C (max. 5 minutes)
Motor power	1.3–2.6 kW

Applications

- Sewage and wastewater containing toilet waste

