

## Plain End System for Carbon Steel

**QuickVic™ SD Threaded Adapters****NO. P40 THREADED ADAPTER****(MALE NPT x PLAIN END)****NO. P80 THREADED ADAPTER****(FEMALE NPT x PLAIN END)**

[Download publication 34.01](#) for complete information

- For use on plain end Schedules 10 through 80 carbon steel pipe
- Compatible with QuickVic™ SD couplings, fittings and valve
- Sizes from ½–1¼" | DN15–DN32
- Regional availability, contact [Victaulic](#) for details

**QuickVic™ SD Dielectric Adapters****NO. P47 STRAIGHT DIELECTRIC ADAPTER****(SWEAT x PLAIN END)****NO. P97 90° ELBOW DIELECTRIC ADAPTER****(SWEAT x PLAIN END)**

[Download publication 34.01](#) for complete information

- For use on plain end Schedules 10 through 80 carbon steel pipe
- Compatible with *QuickVic* SD couplings, fittings and valve
- Sizes from ½–1¼" | DN15–DN32
- Regional availability, contact [Victaulic](#) for details

**QuickVic™ SD Ball Valve****SERIES P89**

[Download publication 34.01](#) for complete information

- For use on plain end Schedules 10 through 80 carbon steel pipe
- Sizes from ½–2" | DN15–DN50
- Pressures up to 300 psi | 2068 kPa | 21 bar
- Regional availability, contact [Victaulic](#) for details