

OGS

Original Groove System (OGS)



OS&Y Gate Valve

SERIES 771M

[Download publication 08.45](#) for complete information

- Available as groove x groove or groove x flange
- For On/Off service only
- Sizes from 2½–12" | 73.0mm–DN300
- Pressures up to 250 psi | 1725 kPa | 17 bar

Certifications/Listings:

This product is not agency listed for fire protection service.
[Download publication 10.92](#) for fire service products.

AGS

VBSP

Hole Cut

Plain End

Stainless Steel

Potable Water

Shouldered Steel

Ductile Iron

High Performance

Hydronic Balancing

HDPE

Aquamine™ PVC

CPVC/PVC

Specialty

Tools

Gaskets, Seals and O-Rings

Design Data

Reference Guide



OS&Y Gate Valve

SERIES 371

[Download publication 08.48](#) for complete information

- Conforms to AWWA C-509 requirements
- For On/Off service only
- Series 371 sizes from 2½–12" | 73.0mm–DN300 available with Original Groove System (OGS) ends
- Series W371 sizes from 14–16" | DN350–DN400 available with Advance Groove System (AGS) ends, see pg. 34
- Pressures up to 250 psi | 1725 kPa | 17 bar

Certifications/Listings:

This product is not agency listed for fire protection service.
[Download publication 10.92](#) for fire service products.



NRS Gate Valve

SERIES 372

[Download publication 08.48](#) for complete information

- Conforms to AWWA C-509 requirements
- For On/Off service only
- Series 372 sizes from 2½–12" | 73.0mm–DN300 available with Original Groove System (OGS) ends
- Series W372 sizes from 14–16" | DN350–DN400 available with Advance Groove System (AGS) ends, see pg. 34
- Pressures up to 250 psi | 1725 kPa | 17 bar

Certifications/Listings:

This product is not agency listed for fire protection service.
[Download publication 10.92](#) for fire service products.

