

Advanced Groove System **AGS**



**AGS Fittings**

[Download publication 20.05](#) for complete information

- Sizes from 14–60" | DN350–DN1500
- Fitting pressure ratings are equivalent to the maximum allowable working pressure (MAWP) of joints installed with Victaulic® AGS couplings
- For original groove fittings, [download publication 07.01](#) for more information

**Certifications/Listings:**



[Download publication 10.01](#) for Fire Protection Certifications/Listings



**No. W10**  
90° Elbow



**No. W11**  
45° Elbow



**No. W12**  
22½° Elbow



**No. W13**  
11¼° Elbow



**No. W100**  
90° 1½ D Long  
Radius Elbow



**No. W110**  
45° 1½ D Long  
Radius Elbow



**No. W20**  
Tee



**No. W25**  
Reducing Tee



**No. W30**  
45° Lateral



**No. W30-R**  
45° Reducing  
Lateral



**No. W33**  
True Wye



**No. W35**  
Cross



**No. W42**  
Adapter Nipple  
(AGS Groove x  
Bevel)



**No. W43**  
Adapter Nipple  
(AGS Groove x  
AGS Groove)



**No. W45R**  
Flanged  
Adapter Nipple



**No. W49**  
Adapter Nipple  
(AGS Groove x  
OGS Groove)



**No. W50**  
Concentric  
Reducer



**No. W51**  
Eccentric  
Reducer



**No. W60**  
Cap

