




INTERCAMBIADORES VINCKE / VINCKE HEAT EXCHANGERS / ÉCHANGEURS VINCKE

INTERCAMBIADORES AIRE/ACEITE VINCKE
VINCKE AIR/OIL HEAT EXCHANGERS
ÉCHANGEURS AIR/HUILE VINCKE




INTERCAMBIADORES AIRE/ACEITE CON BY-PASS Y VALVULA TERMOSTATICA VINCKE
AIR/OIL HEAT EXCHANGERS WITH BY-PASS AND THERMOSTATIC VALVE VINCKE
ÉCHANGEURS AIR/HUILE AVEC BY-PASS ET VALVE THERMOSTATIQUE VINCKE






INTERCAMBIADORES VINCKE EXLV PARA CAUDALES DE 5 A 100 L/M
EXLV HEAT EXCHANGERS VINCKE FLOWS FROM 5 TO 100 L/M
ÉCHANGEURS VINCKE EXLV DEBITS 5 A 100 L/M

Ref.	Type	Long.	Q (l/min.)		Rang.			Volt.
VNKEXLV1-12-A-60	VNKEXLV1	297x290x63	100	3/4	60°C	20	30	12 dc
VNKEXLV1-24-A-60	VNKEXLV1	297x290x63	100	3/4	60°C	20	30	24 dc
VNKEXLV1-22-A-47-C	VNKEXLV1	297x290x63	100	3/4	47°C	20	30	220 ac
VNKEXLV1-38-A-47	VNKEXLV1	297x290x63	100	3/4	47°C	20	30	380 ac

INTERCAMBIADORES VINCKE EXLV PARA CAUDALES DE 10 A 120 L/M
EXLV HEAT EXCHANGERS VINCKE FLOWS FROM 10 TO 120 L/M
ÉCHANGEURS VINCKE EXL DEBITS 10 A 120 L/M





Ref.	Type	Long.	Q (l/min.)		Rang.			Volt.
VNKEXLV2-12-A-60	VNKEXLV2	354x390x63	120	3/4	60°C	20	30	12 dc
VNKEXLV2-24-A-60	VNKEXLV2	354x390x63	120	3/4	60°C	20	30	24 dc
VNKEXLV2-22-A-47-C	VNKEXLV2	354x390x63	120	3/4	47°C	20	30	220 ac
VNKEXLV2-38-A-47	VNKEXLV2	354x390x63	120	3/4	47°C	20	30	380 ac

INTERCAMBIADORES VINCKE EXLV PARA CAUDALES DE 20 A 150 L/M
EXLV HEAT EXCHANGERS VINCKE FLOWS FROM 20 TO 150 L/M
ÉCHANGEURS VINCKE EXLV DEBITS 20 A 150 L/M

Ref.	Type	Long.	Q (l/min.)		Rang.			Volt.
VNKEXLV3-12-A-60	VNKEXLV3	397x440x63	150	1"	60°C	20	30	12 dc
VNKEXLV3-24-A-60	VNKEXLV3	397x440x63	150	1"	60°C	20	30	24 dc
VNKEXLV3-22-A-47-C	VNKEXLV3	397x440x63	150	1"	47°C	20	30	220 ac
VNKEXLV3-38-A-47	VNKEXLV3	397x440x63	150	1"	47°C	20	30	380 ac

INTERCAMBIADORES EXK PARA CAUDALES DE 5 A 60 L/M
EXK HEAT EXCHANGERS FLOWS FROM 5 TO 60 L/M
ÉCHANGEURS EXK DEBITS 5 A 60 L/M






Ref.	Type	Q (l/min.)			Rang.			Volt.
VNKEKK2-12-A-60	EXK2	55	26x150	1" 1/4	60°C	5	5	12 dc
VNKEKK2-24-A-60	EXK2	55	26x150	1" 1/4	60°C	5	5	24 dc
VNKEKK3-12-A-60	EXK3	60	26x150	1" 1/4	60°C	5	5	12 dc
VNKEKK3-24-A-60	EXK3	60	26x150	1" 1/4	60°C	5	5	24 dc

INTERCAMBIADORES VINCKE / VINCKE HEAT EXCHANGERS / ÉCHANGEURS VINCKE




INTERCAMBIADORES AGUA/ACEITE EXW PARA CAUDALES DE 30 A 400 L/M
EXW WATER/OIL HEAT EXCHANGERS FLOWS FROM 30 TO 400 L/M
ÉCHANGEURS EAU/HUILE EXW DEBITS 30 A 400 L/M



Ref.	Type	Q (l/min.)			
VNKEW1-14-2	EXW1	30	3/8	12	18
VNKEW1-26-2	EXW1	40	3/8	12	18
VNKEW1-44-2	EXW1	50	3/8	12	18
VNKEW1-9-2I	EXW1	30	3/8	12	18
VNKEW1-19-2I	EXW1	40	3/8	12	18
VNKEW2-12-2	EXW2	50	1/2	12	18
VNKEW2-28-2	EXW2	60	1/2	12	18
VNKEW2-53-2	EXW2	80	1/2	12	18
VNKEW2-18-2I	EXW2	60	1/2	12	18
VNKEW3-15-4	EXW3	70	1/2	12	18
VNKEW3-31-4	EXW3	90	1/2	12	18
VNKEW3-38-4	EXW3	90	1/2	12	18
VNKEW3-56-4	EXW3	90	1/2	12	18
VNKEW3-71-4	EXW3	130	1/2	12	18
VNKEW3-87-4	EXW3	140	1/2	12	18
VNKEW4-31-4	EXW4	125	1/2	12	18
VNKEW4-38-4	EXW4	125	1/2	12	18
VNKEW4-56-4	EXW4	155	1/2	12	18
VNKEW4-71-4	EXW4	185	1/2	12	18
VNKEW4-87-4	EXW4	195	1/2	12	18
VNKEW5-28-4	EXW5	170	1"	12	18
VNKEW5-53-4	EXW5	220	1"	12	18
VNKEW5-84-4	EXW5	300	1"	12	18
VNKEW5-99-4	EXW5	310	1"	12	18
VNKEW6-28-4	EXW6	160	1"	12	18
VNKEW6-53-4	EXW6	230	1"	12	18
VNKEW6-54-4	EXW6	300	1"	12	18
VNKEW6-83-4	EXW6	420	1"	12	18
VNKEW6-84-4	EXW6	270	1"	12	18
VNKEW6-99-4	EXW6	310	1"	12	18
VNKEW6-113-4	EXW6	450	1"	12	18
VNKEW6-114-4	EXW6	320	1"	12	18
VNKEW7-47-4	EXW7	455	1" 1/2	12	18
VNKEW7-77-4	EXW7	525	1" 1/2	12	18
VNKEW7-108-4	EXW7	570	1" 1/2	12	18
VNKEW7-138-4	EXW7	570	1" 1/2	12	18
VNKEW8-74-4	EXW8	134	2"	12	18
VNKEW8-104-4	EXW8	186	2"	12	18
VNKEW8-135-4	EXW8	239	2"	12	18
VNKEW8-165-4	EXW8	291	2"	12	18

INTERCAMBIADORES AUTÓNOMOS AIRE/ACEITE PARA CAUDALES DE 30 A 50 L/M
AUTONOMOUS HEAT EXCHANGERS AIR/OIL FLOWS FROM 30 TO 50 L/M
ÉCHANGEURS AUTONOMES AIR/HUILE POUR DEBITS 30 A 50 L/M



Ref.	Type	Q (l/min.)		Rang.			Volt.
VNKEXA1-22-A-47	EXRA1	30	3/4	47°C	20	30	220 ac
VNKEXA1-38-A-47	EXRA1	30	3/4	47°C	20	30	380 ac
VNKEXA2-22-A-47	EXRA2	30	3/4	47°C	20	30	220 ac
VNKEXA2-38-A-47	EXRA2	30	3/4	47°C	20	30	380 ac
VNKEXA3-22-A-47	EXRA3	30	3/4	47°C	20	30	220 ac
VNKEXA3-38-A-47	EXRA3	30	3/4	47°C	20	30	380 ac
VNKEXA4-22-A-47	EXRA4	50	3/4	47°C	20	30	220 ac
VNKEXA4-38-A-48	EXRA4	50	3/4	47°C	20	30	380 ac
VNKEXA5-22-A-47	EXRA5	50	3/4	47°C	20	30	220 ac
VNKEXA5-38-A-47	EXRA5	50	3/4	47°C	20	30	380 ac
VNKEXA6-22-A-47	EXRA6	50	3/4	47°C	20	30	220 ac
VNKEXA6-38-A-47	EXRA6	50	3/4	47°C	20	30	380 ac