

CANopen

PRO COM CANopen

PRO COM CAN OPEN



Technical data

System data
Connection type
Field bus protocol
Module type
Interface
General data
Ambient temperature (operational)
Protection degree
Weight
Depth x width x height
Approvals
Approvals

2 x RJ45 plug-in connectors
CANopen
plug-on module
PROtop interconnection interface
-25 °C...70 °C
IP20
36 g
33.6 / 35 / 74.4 mm
ABS; BURVER; CCS; cULus; cULusEX; DETNORVER; RINA

Note

Ordering data

||
||
||

Type	Qty.	Order No.
PRO COM CAN OPEN	1	2467320000

Note

||
||
||

PRO COM IO-LINK

PRO COM IO-LINK



Technical data

System data
Connection type
IO link standard
Compatible IO-Link Master
Module type
Interface
General data
Ambient temperature (operational)
Protection degree
Weight
Depth x width x height
Approvals
Approvals

IO-Link
IEC 61131-9
Beckhoff, GE, Rockwell, Siemens, Weidmüller
plug-on module
topGUARD interconnection interface, PROtop interconnection interface
-25 °C...70 °C
IP20
29 g
33.6 / 35 / 74.4 mm
ABS; BURVER; CE; cULus; cULusEX; DETNORVER; LLOYDSREG; RINA

Note

--

Ordering data

--

Type	Qty.	Order No.
PRO COM IO-LINK	1	2587360000

Note

--

Display 7S

PRO COM Display 7S

PRO COM Display 7S



Technical data

General data	
Ambient temperature (operational)	-25 °C...70 °C
Protection degree	IP20
Depth x width x height	33.6 / 34 / 74.4 mm
Weight	36 g
Approvals	
Approvals	CE; cULus; cULusEX

Note	
------	--

Ordering data

Type	Qty.	Order No.
PRO COM DISPLAY 7S	1	2466960000

Note	
------	--