

Hub version 5: flange-mounting

	T_{KN} (Nm)	$T_{K,max}$ (Nm)	n_{max} (1/min)	ΔK_v (mm)	$\Delta K_{r,min}$ (mm)	ΔK_r (mm)	ΔK_s (mm)	ΔK_w (°)	C_t (kNm/rad)	J (kg cm ²)	m (kg)	ØR (mm)	H (mm)	L (mm)	Ød (mm)	ØF (mm)	SkG
P 4800	4.800	9.380	900	219	30	115	2	0,3	1.075	4.080	45	250	33	196	100	200	10xM20
P 4805	4.800	9.380	1.000	162	22	85	2	0,3	1.075	4.000	43	250	33	196	100	200	10xM20
P 6610	6.610	12.940	800	219	30	115	2	0,2	1.483	8.700	52	280	33	196	150	230	12xM20
P 6615	6.610	12.940	1.000	162	22	85	2	0,2	1.483	5.600	43	280	33	196	150	230	12xM20

Order Example 1: P 350.55 Order Example 2: P 595.55

P 595	55
Type Schmidt-Kupplung® Power Plus P 595	both sides flange-mounting

To ensure the correct selection of the Schmidt-Kupplung® please use the TD Calculator of the column Schmidt-Kupplung® or please use our selection procedure and legend area to download the required information.