

REFERENCIA Y FIGURA REFERENCE AND FIGURE	DESCRIPCIÓN Y DIMENSIONES DESCRIPTION AND DIMENSIONS	CÓDIGO CODE	MEDIDA SIZE	TIPO ACT. ACT. TYPE	PESO WEIGHT
---	---	----------------	----------------	------------------------	----------------



Instalados sobre válvula manual
Installed on handle valve
Electromecánico a válvula soldar/rosca (*)
Electromechanical welded/threaded valve ()*

Electromecánico a válvula bridada (*)
Electromechanical flanged valve ()*

Inductivos a válvula soldar/rosca (*)
Inductive welded/threaded valve ()*
(NCB2-V3-V0 "P+F")

Inductivos a válvula bridada (*)
Inductive flanged valve ()*
(NCB2-V3-V0 "P+F")

5315 00	1/4"-1/2"			
5315 01	3/4"-1"			
5315 02	1 1/4"-2"			
5315 03	2 1/2"-4"			

5328 00	1/2"-3/4"			
5328 01	1"			
5328 02	1 1/4"-2"			
5328 03	2 1/2"-4"			

5315 10	1/4"-1/2"			
5315 11	3/4"-1"			
5315 12	1 1/4"-2"			
5315 13	2 1/2"-4"			

5328 10	1/2"-3/4"			
5328 11	1"			
5328 12	1 1/4"-2"			
5328 13	2 1/2"-4"			

(*) (Válvula no incluida) / (Valve not included)



Instalados sobre reductor manual
Installed on gear operator

Electromecánico (**)
Electromechanical

Inductivos (NCB2-V3-V0 "P+F") (**)
Inductive (NCB2-V3-V0 "P+F")

Inductivos ALPS 10-30V (**)
Inductive ALPS 10-30V

5981 00				
5982 00				

5983 00				
---------	--	--	--	--

(**) (Reductor manual no incluido) / (Gear operator not included)

MONTAJES BAJO DEMANDA / ASSEMBLY ON REQUEST



Válvulas de esfera con reductor manual
Ball valves with gear operator



Válvula de asiento inclinado con microinterruptores
final de carrera
Angle seat valve with limit switch box