








CARVER CLAMP SERIES

Product Overview

Buttress-Style


	Model	Holding Capacity max	Page MC-CVR-#
	T614-0	[2900 lbf] 13000N	7-8
	T614-1	[14000 lbf] 62500N	
	T614-2	[18000 lbf] 80000N	

T-Slot Style


	Model	Holding Capacity max	Page MC-CVR-#
	T400-4 T400-6 T400-8	[5100 lbf] 22700N	9-12
	T600-4 T600-6 T600-8	[3600 lbf] 16000N	
	T402-6 T402-12 T402-18 T402-24	[8160 lbf] 36300N	
	T602-6 T602-12 T602-18	[5620 lbf] 25000N	

Typical Applications

Buttress Clamps



T-Slot Clamps



Ideal for use as manual die clamps. Eliminates the need for step blocks or riser blocks.

T-SLOT SERIES

CARVER Clamps | Product Overview

Features:

These clamps provide rapid height adjustment and positive holding. They are designed with a single-unit clamp head and base. The DESTACO Carver T-Slot Clamp is one single assembly – there are no loose parts. When setting up, the safety lock on the back is released and the clamp lifted on the base to the desired height. When the clamp screw is turned, 100% of the force is transmitted to the work-piece. Backing off the clamp adjusting screw and releasing the safety lock and lifting the clamp head makes for rapid job changeover.







If the clamping height is more than [29.5in] 750mm the connector shown below will be delivered as standard equipment.

MODEL T813400



Technical Information | Holding Capacities


Holding Capacity	Throat Depth		Working Height C		Model	Max. Torque	Accessories Standard Equipment	Weight [lbs.] kg
	a	b	min.	max.				
 [5100 lbf] 22700N	[0.55] 14	[1.30] 33	[0.50] 12	[4.00] 100	T400-4	[36 ft. lbs.] 49Nm	(2) M12 T-nuts for 14mm T-slot T2060-05	[5.1] 2,3
			[0.50] 12	[6.00] 150	T400-6			[5.5] 2,5
			[2.00] 50	[8.00] 200	T400-8			[5.7] 2,6
 [3600 lbf] 16000N	[2.24] 57	[2.87] 73	[0.50] 12	[4.00] 100	T600-4	[30 ft. lbs.] 40Nm	(2) M12 T-nuts for 14mm T-slot T2060-05	[5.9] 2,7
			[0.50] 12	[6.00] 150	T600-6			[6.4] 2,9
			[2.00] 50	[8.00] 200	T600-8			[6.6] 3,0
 [8160 lbf] 36300N	[1.73] 44	[2.68] 68	0	[6.00] 150	T402-6	[85 ft. lbs.] 115Nm	(2) M16 T-nuts for 18mm T-slot T2060-07	[14.00] 6.4
			0	[12.00] 300	T402-12			[17.70] 8.0
			[6.00] 150	[18.00] 450	T402-18			[19.40] 8.8
			[12.00] 300	[24.00] 600	Ⓜ T402-24			[20.00] 9.0
 [5320 lbf] 25000N	[3.90] 99	[4.84] 123	0	[6.00] 150	T602-6	[70 ft. lbs.] 95Nm	(2) M16 T-nuts for 18mm T-slot T2060-07	[16.00] 7.3
			0	[12.00] 300	T602-12			[19.80] 9.0
			[6.00] 150	[18.00] 450	Ⓜ T602-18			[21.60] 9.8

Ⓜ Available upon request



These clamps provide rapid height adjustment and positive holding. They are designed with a single-unit clamp head and base, providing up to [8000 lbf] 35.6kn. of positive holding capacity for workpieces up to 60" high. The design applies 100% of the screw

force directly onto the workpiece far more than any strap clamp arrangement. Additionally, there is no searching for the correct riser block height. The DESTACO Carver T-Slot Clamp is one single assembly – there are no loose parts.

When setting up, the safety lock on the back is released and the clamp lifted on the base to the desired height. When the clamp screw is turned, 100% of the force is transmitted to the workpiece. Backing off the clamp adjusting screw and releasing the safety lock and lifting the clamp head makes for rapid job changeover.



Ideal for use as manual die clamps. Eliminates the need for step blocks or riser blocks.



Safety – No loose parts. Clamp and base are one unit.

Higher clamping force holds parts more securely and safely.


Speed – The clamp head adjusts much faster than an operator can select proper size spacers and bolts. Benefits include:

- Cuts set-up time by as much as 80%
- Reduces machine downtime
- Offers more rapid loading and unloading

Economy – Tool tip technology and digital control have reduced machining time. Why lose these advantages on long set-up times? T-Slot clamps can reduce set-up time by as much as 80%. Benefit: Money saved.

Ease of Operation – Loosen adjusting screw and release safety catch to adjust height instantly.

Versatility - Selection of bases gives standard clamping heights from 0 to 600mm[0 to 24in.]. Additional heights available up to 1500mm[60in.] are available upon request. Two or more heads can be used on one base to position and hold down as well as support – ideal for fine height adjustment during set-up. Also eliminates riser blocks.



The T402 and T602 can be reversed on their bases to give added reach.

