

**Atornilladores de impacto**

 DF010DSE  
 TD022DSE  
 TD110DSAE  
 TD110DZ

**LITHIUM-ION**

**CXT**


	7,2V		10,8V	
	DF010DSE	TD022DSE	TD110DSAE	TD110DZ
R.p.m	200 - 650	0 - 2.450	0 - 2.600	0 - 2.600
Tipo de embrague	N/A	N/A	N/A	N/A
Rango de par	0,5 - 6 Nm	25 Nm	0 - 110 Nm	0 - 110 Nm
Impactos por minuto	N/A	3.000 lpm	3.500 lpm	3.500 lpm
Tornillo mecánico	N/A	M3 - M8	M4 - M8	M4 - M8
Tornillo	M5	M3 - M8	M5 - M12	M5 - M12
Niveles de ruido	70 dB	96 dB	105 dB	105 dB
Presión sonora	70 dB	85 dB	94 dB	94 dB
Vibración	2,5 m/s <sup>2</sup>	7,0 m/s <sup>2</sup>	1,2 m/s <sup>2</sup>	8,0 m/s <sup>2</sup>
Voltage	7,2 V	7,2 V	10,8 V	1,8 V
Inserción	1/4" Hex	1/4" Hex	1/4" Hex	1/4" Hex
Tipo de batería	Litio-ion	Litio-ion	Litio-ion	Litio-ion
1,0Ah	194355-4	194355-4		
1,5Ah				
2,0Ah			197394-3	
3,0Ah				
Peso	0,55Kg	0,53Kg	1,0Kg	1,0Kg
Punto de luz	✓	✓	✓	✓
Luces de aviso	X	X	X	X
Señal acústica	X	X	X	X
Escobillas	✓	✓	✓	✓
Motor BL	X	X	X	X
Dimensiones				
Largo	224 mm	282 mm	153 mm	153 mm
Ancho	43 mm	42 mm	66 mm	66 mm
Alto	141 mm	14 mm	204 mm	204 mm


**Baterías (opcional)**

 BL7010  
 (194355-4)

 BL1020B  
 (197394-3)

 BL1040B  
 (197402-0)
