



Fresa de ranurar de metal duro enteriza y punta esférica CoroMill® Plura para perfilado

Para material no férreo

FHA 40°
BSG COROMANT
TCDC h10
TCDCON h8
PSIR 0°



Versión métrica

						N	Dimensiones, mm			
						HTUF	DCON _{MS}	LF	DN	
DC	CZC _{MS}	APMX	RE ₁	LU	ZEFP	Código de pedido				
3.0	3	5.0	1.50	8.8	2	2B330-0300-NC	★	3.0	38.0	2.7
4.0	4	7.0	2.00	11.8	2	2B330-0400-NC	★	4.0	50.0	3.7
5.0	5	10.0	2.50	14.8	2	2B330-0500-NC	★	5.0	50.0	4.7
6.0	6	11.0	3.00	17.8	2	2B330-0600-NC	★	6.0	57.0	5.7
8.0	8	14.0	4.00	23.8	2	2B330-0800-NC	★	8.0	63.0	7.7
10.0	10	18.0	5.00	29.8	2	2B330-1000-NC	★	10.0	73.0	9.7
12.0	12	22.0	6.00	35.8	2	2B330-1200-NC	★	12.0	83.0	11.7
16.0	16	29.0	8.00	47.8	2	2B330-1600-NC	★	16.0	92.0	15.7



A192



A194



E9



E22



E14

