

# ENC ZZ 200°

ZZ

## TECHNICAL CHARACTERISTICS

- AISI 52100 Steel
- C4 radial clearance
- Grease from -25° C to 200°C
- ZZ shields

## FIELDS OF USE

- Industrial fans
- Packaging machinery
- Ceramic industry
- Roller chains
- Steel production
- Etc.



## 6000 SERIES

Code	Inner diameter	Diameter (D)	Width (W)	Weight	Speed Revs/min.	Static charge Kn
6000 ZZ ENC 200°C	10	26	8	20	6000	1,78
6001 ZZ ENC 200°C	12	28	8	25	5800	2,13
6002 ZZ ENC 200°C	15	32	9	30	5600	2,53
6003 ZZ ENC 200°C	17	35	10	40	5400	2,94
6004 ZZ ENC 200°C	20	42	12	69	5200	4,56
6005 ZZ ENC 200°C	25	47	12	80	4800	5,14
6006 ZZ ENC 200°C	30	55	13	120	4400	7,11
6007 ZZ ENC 200°C	35	62	14	160	4000	9,19
6008 ZZ ENC 200°C	40	68	15	190	3600	10,47
6009 ZZ ENC 200°C	45	75	16	250	3200	12,64
6010 ZZ ENC 200°C	50	80	16	260	2800	13,83
6011 ZZ ENC 200°C	55	90	18	390	2400	18,77
6012 ZZ ENC 200°C	60	95	18	420	2000	20,54

## 6200 SERIES

Code	Inner diameter	Diameter (D)	Width (W)	Weight	Speed Revs/min.	Static charge Kn
6200 ZZ ENC 200°C	10	30	9	30	5800	2,33
6201 ZZ ENC 200°C	12	32	10	37	5600	2,84
6202 ZZ ENC 200°C	15	35	11	45	5400	3,35
6203 ZZ ENC 200°C	17	40	12	65	5200	4,26
6204 ZZ ENC 200°C	20	47	14	110	4800	5,98
6205 ZZ ENC 200°C	25	52	15	130	4400	7,11
6206 ZZ ENC 200°C	30	62	16	200	4000	9,88
6207 ZZ ENC 200°C	35	72	17	290	3600	13,53
6208 ZZ ENC 200°C	40	80	18	370	3200	16,00
6209 ZZ ENC 200°C	45	85	19	410	2800	18,07
6210 ZZ ENC 200°C	50	90	20	460	2400	21,33
6211 ZZ ENC 200°C	55	100	21	610	2000	25,78
6212 ZZ ENC 200°C	62	110	22	780	1800	32,00

## 6300 SERIES

Code	Inner diameter	Diameter (D)	Width (W)	Weight	Speed Revs/min.	Static charge Kn
6300 ZZ ENC 200°C	10	35	11	52	5600	3,14
6301 ZZ ENC 200°C	12	37	12	60	5400	3,75
6302 ZZ ENC 200°C	15	42	13	80	5200	4,87
6303 ZZ ENC 200°C	17	47	14	120	4800	5,88
6304 ZZ ENC 200°C	20	52	15	140	4400	6,39
6305 ZZ ENC 200°C	25	62	17	225	4000	10,07
6306 ZZ ENC 200°C	30	72	19	350	3600	14,42
6307 ZZ ENC 200°C	35	80	21	450	3200	16,89
6308 ZZ ENC 200°C	40	90	23	620	2800	22,22
6309 ZZ ENC 200°C	45	100	25	830	2400	28,45
6310 ZZ ENC 200°C	50	110	27	1050	2000	33,78
6311 ZZ ENC 200°C	55	120	29	1350	1800	42,17
6312 ZZ ENC 200°C	60	130	31	1700	1600	46,22