



9330 OMNITRACK
HEAVY DUTY
BALL TRANSFER UNIT

4 HOLES \varnothing 8.1 THRO
C'BORE 4.2 DP @ 90° INCLUSIVE

Available Material Options			
Part #	Load Bearing Internal Materials	Ball Material	Casing Material & Finish
9330	AISI 52100	AISI 52100	AISI 1012 ZINC/ELECTROPHORETIC (BLACK)
9330 A	AISI 52100	AISI 440	AISI 1012 ZINC/ELECTROPHORETIC (BLACK)
9330 Z	AISI 440	AISI 440	AISI 1012 ELECTROPHORETIC (BLACK)
9330 SS	AISI 440	AISI 440	AISI 304 - NATURAL
9330 PB	PHENOLIC RESIN MAIN BALL OPTION AVAILABLE FOR ALL MATERIAL OPTIONS - 30 Kg / 65 Lbs		

~ Operating temperature -20° C + 125° C (continuous)

Removable & reusable 'Spirolox'
circlip allows cleaning/user servicing

LOAD CAPACITY 385 Kg / 850 Lbs

REVISION # 03

<p>ALL DIMENSIONS IN mm [inch] IF VIEWED AS PDF, DO NOT SCALE IF VIEWED AS DWG, SCALE 2 : 3 TOLERANCE \pm 0,25 [0.01] QMF 31 ISSUE 02: 09/01/2017</p>	<p>OMNITRACK RODBOROUGH COURT STROUD, GL5 3LR, ENGLAND</p>	<p>Telephone: +44 (0)1453 873 345 Fax: +44 (0)1453 878 500 info @ omnitrack.com www.omnitrack.com</p>	<p>THIS DOCUMENT CONTAINS OMNITRACK PROPERTY AND CONFIDENTIAL INFORMATION. IT IS LOANED FOR LIMITED PURPOSES ONLY AND REMAINS THE PROPERTY OF OMNITRACK. IT MAY NOT BE REPRODUCED IN WHOLE OR PART OR DISCLOSED TO THIRD PARTIES WITHOUT THE PRIOR WRITTEN CONSENT OF OMNITRACK. THE DOCUMENT IS TO BE RETURNED TO OMNITRACK UPON REQUEST AND IN ALL EVENTS UPON COMPLETION OF THE USE FOR WHICH IT WAS LOANED</p>
--	---	---	--

