

## V.CORTE



VÁLVULA MANUAL DE CORTE 3/2 VÍAS CON SILENCIADOR DE ESCAPE  
- Ball valves 3/2 ways with pressure relief and silencer

REFERENCIA	ROSCA	CAUDAL RECOMENDADO	TEMPERATURA DE TRABAJO	PRESIÓN ENTRADA
V.CORTE-200-1/4	G1/4"	550 l/min	0°C + 60°C	0-16 bar
V.CORTE-200-3/8	G3/8"	850 l/min	0°C + 60°C	0-16 bar
V.CORTE-300-1/2	G1/2"		-10°C +60°C	0-16 bar
V.CORTE-400-3/4	G3/4"	1900 l/min	-10°C +60°C	0-17,5 bar
V.CORTE-400-1	G1"	1900 l/min	-10°C +60°C	0-17,5 bar

## ANG



ÁNGULO DE FIJACIÓN  
- Mounting bracket

REFERENCIA
ANG-FIJ-100
ANG-FIJ-200
ANG-FIJ-300
ANG-FIJ-400
ANG-FIJ-500

## KIT



KIT DE UNIÓN  
- Assembling kit

REFERENCIA
KIT-100 (unión 2 cuerpos)
KIT-105 (unión 3 cuerpos)
KIT-200 (unión 2 cuerpos)
KIT-300 (unión 2 cuerpos)
KIT-400 (unión 2 cuerpos)
KIT-500 (unión 2 cuerpos)

## ACEITE



PURGA AUTOMÁTICA DE CONDENSACIÓN

REFERENCIA	LITRO
A-01	1