



- f = 0,3 ▶ d1 = 1-6
- f = 0,5 ▶ d1 = 6-12
- f = 0,8 ▶ d1 = 12-30
- f = 1,2 ▶ d1 > 30

Chafilán en función de d1
 Medidas según ISO 3547-1 y
 medidas especiales

Estructura - Ref.:
W F M-03 04 - 03



Referencia	d1*	d2	d3	b1	b2
			d13	h13	-0,14
WFM-0304-03	3,0	4,5	7,5	3,0	0,75
WFM-0304-05	3,0	4,5	7,5	5,0	0,75
WFM-0405-03	4,0	5,5	9,5	3,0	0,75
WFM-0405-04	4,0	5,5	9,5	4,0	0,75
WFM-0405-06	4,0	5,5	9,5	6,0	0,75
WFM-0506-08	5,0	6,0	10,0	8,0	0,50
WFM-0507-04	5,0	7,0	11,0	4,0	1,00
WFM-0507-05	5,0	7,0	11,0	5,0	1,00
WFM-0608-04	6,0	8,0	12,0	4,0	1,00
WFM-0608-06	6,0	8,0	12,0	6,0	1,00
WFM-0608-08	6,0	8,0	12,0	8,0	1,00
WFM-0608-10	6,0	8,0	12,0	10,0	1,00
WFM-0608-15	6,0	8,0	12,0	15,0	1,00
WFM-0709-12	7,0	9,0	15,0	12,0	1,00
WFM-0810-02	8,0	10,0	15,0	2,7	1,00
WFM-0810-05	8,0	10,0	15,0	5,5	1,00
WFM-0810-07	8,0	10,0	15,0	7,5	1,00
WFM-0810-09	8,0	10,0	15,0	9,5	1,00
WFM-0810-10	8,0	10,0	15,0	10,0	1,00
WFM-0810-23	8,0	10,0	15,0	23,0	1,00
WFM-0810-30	8,0	10,0	15,0	30,0	1,00
WFM-081015-05	8,0	10,0	15,0	5,0	1,00
WFM-1012-04	10,0	12,0	18,0	4,0	1,00
WFM-1012-05	10,0	12,0	18,0	5,0	1,00
WFM-1012-06	10,0	12,0	18,0	6,0	1,00
WFM-1012-07	10,0	12,0	18,0	7,0	1,00
WFM-1012-09	10,0	12,0	18,0	9,0	1,00
WFM-1012-10	10,0	12,0	18,0	10,0	1,00
WFM-1012-12	10,0	12,0	18,0	12,0	1,00
WFM-1012-15	10,0	12,0	18,0	15,0	1,00
WFM-1012-17	10,0	12,0	18,0	17,0	1,00
WFM-1214-04	12,0	14,0	20,0	4,0	1,00
WFM-1214-044	12,0	14,0	20,0	4,4	1,00
WFM-1214-06	12,0	14,0	20,0	6,0	1,00
WFM-1214-07	12,0	14,0	20,0	7,0	1,00
WFM-1214-09	12,0	14,0	20,0	9,0	1,00
WFM-1214-10	12,0	14,0	20,0	10,0	1,00
WFM-1214-11	12,0	14,0	20,0	11,0	1,00
WFM-1214-12	12,0	14,0	20,0	12,0	1,00
WFM-1214-15	12,0	14,0	20,0	15,0	1,00
WFM-1214-17	12,0	14,0	20,0	17,0	1,00
WFM-1214-20	12,0	14,0	20,0	20,0	1,00
WFM-1315-06	13,0	15,0	22,0	6,0	1,00
WFM-1416-04	14,0	16,0	22,0	4,0	1,00
WFM-1416-05	14,0	16,0	22,0	5,0	1,00

Referencia	d1*	d2	d3	b1	b2
			d13	h13	-0,14
WFM-1416-08	14,0	16,0	22,0	8,0	1,00
WFM-1416-12	14,0	16,0	22,0	12,0	1,00
WFM-1416-17	14,0	16,0	22,0	17,0	1,00
WFM-1416-29	14,0	16,0	22,0	29,0	1,00
WFM-1517-09	15,0	17,0	23,0	9,0	1,00
WFM-1517-12	15,0	17,0	23,0	12,0	1,00
WFM-1517-17	15,0	17,0	23,0	17,0	1,00
WFM-1517-20	15,0	17,0	23,0	20,0	1,00
WFM-1618-09	16,0	18,0	24,0	9,0	1,00
WFM-1618-12	16,0	18,0	24,0	12,0	1,00
WFM-1618-17	16,0	18,0	24,0	17,0	1,00
WFM-1719-12	17,0	19,0	25,0	12,0	1,00
WFM-1719-18	17,0	19,0	25,0	18,0	1,00
WFM-1719-25	17,0	19,0	25,0	25,0	1,00
WFM-1820-12	18,0	20,0	26,0	12,0	1,00
WFM-1820-17	18,0	20,0	26,0	17,0	1,00
WFM-1820-22	18,0	20,0	26,0	22,0	1,00
WFM-2023-11	20,0	23,0	30,0	11,5	1,50
WFM-2023-14	20,0	23,0	30,0	14,0	1,50
WFM-2023-16	20,0	23,0	30,0	16,5	1,50
WFM-2023-21	20,0	23,0	30,0	21,5	1,50
WFM-2427-10	24,0	27,0	32,0	10,0	1,50
WFM-2528-11	25,0	28,0	35,0	11,0	1,50
WFM-2528-16	25,0	28,0	35,0	16,0	1,50
WFM-2528-21	25,0	28,0	35,0	21,0	1,50
WFM-2528-30	25,0	28,0	32,0	30,0	1,50
WFM-252831-13	25,0	28,0	31,0	13,0	1,50
WFM-2830-36	28,0	30,0	35,0	36,0	1,00
WFM-3034-10	30,0	34,0	42,0	10,0	2,00
WFM-3034-16	30,0	34,0	42,0	16,0	2,00
WFM-3034-26	30,0	34,0	42,0	26,0	2,00
WFM-3034-37	30,0	34,0	42,0	37,0	2,00
WFM-3236-16	32,0	36,0	40,0	16,0	2,00
WFM-3236-26	32,0	36,0	40,0	26,0	2,00
WFM-3539-16	35,0	39,0	47,0	16,0	2,00
WFM-3539-26	35,0	39,0	47,0	26,0	2,00
WFM-353950-35	35,0	39,0	50,0	35,0	2,00
WFM-3842-22	38,0	42,0	50,0	22,0	2,00
WFM-4044-30	40,0	44,0	52,0	30,0	2,00
WFM-4044-40	40,0	44,0	52,0	40,0	2,00
WFM-4550-50	45,0	50,0	58,0	50,0	2,00
WFM-5055-40	50,0	55,0	63,0	40,0	2,00
WFM-5055-50	50,0	55,0	63,0	50,0	2,00
WFM-5560-60	55,0	60,0	68,0	60,0	2,00
WFM-5762-40	57,0	62,0	67,0	40,0	2,00

* Tolerancias estándar para iglidur® W300: E10 tras montaje a presión en alojamiento H7

