

ELECTRIC DRIVEN GREASE LUBRICATOR

Electric Driven Grease Lubricators

The KPL-24 is an electrically powered grease lubricator specifically designed for use on heavy construction machinery. It is powered by the internal DC 24V batteries standard in most heavy vehicles. The KPL-24 is compact, sturdy and provides maximum portability on any work site especially where there are no other readily available power sources. It will fit onto standard 18 liter grease pails. It has a high discharge pressure and is capable of pumping grease of various viscosities. A variety of accessories are available including different length hoses, power cords, reels and metering devices. This pump is very efficient and a good option for any worksite. AC240V powered version is also available.



880639
KPL-24



※ Grease container is not included.



880899
EPL-100
881081
EPL-240




※ Grease container is not included.

880639 KPL-24 ELECTRIC DRIVEN GREASE LUBRICATOR DC-24V

SPECIFICATIONS

MODEL NO.	MODEL	CONTAINER	POWER SOURCE	MAX FREE FLOW	MAX OUTPUT PRESSURE	ACCESSORIES	NET WEIGHT (kg)	MEASUREMENT (m ³)
880639	KPL-24	18 PAIL	DC24V 100~300W 2~7.5A	120 M ³ /min	28MPa (280kgf/cm ²)	852164 HPG-G13 H.P. GREASE DISPENSE VALVE 803085 FOLLOWER PLATE POWER CODE 2.5M	12	0.0494

Dimensions (mm)



880899/881081 EPL-100/EPL-240 ELECTRIC DRIVEN GREASE LUBRICATOR AC100V/240V

SPECIFICATIONS

MODEL NO.	MODEL	CONTAINER	POWER SOURCE	MAX FREE FLOW	MAX OUTPUT PRESSURE	ACCESSORIES	NET WEIGHT (kg)	MEASUREMENT (m ³)
880899	EPL-100	18 PAIL	AC100V 200W 1~3A	190 M ³ /min	28MPa (280kgf/cm ²)	852164 HPG-G13 H.P. GREASE DISPENSE VALVE 695034 SKR-2.5M H.P. GREASE HOSE 1/4"× 2.5M 803085 FOLLOWER PLATE POWER CODE 2.5M	12	0.0494
881081	EPL-240		AC240V 200W 1~3A					

Dimensions (mm)

