

CARACTERÍSTICAS TÉCNICAS



DRblue

Impulsor multicanal abierto

| MODELO | Potencia | | Voltaje (v) ~1 | Intensidad (a) ~1 | Rev./min. | Ø | Paso libre (mm) |
|--------------|----------|------|-------------------|----------------------|-----------|--------|-----------------|
| | KW | HP | | | | | |
| DRblue 50 M | 0,37 | 0,5 | 220 | 2,8 | 2900 | 1 1/4" | 12x7 |
| DRblue 75 M | 0,55 | 0,75 | 220 | 4,1 | 2900 | 1 1/4" | 12x7 |
| DRblue 100 M | 0,74 | 1,0 | 220 | 5,6 | 2900 | 1 1/4" | 12X7 |

| MODELO | Q m³/h | 3 | 6 | 9 | 12 | 15 | 18 | 21 |
|-------------|----------|------|------|-----|-----|-----|-----|-----|
| | l/min. | 50 | 100 | 150 | 200 | 250 | 300 | 350 |
| DRblue 50M | H mts | 9 | 8 | 6 | 4 | 2 | | |
| DRblue 75M | | 11,5 | 10,2 | 9 | 7 | 4 | 2 | |
| DRblue 100M | | 14 | 13 | 11 | 9,5 | 7 | 5 | 2 |

TABLA DE DIMENSIONES Y PESOS

| MODELO | DIMENSIONES EN MM | | | | | | PESO KG |
|------------|-------------------|-----|-----|--------|-----|-----|------------|
| | A | B | C | D | E | F | |
| DRblue 50 | 289 | 114 | 110 | 1 1/4" | 150 | 257 | 12,0 |
| DRblue 75 | 317 | 114 | 110 | 1 1/4" | 150 | 257 | 13,5 |
| DRblue 100 | 317 | 114 | 110 | 1 1/4" | 150 | 257 | 14,0 |

