

Avellanadores 60°

M35-HSS-E
Co5
DIN 334C



| Código | Diámetro cabecera | Diámetro menor | Diámetro mango | Longitud total | Longitud mín cabecera | Longitud mín mango | Peso | HSS-E | TIN | TICN |
|--------------|----------------------|-------------------|-------------------|-------------------|--------------------------|-----------------------|-------|-------|-----|------|
| | mm | mm | mm | mm | mm | mm | kg | | | |
| 334C-6.3-60 | 6.3 | 1.6 | 5 | 45 | 6.3 | 28 | 0.010 | | | |
| 334C-8-60 | 8 | 2 | 6 | 50 | 8 | 36 | 0.013 | | | |
| 334C-12.5-60 | 12.5 | 3.2 | 8 | 56 | 11.2 | 36 | 0.025 | | | |
| 334C-16-60 | 16 | 4 | 10 | 63 | 14 | 40 | 0.041 | | | |
| 334C-20-60 | 20 | 5 | 10 | 67 | 17 | 40 | 0.049 | | | |
| 334C-25-60 | 25 | 6.3 | 10 | 71 | 20 | 40 | 0.060 | | | |

Avellanadores para tornillo ALLEN

M35-HSS-E
Co5
DIN 373



| | Código | Diámetro dirección | Diámetro del filo | Longitud del filo | Longitud total incluyendo dirección | Diámetro del mango | Peso | HSS-E | TIN | TICN |
|-------------|---------------|-----------------------|----------------------|----------------------|--|-----------------------|-------|-------|-----|------|
| | | mm | mm | mm | mm | mm | kg | | | |
| M3 | 373-3.2-6.0 | 3.2f | 6.0 | 14 | 71 | 5.0 | 0.011 | | | |
| M3.5 | 373-3.7-6.5 | 3.7f | 6.5 | 14 | 71 | 5.0 | 0.011 | | | |
| M4 | 373-4.3-8.0 | 4.3f | 8.0 | 14 | 71 | 5.0 | 0.013 | | | |
| M5 | 373-5.3-10.0 | 5.3f | 10.0 | 18 | 80 | 8.0 | 0.029 | | | |
| M6 | 373-6.4-11.0 | 6.4f | 11.0 | 18 | 80 | 8.0 | 0.030 | | | |
| M8 | 373-8.4-15.0 | 8.4f | 15.0 | 22 | 100 | 12.5 | 0.080 | | | |
| M10 | 373-10.5-18.0 | 10.5f | 18.0 | 22 | 100 | 12.5 | 0.090 | | | |
| M12 | 373-13.0-20.0 | 13.0f | 20.0 | 22 | 100 | 12.5 | 0.100 | | | |

NOTA: Recubrimientos Titanio y TICN bajo Pedido.