

13. LUBRICATION AND GREASING

Greasing pumps and accessories	p. 344
Manual pumps	p. 345
Pneumatic oil pumps	p. 347
Pneumatic fluid pumps	p. 347
Mobile oil dispensers	p. 346
Hose reels	p. 348
Used oil equipment	p. 348
Greasing equipment	p. 349
Oil pump kits	p. 349
Oil control guns	p. 350
Lubrication systems	p. 350



>>> Greasing pumps and accessories

Grease pumps and accessories

At www.rodavigo.net Family: Lubrication and greasing
Product: Lubrication-Greasing



Description: High pressure high flow greasing pump specially designed for work in extreme conditions or when high grase deliveries are required in a short time.

Code	Product	Maximum Pressure	For greases until	Flow
29155200GC	Pneumato 55/200 -G-C	440	NLGI-2	5 kg/minute
29110200GC	Pneumato 10/200 GC	80	NLGI-2	5 kg/minute
29175200	Pneumato 75/200	600	NLGI-3	1 kg/minute



Description: Description: High capacity reels made of varnished sheet metal. Exit window with PVC rollers. They are delivered with a rubber stop.

Code	CAR/A-GC-16
291CARAGC16	Maximum pressure: 45 bar. Capacity up to 15 m. DN 06 Window with PVC rollers.



Code	CAR/A-GC-25
291CARAGC25	Maximum pressure: 40 bar. Capacity up to 30 m. DN 25




Code AT-503.
Greaser

291AT5036100	Thread 6-100.
291AT5037100	Thread 7-100.
291AT5038100	Thread 8-100.
291AT5038125	Thread 8-125.
291AT50310100	Thread 10-100.
291AT50310125	Thread 10-125.
291AT50310150	Thread 10-150.
291AT50312100	Thread 12-100.
291AT50312125	Thread 12-125.
291AT50312150	Thread 12-150.
291AT50312175	Thread 12-175.
291AT50314W	Thread 1/4W.
291AT503516W	Thread 5-16W.
291AT50338W	Thread 3-8W.
291AT50314	Thread 1/4 SAE.
291AT503516	Thread 5/16 SAE.
291AT50338	Thread 3/8 SAE.
291AT50318	Thread 1/8 GAS.
291AT50314G	Thread 1/4 GAS.



Code AT-506.
45° greaser

291AT5066100	Thread 6-100.
291AT5067100	Thread 7-100.
291AT5068100	Thread 8-100.
291AT5068125	Thread 8-125.
291AT50610100	Thread 10-100.
291AT50610125	Thread 10-125.
291AT50610150	Thread 10-150.
291AT50612100	Thread 12-100.
291AT50612125	Thread 12-125.
291AT50612150	Thread 12-150.
291AT50612175	Thread 12-175.
291AT50614W	Thread 1/4W.
291AT506516W	Thread 5-16W.
291AT50638W	Thread 3-8W.
291AT50614	Thread 1/4 SAE.
291AT506516	Thread 5/16 SAE.
291AT50638	Thread 3/8 SAE.
291AT50618	Thread 1/8 GAS.
291AT50614G	Thread 1/4 GAS.



Code AT-508.
90° greaser


291AT5086100	Thread 6-100.
291AT5087100	Thread 7-100.
291AT5088100	Thread 8-100.
291AT5088125	Thread 8-125.
291AT50810100	Thread 10-100.
291AT50810125	Thread 10-125.
291AT50810150	Thread 10-150.
291AT50812100	Thread 12-100.
291AT50812125	Thread 12-125.
291AT50812150	Thread 12-150.
291AT50812175	Thread 12-175.
291AT50814W	Thread 1/4W.
291AT508516W	Thread 5-16W.
291AT50838W	Thread 3-8W.
291AT50814	Thread 1/4 SAE.
291508516	Thread 5/16 SAE.
291AT50838	Thread 3/8 SAE.
291AT50818	Thread 1/8 GAS.
291AT50814G	Thread 1/4 GAS.



Code DIN 71412.B
45° greaser

29171412B66100	Thread 6-100
29171412B8100	Thread 8-100
29171412B1010100	Thread 10-100

Conical thread
Hardened head. Bichromated.



Code DIN 71412.C.
90° greaser

29171412C66100	Thread 6-100
29171412C8100	Thread 8-100
29171412C1010100	Thread 10-100

Conical thread
Hardened head. Bichromated.



Code DIN 71412.
Conical thread oiler

29171412A66100	AM 6. Thread 6-100
29171412A8100	AM 8. Thread 8-100
29171412A1010100	AM 10. Thread 10-100

Conical thread
Hard. Bichromated.



Code AT-503.
Greaser

291AT5036	Pressure 6 mm.
291AT5038	Pressure 8 mm.
291AT50310	Pressure 10 mm.



Code AT-505.
Long greaser

2915056100	Thread 6-100.
29150514	Thread 1/4 SAE.

Assorted box of greasers. Very useful. They facilitate the service by containing the most commonly used models. NOTE: Other compositions are possible on request.

BOX 1 Code 291BOX1

Total content: 280 pieces.

Composition:

Thread	AT-503	AT-506	AT-508
6-100	75	20	0
8-100	40	20	0
10-100	50	25	0
1/8 GAS	50	0	0



BOX 2 Code 291BOX2

Total content: 485 pieces.

Composition:

Thread	AT-503	AT-506	AT-508
6-100	100	25	25
8-100	50	25	25
10-100	40	25	25
1/8 GAS	40	25	25
1/4 GAS	25	15	15




BOX 3 Code 291BOX3

Total content: 765 pieces.

Composition:

Thread	AT-503	AT-506	AT-508
6-100	100	25	25
8-100	50	25	25
8-125	50	25	25
10-100	50	25	25
1/4 SAE	100	25	25
1/8 GAS	50	25	25
1/4 GAS	25	20	20




>>> Greasing pumps and accessories

At www.rodavigo.net Family: Lubrication and greasing
Product: Lubrication-Greasing

Greasing pumps and accessories


(Material: 1.4305 / AISI 303 / V2A)

Code **Stainless steel Greasers.**




29171412A6I	DIN 71412 AM6
29171412A8II	DIN 71412 AM8
29171412A8125I	DIN 71412 AM8 x 1,25
29171412A10I	DIN 71412 AM10
29171412A18GI	FORM DIN 71412 A 1/8 GAS
29171412A14GI	FORM DIN 71412 A 1/4 GAS
29171412B6I	DIN 71412 BM6
29171412B8II	DIN 71412 BM8
29171412B10I	DIN 71412 BM10
29171412B18GI	FORM DIN 71412 B 1/8 GAS
29171412B14GI	FORM DIN 71412 B 1/4 GAS
29171412C6I	DIN 71412 CM6
29171412C8II	DIN 71412 CM8
29171412C10I	DIN 71412 CM10
29171412C18GI	FORM DIN 71412 C 1/8 GAS
29171412C14GI	FORM DIN 71412 C 1/4 GAS

Code **STAUFFER BRASS**



291SL118G	Nº 1. Thread 1/8 GAS.
291SL218G	Nº 2. Thread 1/8 GAS.
291SL214G	Nº 2. Thread 1/4 GAS.
291SL314G	Nº 3. Thread 1/4 GAS.
291SL418G	Nº 4. Thread 1/8 GAS.
291SL514G	Nº 5. Thread 1/4 GAS.
291SL614G	Nº 6. Thread 1/4 GAS.
291SL738G	Nº 7. Thread 3/8 GAS.




Code **UNIKUM. Drip lubricators.**

291UNIKUM1	1. Thread 1/4. Capacity 20 cm ³ . Plexiglas.
291UNIKUM2	2. Thread 1/4. Capacity 38 cm ³ . Plexiglas.
291UNIKUM3	3. Thread 3/8. Capacity 70 cm ³ . Plexiglas.
291UNIKUM4	4. Thread 3/8. Capacity 125 cm ³ . Plexiglas.
291UNIKUM5	5. Thread 1/2. Capacity 220 cm ³ . Plexiglas.
291UNIKUM6	6. Thread 1/2. Capacity 310 cm ³ . Plexiglas.
291UNIKUM7	7. Thread 3/4. Capacity 480 cm ³ . Glass.
291UNIKUM8	8. Thread 3/4. Capacity 660 cm ³ . Glass.
291UNIKUM9	9. Thread 3/4. Capacity 970 cm ³ . Glass.

Code **Vessels for UNIKUM..**

291VP1	VP-1
291VP2	VP-2
291VP3	VP-3
291VP4	VP-4
291VP5	VP-5
291VP6	VP-6
291VC7	VC-7
291VC8	VC-8
291VC9	VC-9


Code



AT-150. Greaser flat head former. 15 mm.

291AT150156100	Thread 6-100.
291AT1507100	Thread 7-100.
291AT150158100	Thread 8-100.
291AT150158125	Thread 8-125.
291AT15010100	Thread 10-100.
291AT15010125	Thread 10-125.
291AT1501510150	Thread 10-150.
291AT1501512100	Thread 12-100.
291AT1501512125	Thread 12-125.
291AT1501512150	Thread 12-150.
291AT1501512175	Thread 12-175.
291AT1501514200	Thread 14-200.
291AT1514W	Thread 1/4W.
291AT150516W	Thread 5/16W.
291AT15038W	Thread 3/8 W.
291AT150716W	Thread 7/16 W.
291AT15012	Thread 1/2 W.
291AT1514	Thread 1/4 SAE.
291AT150516	Thread 5/16 SAE.
291AT15038	Thread 3/8 SAE.
291AT15018G	Thread 1/8 GAS.
291AT1501514G	Thread 1/4 GAS.

Code



AT-873. Greased type "lub".

291AT8735080	Thread 5-080.
291AT8736100	Thread 6-100.
291AT8738125	Thread 8-125.
291AT87310100	Thread 10-100.
291AT87310150	Thread 10-150.
291AT87338W	Thread 3/8W.
291AT87318G	Thread 1/8 GAS.
291AT87314	Thread 1/4 GAS.
291AT87338G	Thread 3/8 GAS.
291AT8736	Pressure 6 mm.
291AT8738	Pressure 8 mm.

Code



AT-862. Greaser ind. mac.

291AT8626	Pressure 6 mm.
291AT8628	Pressure 8 mm.
291AT86210	Pressure 10 mm.
291AT86212	Pressure 12 mm.


Code



AT-156. Greaser flat head Øhead. 16 mm.

291AT1561610100	Thread 10-100.
291AT1561618	Thread 1/8 GAS.
291AT1561614	Thread 1/4 GAS.

Code




AT-157. Greaser flat head Øhead. 22 mm.

291AT1572214	Thread 1/4 GAS.
291AT1572238	Thread 3/8 GAS.

>>> Manual pumps

Manual pumps




Code

291E503MN

E 503/MN

Lever greasing pump.
Equipped with pressure gauge (0-400 bar) for pressure control.
Capacity: 500g
Thread 1/8 Gas.



Code

291E500

E 500 (Capacity 500 cm³)

Lever greasing pump.
Bulk cargo, by aspiration, with cartridge or with eco-FILL dispenser.
Non-slip rod clamping system, fully effective, with purge and ergonomic PVC handle.
It is served in a recyclable cardboard box.
Thread 1/8 Gas.




>>> Manual pumps

Manual pumps


At www.rodavigo.net Family: Lubrication and greasing
Product: Lubrication-Greasing

Code
291E600R




E 600/R
Greasing pump with identical characteristics as the E 600. Equipped with rigid coupling E 4024

Code
291E500R




E 500/R
Greasing pump with identical characteristics as the E 500 (page 507). Equipped with rigid coupling E 4024

Code
291E600F1



E 600/F1
Greasing pump with identical characteristics as the E 600. Equipped with flexible coupling AFH-4/1-340.

Code
291E500F1



E 500/F1
Greasing pump with identical characteristics as the E 500. Equipped with flexible coupling AFH-4/1-340.

Code
291C400G



C 400G
K2K-30 multipurpose grease cartridge
Capacity 400 g
Temperature -30° to 120°C

Code
291E600



E 600 (Capacidad 600 cm³)
Lever greasing pump.
Bulk cargo, by aspiration, with cartridge or with eco-FILL dispenser. Non-slip rod clamping system, fully effective, with purge and ergonomic PVC handle. It is served in a cardboard box. Thread 1/8 Gas

>>> Pneumatic oil pumps

Pneumatic oil pumps



Pneumatic pumps for lubricants.

Equipped with double screw cap. For wall. MATO recommends always using a regulator-purifier filter in the air line.

PNEUMATO 1/P. (25 l./min.)

Code 2911P

PNEUMATO 3/P. (18 l./min.)

Code 2913PPN

PNEUMATO 5/P. (17 l./min.)

Code 2915P



Mobile equipment for oil service.

Of identical characteristics to the previous one, but for 200 liter drums.

MOBILE 200/3. With PNEUMATO 3 pump.

Code 291MOBILE2003

MOBILE 200/5. With PNEUMATO 5 pump.

Code 291MOBILE2005



Mobile equipment for oil service.

For 50 liter drums. It consists of PNEUMATO pump, trolley, flange, service hose, length 2 m., PAM gun, accessories for connection to the air network and pressure regulator.

MOBILE 50/1. With PNEUMATO 1 pump.

Code 291MOBILE501

MOBILE 50/3. With PNEUMATO 3 pump.

Code 291MOBILE503

MOBILE 50/5. With PNEUMATO 5 pump.

Code 291MOBILE505



Mobile equipment for oil service.

For 200 liter drums. It consists of PNEUMATO pump, trolley, reel, service hose length 15m., DIGIMET counter gun, pressure regulator and accessories for the air connection.

MOBILE 200 / C3. With PNEUMATO 3 pump.

Code 291MOBILE200C3

MOBILE 200 / C5. With PNEUMATO 5 pump.

Code 291MOBILE200C5

>>> Pneumatic fluid pumps

At www.rodavigo.net

Family: Lubrication and greasing
Product: Lubrication-Greasing

Pneumatic greasing pumps



For multi-purpose and high-performance bio-greases up to NLGI Class 2 DIN 51818

PNEUMATO greasing pumps

Just plug it into the air and as soon as you run the gun, will start to pump. Long life, high operating pressure, great delivery, Reliable and complete pneumatic control, robust construction and low noise level (<64 dBA) are its most notable advantages.

Its intelligent design makes the number of moving parts minimal and also very simple to use.

Thanks to its high 55: 1 ratio, the PNEUMATO 55 pump achieves a number of performance well above average and that is why they are used in the industry, for repairs and service, in agriculture, automotive, forestry, etc. whenever powerful and safe lubrication equipment is required.

It is always recommended to use a filter-regulator-lubricator position in the air line.

BSP (GAS) threads.


TECHNICAL DATA

Operating data with NLGI class 2 multipurpose grease DIN 51818 standard approx. to 18 degrees

Code	Technical data
2915525	Pneumato 55/25 For drum 18/25 Kg (35/55 lbs.)
2915550	Pneumato 55/50 For drum 50/60 Kg (105/130 lbs.)
29155200	Pneumato 55/200 For drum 185/200 Kg (400 lbs.)

	PNEUMATO 55/25	PNEUMATO 55/50	PNEUMATO 55/200
Model	10-25 Kg	50 Kg	200 Kg
Pressure ratio	1:55	1:55	1:55
Air pressure min./max.	4 a 8 bar	4 a 8 bar	4 a 8 bar
Max pressure at 8 bar	425 bar	425 bar	425 bar
Air inlet thread	1/4" (H)	1/4" (H)	1/4" (H)
Weight	approx. 5.20 Kg	approx. 6.20 Kg	approx. 7.15 Kg.
Suction tube length	500 mm.	700 mm	880 mm
Max int deposit height	420 mm.	620 mm	835 mm


These pumps are designed to be used as directed. For your safety, follow the instructions. Use only original accessories. Check the pump regularly and replace defective parts without delay. Never point at yourself or others with high pressure lubrication equipment.



>>> Mobile oil dispensers


Pneumatic greasing pumps

Code 291TG500S TG-500-S



Greasing gun for one-hand work. Bulk cargo, by aspiration or with cartridge. It is equipped with a straight rigid coupling and a 24 nozzle. Pressure 300 bar. 2 exit ways (vertical / horizontal). Thread 1/8 Gas.

Code 291TG500F TG-500-F



Pump with the same characteristics as the TG-500-S, but equipped with flexible coupling AFH-4 / 1-340.

Code 291ECOFILL eco-FILL Standard



Grease dispenser for lever pumps with charging valve. It consists of a charge pump, dust cover and follower plate. Adaptable to 20 kg drums. For other drums consult.

MATOMAT

Code 291H5
Code 291H10



MATOMAT H-5.
MATOMAT H-10.

New and modern system for lubrication when not have close to air or electricity. It is made up of a pump adaptable to a drum, follower plate, cover and service pump, which is recharged through the bleed and fill valve. Service pump incorporates rigid straight coupling with nozzle and reaches up to 200 bar pressure. The capacity of the service pump is 130 cm³.

Code 291BG20S BG 20-S



Manual greasing equipment adaptable to 20 kg drums Pressure up to 400 bar Delivers 1.3 cm³ per bolus. The equipment consists of a pump, a plate, a 3.5 m long flexible coupling and a 4-clamp greasing nipple.

Code 291FP6 FP-6



Industrial pedal greasing pump. Very simple charging system. It incorporates a follower plate for the perfect compaction of the grease. Capacity of 6 Kg. It is equipped with flexible coupling AFH 4 / 1-2,000.

>>> Hose reels

Manual pumps

At www.rodavigo.net Family: Lubrication and greasing
Product: Lubrication-Greasing

Code 291CARLUFT


CARLUFT



Fairing reel for air and water.
Its design allows work in various workstations
and in different positions.
Ultralight with 11m of Ø8x12 hose, with stopper and
1.5 m. Ø1 / 4 "connection hose.
Threads: 1/4 ".
Working pressure: 20 bar.

Code 291CARG38


CAR/G-3/8



Open hose reel for air hose and
Water. Ø3 / 8 ".
Capacity up to 15 m.
Resistance: 220 bar.
With movable arms to fix the outlet in different
positions.
Without hose.


Code 291CARCC38

CARC/C-3/8



Fairing reel with identical characteristics to
the previous one.
High resistance steel caps.
Without hose.

Code 2913532130



Pivoting support for CAR / G reels.
Valid for all open and fairings types.
Turn up to 175°.

Code 291RCL

RCL



Entry ball joint for CAR / G-3/8 and CAR / G / C-3/8 reel.
3/8 "thread.

Code 291TPL

TPL


Rubber stop for CAR / G-3/8 and CAR / G / C-3/8 reel.

>>> Used oil equipment

Manual pumps



Code 291VAC




VAC

Portable equipment for oil recovery by
aspiration (pneumatic operation) or by
decantation (by funnel).
Technical data:
Tank capacity: 80 liters.
Pressure / Depression: + 0.95 / -0.6 bar.
8 liter capacity display container.
Equipped with 3 special probe holders and
six interchangeable 5, 6 and 8 mm probes.
With wheels for easy handling.

Code 291VAC10


VAC/10



Portable equipment for oil recovery
by aspiration (electrical operation).
Technical data:
Motor power: 1/8 HP.
Voltage: 220V / 50Hz.
Evacuation pressure: +3 bar.
Depression: -0.9 / -0.8 bar.
Visor container of 10 liters of capacity.
Equipped with in-line filter for separation
of impurities, probe holders and three
interchangeable 3.5 and 6 mm probes.
Inverter switch for suction / emptying.
With wheels for easy handling.

Code 291VAC60


VAC/60



Portable equipment for oil
recovery by aspiration
(electrical operation) or by
decantation (by funnel).
Identical technical
characteristics to VAC/10.
Capacity: 60 liters.
With wheels (2 swivel) for
easy handling.

Code 291RAF95

RAF-95




Tray for oil recovery in pit.
Optimal anti-splash design.
Large surface grill with
ability to place
filters, plugs, tools, etc.
Capacity: 95 liters.
Gravity discharge
or by pump.

>>> Greasing equipment

At www.rodavigo.net Family: Lubrication and greasing
Product: Lubrication-Greasing

Greasing equipment

Code: 291MOBILE200C3 **MOBILE 200/C3.** With ratio pump 1:3.
Code: 291MOBILE200C5 **MOBILE 200/C5.** With ratio pump 1:5.



Mobile equipment for oil service.
For 200 liter drums.
It consists of a PNEUMATO pump, bottle cage trolley, connecting hose, reel, hose service 15 m long, DIGIMET counter gun, pressure regulator and accessories for air connection.

Code: 291MOBILE501 **MOBILE 50/1.** With ratio pump 1:1.
Code: 291MOBILE503 **MOBILE 50/3.** With ratio pump 1:3.
Code: 291MOBILE505 **MOBILE 50/5.** With ratio pump 1:5.



Mobile equipment for oil service.
For 50 liter drums.
It consists of a PNEUMATO pump, trolley, flange, service hose, length 2m, PAM gun, accessories for connecting to the air network and a pressure regulator.

Code: 291RP100ME **RP-100-M**



Portable equipment for 50/60 liter drums.
Composed by RP-100-d pump, 1.2 m. hose service and outlet valve and bottle cage.
Valid for diesel, motor oil, gear oil and hydraulic oil up to SAE 90.
Capacity: 250 cm³ per lap.

Code: 291MOBILE2003 **MOBILE 200/3.** With ratio pump 1:3.
Code: 291MOBILE2005 **MOBILE 200/5.** With ratio pump 1:5.



Mobile equipment for oil service.
With identical characteristics to the previous one (MOBILE 50), but for 200 liter drums.

>>> Oil pump kits

Manual pumps

Code: 291WOD80 **WOD-80**

Oil recovery by decantation.
With height adjustable funnel.
Four wheels, two of them swivel, for easy handling.
Funnel: Ø500 mm.
With level to check availability of the deposit.
Equipped with 2m of hose for pressure emptying.



Code: 29120S **centra-FILL 20-s.** For drums of 18/20 kg
Code: 29125S **centra-FILL 25-s.** For drums of 25 kg
Code: 29150S **centra-FILL 50-s.** For drums of 50 kg

Static manual equipment for filling greasing stations.
Composed of cover pump, follower plate, 2m of PVC hose and S / ISO connection standard 7241B DN6R61 / 4.




Code: 29120M **centra-FILL 20-M.** For drums of 18/20 kg
Code: 29125M **centra-FILL 25-M.** For drums of 25 kg
Code: 29150M **centra-FILL 50-M.** For drums of 50 kg

Manual portable equipment for filling greasing stations.
Composition identical to the Centra-FILL standard, but with the incorporation of a bottle cage trolley.



Code: 29120D **pneumato-FILL 20-d.** For drums of 18/20 kg
Code: 29125D **pneumato-FILL 25-d.** For drums of 25 kg
Code: 29150D **pneumato-FILL 50-d.** For drums of 50 kg

Pneumatic static equipment for filling greasing stations.
Pump ratio 1: 3. Delivery at 8 bar: 1,800 g / m.
Composed of pump, cover, follower plate, 2m of PVC hose and S / ISO connection standard 7241B DN6R61 / 4.
For NLGI 2 grease.



Code: 29120P **pneumato-FILL 20-p.** For drums of 18/20 kg
Code: 29125P **pneumato-FILL 25-p.** For drums of 25 kg
Code: 29150P **pneumato-FILL 50-p.** For drums of 50 kg

Pneumatic portable equipment for filling greasing stations.
Composition identical to the pneumato-FILL, but with the incorporation of a bottle cage trolley.



>>> Oil control guns

Oil control guns

At www.rodavigo.net Family: Lubrication and greasing
Product: Lubrication-Greasing

PAM

- Code: 2913540029 Gun
- Code: 2913540180 Gun with rigid outlet and anti-drip.
- Code: 2913540210 Gun with rigid output for gear oil.
- Code: 2913540340 Gun with flexible outlet and anti-drip.



Lubricant supply gun.
It is served with a swivel rod end.



DIGIMET E35 pistol Code: 291PISDIGE35

Digital counter gun for lubricant supply.
Maximum flow: 40 liters / minute.
Maximum working pressure: 40 bar (580 psi).
Accuracy: ± 0.5%.
Counts liters, gallons, quarts or pints.
It is served with a rod end.

- Code: 2913540258 Rigid outlet for engine oil with anti-drip.
- Code: 2913540272 Rigid outlet for gear oil.
- Code: 2913540296 Non-drip flexible outlet.



DIGIMET E35M meter

- Code: 291E150 Electronic digital meter for lubricant.
- Maximum flow: 40 liters / minute.
6-digit partial and total indicators
(2 decimal places).
Auto power off.



Rigid curved outlet without dripping for gear oil.

Code: 2913540272

Rigid curved outlet with anti-drip for motor oil.

Code: 2913540500

Flexible outlet with manual anti-drip for engine oil.

Code: 2913540524

>>> Lubrication systems

Lubrication systems

ACEITERA INDUSTRIAL

- Code: 2919501 950/1. Capacity 250 cm³
 - Code: 2919502 950/2. Capacity 400 cm³
- Steel body and brass pump.
It is served with spikes, rigid and flexible.



- PREMIUM oilcan HDPE 300 cm³**
Code: 2913308070
 - PREMIUM oilcan HDPE 500 cm³**
Code: 2913308100
- PREMIUM HDPE OILCAN**
Superior quality oilcan for professional use in all areas of maintenance and service.
High-density polyethylene body.
High quality brass double pumping mechanism.
With rotating suction system.
It allows working in any position.



- PREMIUM Atomizer HDPE 300 cm³**
Code: 2913308445
 - PREMIUM Atomizer HDPE 500 cm³**
Code: 2913308506
- PREMIUM HDPE Atomizer.**
Superior quality atomizer for professional use in all areas of maintenance and service.
High-density polyethylene body.
High quality brass double pumping mechanism.
With rotating suction system.
For fluid oils, petroleum and others non-corrosive liquids.
It allows working in any position.



- SK-PE 125 (Capacity 125 cm³)**
Code: 291SKPE125
 - SK-PE 250 (Capacity 250 cm³)**
Code: 291SKPE250
- Plastic oil sprayer.**
Translucent polyethylene tank and brass spike.



BUTTON TYPE OILCANS

- Code: 291AB250 AB - 250. Capacity 250 cm³
- Code: 291AB350 AB - 350. Capacity 350 cm³
- Code: 291AB750 AB - 750. Capacity 750 cm³



- Code: 291SKPE125 **SK-PE 125**
Pressure oiler. Capacity 125 cm³.
Polyethylene tank and brass spout.

